

This Certificate is issued under the authority of the Province of Saskatchewan

**A209956**

Station #: 71095  
Technician #: 83671  
Signing Officer #: 87242

Station Name: Prairie Diesel Inc.  
Technician Name: Joseph J. Dosch  
Signing Officer Name: Amanda Dosch

**Customer Details:**

Name: [REDACTED] Address: [REDACTED]

Inspection Completed Date: 28Jan2026

Inspection Expiry Date: 31Jul2026

**Vehicle Details:**

VIN: 2HSCEAPR55C158107

Odometer Reading: 1052712 km

Year: 2005

Vehicle Make/Model: INTERNATIONAL/HEAVY VEHICLE

Plate:

Jurisdiction:

Unit:

**Message(s):** VIN has been validated.

This certificate does not warranty or guarantee the condition of this vehicle's components and systems for any period of time.



Vehicle Standards and Inspection

## Power Unit Record of Inspection

The Record of Inspection must be given to the customer regardless of whether the vehicle passes or fails.

Station #: 71095

Station Name: Prairie Diesel Inc.

Technician #: 83671

Technician Name: Joseph J. Dosch

Signing Officer #: 87242

Signing Officer Name: Amanda Dosch

Customer Details:

Name: [REDACTED]

Address: [REDACTED]

Vehicle Details:

VIN: 2HSCEAPR55C158107

Odometer Reading: 1052712 km

Year: 2005

Vehicle Make/Model: INTERNATIONAL HEAVY VEHICLE

Inspection Details:

Pass	Rejected	Corrected	Req Attn	DRIVERS COMPARTMENT	Comments
x				Vehicle Identification (5)	
x				Sun Visor Interior (8)	
x				Horn Operation (5)	
x				Mirrors (8)	
x				Windshield Wipers/Washers (8)	
x				Windshield Defroster/Heater (8)	
x				Windshield/Other Glass (8)	
x				Gear Position Indicator & Neutral Switch (1)	
x				Instrument Lamps (6)	
x				Accessibility Features/Equip (5)	
x				Auxiliary Heaters (5)	
x				Auxiliary Drive Controls (5)	
x				Emergency Exits (8)	
x				Floor/Step Well Covering (8)	
x				Service/Exit Doors (8)	
x				Indicator Lamps (5)	
x				Instruments/Gauges (5)	
x				Switches (7)	
x				Brake Pedal/Actuator (3)	
x				Clutch/Clutch Pedal (1)	

x				Fire Extinguisher/Hazard Kit (5)	
x				Seats/Seat Belts/SRS (8)	
x				Steering Column/Components (4)	
x				Auxiliary Controls/Equip (5)	
x				Speedometer/Odometer (5)	
x				Steering Lash/Travel (5)	
x				Accelerator Pedal/Actuator (1)	
x				Engine Shut Down Control (1)	
x				Engine Start Feature (1)	
x				Body Interior/Fixtures (8)	

Pass	Rejected	Corrected	Req Attn	BODY EXTERIOR	Comments
x				Lamps (6)	
x				Headlamp Aim (6)	
x				Reflex Reflectors (6)	
x				Retro Reflective Markings (6)	
x				Body/Bumpers (8)	
x				Trailer Hitch (10)	
x				Cab Grab Handles/Steps (8)	
x				Attached Equipment (8)	
x				Cargo Bodies/Vessels (8)	
x				Sun Visor Exterior (8)	
x				Mud Flaps/Fenders (8)	
x				Trailer Power Cord (7)	
x				Chain/Headache Rack (5)	
x				Auxiliary Compartments (8)	
x				Hybrid Vehicle Drive Systems (1)	
x				Unitized Body Elements (8)	

Pass	Rejected	Corrected	Req Attn	ENGINE COMPARTMENT	Comments
x				Cab/Hood Safety Catches (8)	
x				Power Steering System (4)	
x				Fuel System (1)	
x				Battery/Wiring Condition (7)	
x				Air Suspended Cab (8)	
x				Cab Mounts (8)	
x				Drive Belts (1)	

Pass	Rejected	Corrected	Req Attn	CHASSIS	Comments
x				Hyd Brake System/Components (3.1)	

			Air Brake System/Components (3.2)	
x			Wheel Bearings (9)	
x			King Pins/Ball Joints (4)	
x			Steering Linkage (4)	
x			Tires/Wheels (9)	
x			Self-Steering Axle (4)	
x			Engine/Transmission Mounts (1)	
x			Frame/Crossmembers/Mounts (8)	
x			Suspension/Axles (2)	
x			Drive Shaft/Universal Joints (1)	
x			Exhaust/Emission System (1)	

#### Brake/Tire Measurements

##### **Axle 1-Pass**

Wheel1-On : Tire Tread Depth: 15 mm

Brake(1): S-CAM Brake

- Min Brake Lining/Pad: 14 mm • Cam Rotation: 65 degrees • Brake Stroke: 1.25 in

Wheel2-On : Tire Tread Depth: 14 mm

Brake(1): S-CAM Brake

- Min Brake Lining/Pad: 18 mm • Cam Rotation: 40 degrees • Brake Stroke: 1.25 in

##### **Axle 2-Pass**

Wheel1-On : Tire Tread Depth: 23 mm

Brake(1): S-CAM Brake

- Min Brake Lining/Pad: 21 mm • Cam Rotation: 35 degrees • Brake Stroke: 1.25 in

Wheel2-On : Tire Tread Depth: 22 mm

Brake(1): S-CAM Brake

- Min Brake Lining/Pad: 21 mm • Cam Rotation: 35 degrees • Brake Stroke: 1.25 in

Wheel3-On : Tire Tread Depth: 23 mm

Brake(1): S-CAM Brake

- Min Brake Lining/Pad: 21 mm • Cam Rotation: 33 degrees • Brake Stroke: 1.25 in

Wheel4-On : Tire Tread Depth: 23 mm

Brake(1): S-CAM Brake

- Min Brake Lining/Pad: 21 mm • Cam Rotation: 33 degrees • Brake Stroke: 1.25 in

##### **Axle 3-Pass**

Wheel1-On : Tire Tread Depth: 23 mm

Brake(1): S-CAM Brake

- Min Brake Lining/Pad: 21 mm • Cam Rotation: 35 degrees • Brake Stroke: 1.25 in

Wheel2-On : Tire Tread Depth: 23 mm

Brake(1): S-CAM Brake

- Min Brake Lining/Pad: 21 mm • Cam Rotation: 35 degrees • Brake Stroke: 1.25 in

Wheel3-On : Tire Tread Depth: 23 mm

Brake(1): S-CAM Brake

- Min Brake Lining/Pad: 21 mm • Cam Rotation: 36 degrees • Brake Stroke: 1.25 in

Wheel4-On : Tire Tread Depth: 24 mm

Brake(1): S-CAM Brake

- Min Brake Lining/Pad: 21 mm • Cam Rotation: 36 degrees • Brake Stroke: 1.25 in