

Hiab XS 055 CLX Basic data

Technical data	BS-1 CLX	BS-2 CLX	B-2 CLX	D-3 CLX	D-4 CLX
Max. lifting capacity (ft-lbs)	-	-	-	-	-
Outreach, hydraulic extensions	17' 5"	23' 11"	-	30' 6"	37' 1"
Outreach, manual extensions	29' 6"	29' 6"	30' 6"	37' 1"	-
Outreach / lifting capacity (ft / lbs)	6' 11" / 5 250 11' 6" / 3 220 16' 9" / 2 200 - - -	6' 11" / 4 890 11' 10" / 2 950 16' 9" / 2 030 22' 8" / 1 500 - -	8' 10" / 4 010 12' 6" / 2 780 17' 9" / 1 900 23' 7" / 1 410 - -	9' 6" / 3 570 13' 1" / 2 600 18' 1" / 1 810 23' 11" / 1 280 30' 6" / 990 -	10' 2" / 3 170 13' 5" / 2 380 18' 4" / 1 630 24' 3" / 1 150 30' 10" / 840 37' 1" / 680
Slewing angle	410° - 410°	410° - 410°	410° - 410°	410° - 410°	410° - 410°
Height in folded position	75"	75"	75"	75"	75"
Width in folded position	82"	85"	85"	85"	85"
Installation space needed	22"	22"	22"	26"	26"
Weight, "standard" crane without stabilizers (lbs)	1,610	1,790	-	1,940	2,090

Hiab XS 055 D-4 CLX

