

C04-2

SERIAL NO: C055431

Config: 00091202

Agrifac Condor IV consisting of:

CONDOR V-WIDE-J-212KW-St. 5-HD-30 cm boomheight-+200mm

Tank 1300 USG

133,33/83,33 Ft 20" J-boom 26s pneum. contr. nozzleh.

50 km/h in road mode

4x710/60 R42 Michelin XeoBib

***265-340 cm trackwidth / black rims**

4x Steering cylinder 40/80 stroke 190

Mudguards 26" wide

GPS skidd correction of application rate

Trimble GFX-750 rangepoint RTX (<15, pass to pass) installed

HTA with larger application rate

HighTechAirPlus system 133/83,33 Ft

FastFoldPlus (max 3 boom parts)

Droplet control for automatic droplet size

Elec-pneum.contr end nozzle right

StrictHeightPlus 2.0 Radar

Elec-pneum.contr end nozzle left

Anti-corrosion treatment (liquid fertilisers)

Anti Slip Regulation (ASR)

Vertical folding stairs

Automatic greasing chassis and centre frame(47 greasing p.)

Induction hopper Condor V

Additional display to operate pumps at the back of machine

Electrically operated drain valve underneath tank

Tapping connection on pressure side (pump out) 2"

Filling with external pump incl. connection

GreenFlowPlus with centrifugal pump spraying (stainless)

Cat. 4 cab

Headland management

Agrifac cab floor mat

Camera system: 1x monitor, 1x camera

2 Blue LED lights for boom/spray pattern illumination

Standard radio CD/MP3

Leather seat with heating and ventilation

Full LED package

Headlights right hand driving traffic

Blockheater 120 Volt

ENSIS treatment

Supply machine with antifreeze

Flowmeter for large application rates, 20-400 l/min, mounted

EcoFillPlus connection on induction hopper