

EC-Declaration of Conformity for Machinery

Manufacturer

Dinolift Oy
Raikkolantie 145
FI-32210 Loimaa, FINLAND

declares that

DINO 160XTB Access Platform no YGC160XTBF0160122

is in conformity with the provisions of Machinery Directive **2006/42/EC** as amended and with national implementing legislation.

Inspection according to 2006/42/EC appendix IX carried out by notified body nr. 0537

VTT
P.O.Box 1300
FI-33101 Tampere, FINLAND

which has granted the certificate No. **VTT 176/524/14**

Access platform also fulfils the requirements of the following EEC directives:
2006/95/EC, 2000/14/EC, 2004/108/EC

Following harmonized standards have been applied in designing the machine:
SFS-EN 280:2013; SFS-EN 60204-1/A1; SFS-EN-ISO 12100

Person authorized to draw up the Technical File:

Santtu Siivola
Chief Engineer
Dinolift Oy, Raikkolantie 145,
32210 Loimaa, FINLAND

Loimaa 18.03.2015



Antti Tuura
Supervisor

EC CERTIFICATE OF PRODUCTION rev. E

Side 1

The undersigned Supervisor Antti Tuura hereby certifies that the vehicle:

- 0.1. Make (Trade name of manufacturer): DINO
- 0.2. Type: _____
- Variant : _____
- Version : _____
- 0.2.1. Commercial name: DINO 160XTB II
- 0.4. Vehicle category: O₂
- 0.5. Company name and address of manufacturer: Dinolift Oy, Raikkolantie 145, 32210 Loimaa, FINLAND
- 0.6. Location and method of attachment of the statutory plates: The statutory plates are located on right hand side of the chassis. They are fixed by rivets.
- Location of the vehicle identification number: The vehicle identification number is stamped on top of chassis right hand side and also on bottom of the chassis left hand side below axle.
- 0.9. Name and address of the manufacturer's representative (if any): N/A
- 0.10. Vehicle identification number: YGC160XTBF0160122

conforms in BRAKES to the type described in report issued on 11.03.2015

and can be permanently registered in Member States having right/left hand traffic

(Place) (Date): 18.03.2015

(Signature):



Supervisor Antti Tuura

Side 2

General construction characteristics

1. Number of axles: 1 and wheels: 2

1.1. Number and position of axles with twin wheels: N/A

Main dimensions

4. Wheelbase : 4489 mm

4.1. Axle spacing: 1-2: N/A mm 2-3: N/A mm 3-4: N/A mm

5. Length: 6155 mm

6. Width: 1800 mm

7. Height: 2310 mm

10. Distance between the centre of the coupling device and the rear end of the vehicle: 6121 mm

11. Length of the loading area: N/A mm

12. Rear overhang: 1632 mm

Masses

13. Mass in running order: 2196 kg

13.1. Distribution of this mass amongst the axles: 1. 2098 kg 2. N/A kg 3. N/A kg

13.2 Actual mass of the vehicle: 2196 kg

16. Technically permissible maximum masses

16.1. Technically permissible maximum laden mass: 2196 kg

16.2. Technically permissible mass on each axle: 1. 2500 kg 2. N/A kg 3. N/A kg

16.3. Technically permissible mass on each axle group: 1. N/A kg 2. N/A kg 3. N/A kg

19. Technically permissible maximum static mass on the coupling point of a semi-trailer or centre-axle trailer: 107 kg

Maximum speed

29. Maximum speed: 140 km/h

Axles and suspension

30.1. Track of each steered axle: N/A mm

30.2. Track of all other axles: 1460 mm

31. Position of lift axle: N/A

32. Position of loadable axle: N/A

34. Axle(s) fitted with air suspension or equivalent: No

35. Tyre/wheel combination : 225/70R15C 112/110 N, Rim 6Jx15 ET 0

Brakes

36. Trailer brake connections: Mechanical

Bodywork

38. Code for bodywork : DC27

Coupling device

44. Approval number or approval mark of coupling device (if fitted): Coupling head: AK 300, e1*94/20*0131*02

Over run device: 251S, e1*94/20*0227*02

Drawbar: T/XT draw bar, e17*94/20*94/20*0110*00

45.1. Characteristics values : Coupling head D: 26,9 kN / V: N/A / S: 120kg / U: N/A

Over run device D: 24,5 kN / V: N/A / S: 120 kg / U: N/A

Drawbar D: 13,6 kN / V: N/A / S: 107 kg / U: N/A

Miscellaneous

50. Type-approved according to the design requirements for transporting dangerous goods: yes/class(es): No

51. For special purpose vehicles: designation in accordance with Annex II Section 5: N/A

52. Remarks (n): Optional tyre/wheel combinations : 225/75R16C 112/110 N, Rim 6Jx16 ET 0

