

EC-Declaration of Conformity for Machinery

Manufacturer

Dinolift Oy
Raikkolantie 145
FI-32210 Loimaa, FINLAND

declares that

DINO 135TB Access Platform no YGCD135TBF0130052

is in conformity with the provisions of Machinery Directive **2006/42/EC** as amended and with national implementing legislation.

Inspection according to 2006/42/EC appendix IX carried out by notified body nr. 0537

VTT
P.O.Box 1300
FI-33101 Tampere, FINLAND

which has granted the certificate No. **VTT 174/524/14**

Access platform also fulfils the requirements of the following EC directives:
2006/95/EC, 2000/14/EC, 2004/108/EC

Following harmonized standards have been applied in designing the machine:
SFS-EN 280:2013; SFS-EN 60204-1/A1; SFS-EN-ISO 12100


Person authorized to draw up the Technical File:

Santtu Siivola
Chief Engineer
Dinolift Oy, Raikkolantie 145,
32210 Loimaa, FINLAND

Loimaa 16.04.2015



Antti Tuura
Supervisor



START-UP TESTS:

Inspection place: Dinolift Oy

Inspector's signature: *Sauli Lehtinen* 1208

Lehtinen Sauli NT0574-2

BASIC KNOWLEDGE

Manufacturer: Dinolift Oy Place of manufacture: Finland

Address: Raikkolantie 145
32210 LOIMAA

Importer: _____

Type of lift: Boom platform Scissor platform Mast platform

Chassis: Car Self propelled Trailer mounted

Boom: Articulated boom Telescope boom Articulated telescope boom

Scissor Fixed mast Telescope mast

Outriggers: Hydraulic turning Hydraulic pushing Mechanical

TECHNICAL SPECIFICATION

Machine and type:	<u>DINO 135 TB</u>	Max. platform height	<u>11,5m</u>
Number of manufacture	<u>YGCD135TBF0130052</u>	Max. outreach: depend on load:	<u>Depend on load</u>
Year of manufacture	<u>2015</u>		
Max. lifting capacity:	<u>215 kg</u>	Boom rotation:	<u>Continuous</u>
Max. person number:	<u>2</u>	Support width:	<u>3,8m</u>
Max. additional load:	<u>55kg</u>	Transport width:	<u>1,78 m</u>
Power supply:	<u>24 VDC</u>	Transport length:	<u>5,94 m</u>
Lowest temperature:	<u>-20 °C</u>	Transport height:	<u>2,14 m</u>
Weight:	<u>1765 kg</u>	Basket size:	<u>0,7x1,3 m</u>

Inspection points: (Y = meet standards N = do not meet standards)

	Y	N		Y	N
A. STRENGTH			6. Plate for supports	<input checked="" type="checkbox"/>	<input type="checkbox"/>
1. Certificate of material	<input checked="" type="checkbox"/>	<input type="checkbox"/>	7. Safety colours	<input checked="" type="checkbox"/>	<input type="checkbox"/>
2. Certificate of strength	<input checked="" type="checkbox"/>	<input type="checkbox"/>			
B. STABILITY			D. SAFETY REQUIREMENTS		
1. Certificate of stability test	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1. Indicating device for horizontal position	<input checked="" type="checkbox"/>	<input type="checkbox"/>
2. Working space diagram	<input checked="" type="checkbox"/>	<input type="checkbox"/>	2. Locking device and lockings	<input checked="" type="checkbox"/>	<input type="checkbox"/>
C. GENERAL REQUIREMENTS			3. Stop device for lifting	<input checked="" type="checkbox"/>	<input type="checkbox"/>
1. User's manual	<input checked="" type="checkbox"/>	<input type="checkbox"/>	4. Stop for opening of support	<input checked="" type="checkbox"/>	<input type="checkbox"/>
2. Place for safekeeping for user's manual	<input checked="" type="checkbox"/>	<input type="checkbox"/>	5. Safety distances	<input checked="" type="checkbox"/>	<input type="checkbox"/>
3. Machine plate - checking plate	<input checked="" type="checkbox"/>	<input type="checkbox"/>	6. Position of working face	<input checked="" type="checkbox"/>	<input type="checkbox"/>
4. Load plate	<input checked="" type="checkbox"/>	<input type="checkbox"/>	7. Structure of working face	<input checked="" type="checkbox"/>	<input type="checkbox"/>
5. Warning plate	<input checked="" type="checkbox"/>	<input type="checkbox"/>	8. Emergency descent system	<input checked="" type="checkbox"/>	<input type="checkbox"/>
			9. Limit devices	<input checked="" type="checkbox"/>	<input type="checkbox"/>

E. ELECTRIC APPLIANCES

1. Electric appliances

G. SAFETY DEVICE

1. Safety limit switch

2. Sound signal

F. CONTROL DEVICES

1. Protections

H. LOADING TEST

2. Symbols / directions

1. Overload test = 323 kg (150%)

3. Placings

2. Funktional test = 237 kg (110%)

4. Emergency stop

FAILINGS AND NOTES

Failings have been repaired.

Date: _____

Signature: _____

Dinolift Oy

Raikkolantie 145

FIN-32210 LOIMAA, FINLAND

Tel. +358 - 20 - 1772 400, Fax +358 - 2 - 7627 160, e-mail: info@dinolift.com