

CERTIFICATE OF CONFORMITY

Side 1 – Complete Vehicles

The undersigned: Alican GÜVEN / Product Manager hereby certifies that the vehicle:

0.1. Make (Trade name of manufacturer)	:GVN TRAILER
0.2. Type	:3GVN
0.2.1. Commercial name	Variant ⁽¹⁵³⁾ :1R29A
0.4. Vehicle Category	Version ⁽¹⁵³⁾ :F3W1L1D
0.5. Company name and address of the manufacturer	:3GVN29
0.6. Location and method of attachment of the statutory plates	:O ₄
Location of the vehicle identification number	: GVN TRAILER OTOMOTİV SANAYİ TİCARET LİMİTED ŞİRKETİ BÜYÜKKAYACIKOSB MAH. LALEHAN CAD. NO:1 SELÇUKLU/KONYA/TÜRKİYE
0.9. Name and address of manufacturer's representative (if any)	: Statutory plate is clinched on the front right-hand side of the chassis VIN is stamped on the front right-hand side of the chassis
0.10. Vehicle Identification Number	: FRANCISCO MIRÓN FERNANDEZ
0.11. Date of manufacture of the vehicle	Autovia A-, salida 507 Pol. Ind. fase 1, parcela 2- 4, Villa Outeiro de Rei, 6, 27150 Outeiro de Rei, Lugo, Spain
	: NR93GVN03S1186147
	: 31.10.2025

conforms in all respect to the type described in approval (e24*2018/858*00401*00) granted on (20.09.2024) and can be permanently registered in Member States having right ~~Left~~ ⁽¹⁵⁴⁾ hand traffic and using metric ~~imperial~~ ⁽¹⁵⁴⁾ units for the speedometer and metric/~~imperial~~ ⁽¹⁵⁵⁾ units for the odometer (if applicable) ⁽¹⁵⁶⁾

Place: Konya / TURKEY



VEHICLE CATEGORIES O3 and O4
Side 2 – Complete and Completed Vehicles

General Construction Characteristics

- | | | |
|------|--|---------------------|
| 1. | Number of axles: and wheels ⁽⁵⁾ | : 3 axles 12 wheels |
| 1.1. | Number and position of axles with twin wheels | : All axles |
| 2. | Steered axles (number, position) | : NA |

Main Dimensions

- | | | |
|------|---|---|
| 4. | Wheelbase ⁽¹⁵⁷⁾⁽¹⁷⁴⁾ | : 9890 mm |
| 4.1. | Axle spacing | : 0-1: 7050mm-1-2: 1420 mm-2-3: 1420 mm |
| 5. | Length | : 13300mm |
| 5.3. | Vehicle equipped with aerodynamic device or equipment on the rear/not equipped ⁽⁴⁾ | : Not equipped |
| 6. | Width | : 2550 mm |
| 7. | Height | : 3000 mm |
| 10. | Distance between the centre of the coupling device and the rear end of the vehicle | : 11300 mm |
| 11. | Length of the loading area | : 9200 mm |
| 12. | Rear overhang ⁽¹⁵⁸⁾ | : 1400 |

Masses

- | | | |
|--------|--|---|
| 13. | Mass in running order | : 10500 kg |
| 13.Oca | Distribution of this mass amongst the axles | : 1. 2820kg; 2. 2820kg; 3. 2820 kg |
| 13.2. | Actual mass of the vehicle | : 10500 kg |
| 16. | Technically permissible maximum masses | |
| 16.1. | Technically permissible maximum laden mass | : 58000 kg |
| 16.2. | Technically permissible mass on each axle | : 1. 12000 kg; 2. 12000 kg; 3. 12000 kg |
| 16.3. | Technically permissible mass on each axle group | : 1. 36000 kg |
| | Intended registration/in service maximum permissible masses in national/international traffic (4) (166) | |
| 17. | Only for national traffic, the lower-case letter 'e' followed by the distinguishing number of the Member State: N.A.
For international traffic, number of the Directive/Regulation: | |
| 17.1. | Intended registration/in service maximum permissible laden mass | : 58000 kg |
| 17.2. | Intended registration/in service maximum permissible laden mass on each axle | : 1. 12000 kg; 2. 12000 kg; 3. 12000 kg |
| 17.3. | Intended registration/in service maximum permissible laden mass on each axle group | : 1. 36000 kg |
| 19. | Technically permissible maximum static mass on the coupling point of a semi-trailer or centre-axle trailer | : 22000 kg |

Maximum Speed

- | | | |
|-----|---------------|-----------|
| 29. | Maximum speed | : 80 km/h |
|-----|---------------|-----------|

Axles and Suspension

- | | | |
|-----|--|-----------------------|
| 31. | Position of lift axle(s) | : 1st axle |
| 32. | Position of loadable axle(s) | : N.A. |
| 33. | Drive axle(s) fitted with air suspension or equivalent: yes/no (4) | : N.A. |
| 34. | Axle(s) fitted with air suspension or equivalent: yes/no (4) | : Yes, Air suspension |
| 35. | Tyre/wheel combination (160) | : All, 235/75R17,5" |

Brakes

- | | | |
|-----|--|----------|
| 36. | Trailer brake connections mechanical/electric/pneumatic/hydraulic ⁽⁴⁾ | : HALDEX |
|-----|--|----------|

Bodywork

- | | | |
|-----|------------------------------------|--|
| 38. | Code for bodywork ⁽¹¹³⁾ | : DA: Semi-trailer ; 29: Low Floor Trailer |
|-----|------------------------------------|--|

Coupling Device

- | | | |
|-------|---|--|
| 44. | Approval number or approval mark of coupling device (if fitted) | : E2055R-01 3753 |
| 45.1. | Characteristics values (4) D: ... / V: ... / S: ... / U: ... | : D: 190 kN / V: ... / S: ... / U: ... |

Miscellaneous

- | | | |
|-----|---|---|
| 50. | Type-approved in accordance with the design requirements for transporting dangerous goods of UN Regulation No 105 of the Economic Commission for Europe of the United Nations: yes/class(es): .../no (4): | |
| 51. | For special purpose vehicles: designation in accordance with point 5 of Part A of Annex I to Regulation (EU) 2018/858 of the European Parliament and of the Council | : SK: Exceptional load transport trailer |
| 52. | Remarks (165) | : Removable hydraulic ramps in rear part. Rotating headlight support in rear part. Double placement for the king pin. |

GVN TRAILER
OTOMOTIV SAN. TIC. LTD. STI
Calehan Cad. No:1
Selçuklu/KONYA
Tic. Sic. No: 55323
Mersis No: 0454189611700001

