

# EC CERTIFICATE OF CONFORMITY

## Side 1 – Complete Vehicles

The undersigned: ... (ALICAN GÜVEN / PRODUCT MANAGER) hereby certifies that the vehicle:

- 0.1. Make (Trade name of manufacturer) : GVN TRAILER
- 0.2. Type : 4GVN  
Variant <sup>(153)</sup> : 1R29A  
Version <sup>(153)</sup> : F3W1L1C
- 0.2.1. Commercial name : 4GVN29
- 0.4. Vehicle Category : O4
- 0.5. Company name and address of the manufacturer : GVN TRAILER OTOMOTİV  
SANAYİ TİCARET LİMİTED  
ŞİRKETİ BÜYÜKKAYACIKOSB  
MAH. LALEHAN CAD. NO:1  
SELÇUKLU/KONYA/TÜRKİYE
- 0.6. Location and method of attachment of the statutory plates : Statutory plate is clinched to  
front right hand side of the  
chassis.  
Location of the vehicle identification number : VIN is stamped to front right  
hand side of the chassis.
- 0.9. Name and address of manufacturer's representative (if any) : FRANCISCO MIRÓN  
FERNANDEZ  
Autovía A-, salida 507 Pol. Ind.  
fase 1, parcela 2-4, Villa Outeiro  
de Rei, 6, 27150 Outeiro de Rei,  
Lugo, Spain
- 0.10. Vehicle Identification Number : NR94GVN06S1186096
- 0.11. Date of manufacture of the vehicle : 19.08.2025

conforms in all respect to the type described in approval ( e24\*2018/858\*00402\*00) granted on (22.11.2024) and can be permanently registered in Member States having right/left<sup>(154)</sup> hand traffic and using metric/imperial<sup>(154)</sup> units for the speedometer and metric/imperial<sup>(155)</sup> units for the odometer (if applicable)<sup>(156)</sup>

Place: Konya

**GVN** GVN TRAILER  
OTOMOTİV SAN.  
TİC. LTD. ŞTİ.  
Büyükkayacık OSB Mahallesi Lalehan Cad. No:1  
Tel: 0332 502 27 99 Selçuklu/KONYA  
Tic. Sic. No: 55323  
Tic. Sic. No: 0454189611700001





**General Construction Characteristics**

- |      |  |                     |
|------|--|---------------------|
| 1.   | Number of axles: ..... and wheels <sup>(5)</sup> | : 4 Axle, 16 Wheels |
| 1.1. | Number and position of axles with twin wheels    | : All axles         |
| 2.   | Steered axles (number, position)                 | : 4. Axle           |

**Main Dimensions**

- |      |   |   |
|------|---|---|
| 4.   | Wheelbase <sup>(157)(174)</sup>   | : 10780 mm  |
| 4.1. | Axle spacing  | : 0-1 : 6520 mm, 1-2: 1420 mm, 2-3: 1420 mm, 3-4: 1420 mm |
| 5.   | Length  | : 13450 mm  |
| 5.3. | Vehicle equipped with aerodynamic device or equipment on the rear/not equipped <sup>(4)</sup> | : N.A   |
| 6.   | Width   | : 2550 mm   |
| 7.   | Height  | : 3000 mm   |
| 10.  | Distance between the centre of the coupling device and the rear end of the vehicle            | : 12180 mm  |
| 11.  | Length of the loading area  | : 9600 mm   |
| 12.  | Rear overhang   | : 1400 mm   |

**Masses <sup>(158)</sup>**

- |       |   |  |
|-------|---|--|
| 13.   | Mass in running order   | : 11500 kg   |
| 13.1  | Distribution of this mass amongst the axles   | : 1. 2240 kg; 2. 2240 kg; 3. 2240 kg, 4. 2240 kg     |
| 13.2. | Actual mass of the vehicle  | : 11500kg  |
| 16.   | Technically permissible maximum masses  |  |
| 16.1. | Technically permissible maximum laden mass  | : 68000 kg   |
| 16.2. | Technically permissible mass on each axle   | : 1. 12000 kg; 2. 12000 kg; 3. 12000 kg, 4. 12000 kg |
| 16.3. | Technically permissible mass on each axle group   | : 48000 kg   |
| 17.   | Intended registration/in service maximum permissible masses in national/international traffic <sup>(4)</sup> <sup>(166)</sup> |  |

Only for national traffic, the lower-case letter 'e' followed by the distinguishing number of the Member State:

For international traffic, number of the Directive/Regulation:

- |       |  |  |
|-------|--|--|
| 17.1. | Intended registration/in service maximum permissible laden mass  | : 43500 kg                                       |
| 17.2. | Intended registration/in service maximum permissible laden mass on each axle                               | : 1. 8000 kg; 2. 8000 kg; 3. 8000 kg, 4. 8000 kg |
| 17.3. | Intended registration/in service maximum permissible laden mass on each axle group                         | : 32000 kg                                       |
| 19.   | Technically permissible maximum static mass on the coupling point of a semi-trailer or centre-axle trailer | : 20000 kg                                       |



**Maximum Speed**

- |     |               |           |
|-----|---------------|-----------|
| 29. | Maximum speed | : 80 km/h |
|-----|---------------|-----------|

**Axles and Suspension**

- |     |   |                              |
|-----|---|------------------------------|
| 31. | Position of lift axle(s)  | :1st axle                    |
| 32. | Position of loadable axle(s)  | : N.A                        |
| 34. | Axle(s) fitted with air suspension or equivalent: yes/no <sup>(4)</sup> | : Yes, Air suspension        |
| 35. | Tyre/wheel combination <sup>(160)</sup>                                 | : ALL 245/70R17,5" 143/141 J |

**Brakes**

- |     |  |          |
|-----|--|----------|
| 36. | Trailer brake connections mechanical/electric/pneumatic/hydraulic <sup>(4)</sup> | : HALDEX |
|-----|--|----------|

**Bodywork**

- |     |                                    |   |
|-----|------------------------------------|---|
| 38. | Code for bodywork <sup>(113)</sup> | : DA: Semi-trailer ; 29 Low Floor trailer |
|-----|------------------------------------|---|

**Coupling Device**

- |       |   |  |
|-------|---|--|
| 44.   | Approval number or approval mark of coupling device (if fitted)         | : E20 55R-01 3753                      |
| 45.1. | Characteristics values <sup>(4)</sup> D: ... / V: ... / S: ... / U: ... | : D: 190 kN / V: ... / S: ... / U: ... |

**Miscellaneous**

- |     |   |  |
|-----|---|--|
| 50. | Type-approved in accordance with the design requirements for transporting dangerous goods of UN Regulation No 105 of the Economic Commission for Europe of the United Nations: yes/class(es): .../no <sup>(4)</sup> : | : No   |
| 51. | For special purpose vehicles: designation in accordance with point 5 of Part A of Annex I to Regulation (EU) 2018/858 of the European Parliament and of the Council:  | :SK: Exceptional load transport trailer  |
| 52. | Remarks <sup>(165)</sup>  | :Removable hydraulic ramps in rear part. Rotating headlight support in rear part. Double placement for the king pin. |