

EC CERTIFICATE OF CONFORMITY

Side 1

The undersigned Production Coordinator Matti Jalonen hereby certifies that the vehicle:

0.1. Make (Trade name of manufacturer): DINO

0.2. Type: T/XT

Variant : 260XTD

Version : A

0.2.1. Commercial name: DINO

0.4. Vehicle category: O₂

0.5. Name and address of manufacturer: Dinolift Oy, Raikkolantie 145, 32210 Loimaa, FINLAND

0.6. Location and method of attachment of the statutory plates: The statutory plates are located on right hand side of the drawbar. They are fixed by rivets.

Location of the vehicle identification number: The vehicle identification number is stamped on the center of chassis on the right hand side of the vehicle behind the axle as well as on the drawbar on the right hand side.

0.9. Name and address of the manufacturer's representative (if any): N/A

0.10. Vehicle identification number: YGCD260XTE0026387

conforms in all respects to the type described in approval **e17*2007/46*0010*00** issued on **13.12.2010**

and can be permanently registered in Member States having right/left hand traffic

(Place) (Date): 08.05.2014

(Signature): 

Matti Jalonen

Side 2

General construction characteristics

1. Number of axles: 1 and wheels: 2

1.1. Number and position of axles with twin wheels: N/A

Main dimensions

4. Wheelbase : N/A mm

4.1. Axle spacing: 1-2: N/A mm 2-3: N/A mm 3-4: N/A mm

5. Length: 8210 mm

6. Width: 2050 mm

7. Height: 2435 mm

10. Distance between the centre of the coupling device and the rear end of the vehicle: 8175 mm

11. Length of the loading area: N/A mm

12. Rear overhang: 2230 mm

Masses

13. Mass of the vehicle in running order: 3495 kg

13.1. Distribution of this mass amongst the axles: 1. 3380 kg 2. N/A kg 3. N/A kg

16. Technically permissible maximum masses

16.1. Technically permissible maximum laden mass: 3495 kg

16.2. Technically permissible mass on each axle: 1. 3500 kg 2. N/A kg 3. N/A kg

16.3. Technically permissible mass on each axle group: 1. N/A kg 2. N/A kg 3. N/A kg

19. Technically permissible maximum static mass on the coupling point of a semi-trailer or centre-axle trailer: 150 kg

Maximum speed

29. Maximum speed: 130 km/h

Axles and suspension

30.1. Track of each steered axle: N/A mm

30.2. Track of all other axles: 1705 mm

31. Position of retractable axle: N/A

32. Position of loadable axle: N/A

34. Axle(s) fitted with air suspension or equivalent: No

35. Tyre/wheel combination : 225/75R17.5, 128/126 M, Rim 17.5x6.75 ET-0

Brakes

36. Trailer brake connections: mechanical

Bodywork

38. Code for bodywork : DC Centre-axle trailer

Coupling device

44. Approval number or approval mark of coupling device (if fitted): Coupling head: AK351, e1 00-1595

Over run device: AL-KO 2.8VB/1/351S, e1 00-0384

45.1. Characteristics values : Coupling head D: 31 kN / V: N/A / S: 350 kg / U: N/A

Over run device D: 31 kN / V: N/A / S: 150 kg / U: N/A

Miscellaneous

50. Type-approved according to the design requirements for transporting dangerous goods: yes/class(es): No

51. For special purpose vehicles: designation in accordance with Annex II Section 5: N/A

52. Remarks : N/A

START-UP TESTS:

Inspection place: Dinolift OyInspector's signature: *F. Schmidt*

Schmidt Florian NT0578-2

1131

BASIC KNOWLEDGE

Manufacturer: Dinolift OYPlace of manufacture: FinlandAddress: Raikkolantie 145
32210 LOIMAA

Importer: _____

- Type of lift: Boom platform Scissor platform Mast platform
- Chassis: Car Self propelled Trailer mounted
- Boom: Articulated boom Telescope boom Articulated telescope boom
- Scissor Fixed mast Telescope mast
- Outriggers: Hydraulic turning Hydraulic pushing Mechanical

TECHNICAL SPECIFICATIONS

Machine and type: DINO 260 XTD Max. platform height: 24m

Number of manufacture: YGCD260XT E0026387 Max. outreach: depend on load: Depend on load

Year of manufacture: 2014

Max. lifting capacity: 215 kg Boom rotation: Continuous

Max. person number: 2 Support width: 4,4 m

Max. additional load: 55kg Transport width: 2,04 m

Power supply: 230VAC / Engine Transport length: 8,25 m

Lowest temperature: -20 °C Transport height: 2,33 m

Weight: 3495 kg Basket size: 0,7x1,3 m

Inspection points: (Y = meet standards N = do not meet standards)

A. STRENGTH

1. Certificate of material Y N
2. Certificate of strength Y N

B. STABILITY

1. Certificate of stability test Y N
2. Working space diagram Y N

C. GENERAL REQUIREMENTS

1. User's manual Y N
2. Place for safekeeping for user's manual Y N
3. Machine plate - checking plate Y N
4. Load plate Y N
5. Warning plate Y N

6. Plate for supports Y N7. Safety colours Y N

D. SAFETY REQUIREMENTS

1. Indicating device for horizontal position Y N
2. Locking device and lockings Y N
3. Stop device for lifting Y N
4. Stop for opening of support Y N
5. Safety distances Y N
6. Position of working face Y N
7. Structure of working face Y N
8. Emergency descent system Y N
9. Limit devices Y N

E. ELECTRIC APPLIANCES

1. Electric appliances

G. SAFETY DEVICE

1. Safety limit switch

2. Sound signal

F. CONTROL DEVICES

1. Protections

H. LOADING TEST

2. Symbols / directions

1. Overload test = 323 kg (150%)

3. Placings

2. Funktional test = 237 kg (110%)

4. Emergency stop

FAILINGS AND NOTES

Failings have been repaired.

Date: _____

Signature: _____

Dinolift Oy

Raikkolantie 145

FIN-32210 LOIMAA, FINLAND

Tel. +358 - 20 - 1772 400, Fax +358 - 2 - 7627 160, e-mail: info@dinolift.com