

COMPLETE VEHICLE EU CERTIFICATE OF CONFORMITY

The undersigned, Mr. TIK LOU, Legal Person
Hereby certifies that the following complete vehicle:

General construction characteristics

- | | | | | |
|--------|----------------------------|--------------------------------------|-------------|---|
| 1.3. | Number of axles: | 2 | and wheels: | 4 |
| 1.3.1. | Axles with twinned wheels: | N.A. | | |
| 1.3.2. | Powered axles: | R | | |
| 6.2.4. | Advanced braking system: | ABS + CBS / Both ABS and CBS / None: | None | |

Main dimensions

- | | | |
|----------|--------------------------------------|---------|
| 2.2.1. | Length: | 2530 mm |
| 2.2.2. | Width: | 1500 mm |
| 2.2.3. | Height: | 1560 mm |
| 2.2.4. | Wheelbase: | 1680 mm |
| 2.2.4.1. | Wheelbase sidecar: | N.A. |
| 2.2.5. | Track width: | |
| 2.2.5.1. | Track width front: | 1320 mm |
| 2.2.5.2. | Track width rear: | 1320 mm |
| 2.2.5.3. | Track width sidecar: | N.A. |
| 2.2.10.6 | Ground clearance between the axles: | N.A. |
| 2.2.15. | Wheelbase to ground clearance ratio: | N.A. |
| 2.2.17. | Seat height: | N.A. |

Masses

- | | | |
|----------|--|--------|
| 2.1.1. | Mass in running order: | 449 kg |
| 2.1.2. | Actual mass: | 664 kg |
| 2.1.3. | Technically permissible maximum laden mass: | 774 kg |
| 2.1.3.1. | Technically permissible maximum mass on front axle: | 342 kg |
| 2.1.3.2. | Technically permissible maximum mass on rear axle: | 432 kg |
| 2.1.3.3. | Technically permissible maximum mass on sidecar axle: | N.A. |
| 2.1.7. | Technically permissible maximum towable mass: | |
| | Braked: | N.A. |
| | Unbraked: | N.A. |
| 2.1.7.1. | Technically permissible maximum laden mass of the combination: | N.A. |
| 2.1.7.2. | Technically permissible maximum mass at the coupling point: | N.A. |

Powertrain

- | | | |
|------------|--|--------------------|
| 3.1.1.1. | Manufacturer: | N.A. |
| 3.1.1.2. | Engine code (as marked on the engine or other means of identification): | N.A. |
| 3.2.1.2. | Working principle of the combustion engine: internal combustion engine (ICE) / positive ignition / compression ignition / external combustion engine (ECE) / turbine / compressed air: | N.A. |
| 3.2.1.4.1. | Number of cylinders: | N.A. |
| 3.2.1.4.2. | Arrangement of cylinders: | I / V / O / S N.A. |
| 3.2.1.5. | Engine capacity: | N.A. |
| 1.9. | Maximum net power: | |
| | (CV*, N.A.) | |
| 1.10. | Ratio maximum net power/mass of the vehicle in running order: | |
| | (CV*, N.A.) | |

conforms in all respects to the type described in EU type-approval e9*168.2013*11721*00 (type-approval number including extension number) (CV* type-approval number including extension number) issued on 17/09/2021 (date of issue) (CV* date of issue) and can be permanently registered in Member States having right/left ⁽¹⁾ hand traffic and using metric/imperial ⁽¹⁾ units for the speedometer.

TORINO, ITALY

21. 01. 2022

(place)

(date)

LOU TIK

(signature)

3.2.3.1.	Fuel type:	N.A.	Environmental performance
3.2.3.2.	Vehicle fuel combination:	mono-fuel/bi-fuel/flex-fuel	4.0.1.
3.2.3.2.1.	Maximum amount of bio-fuel acceptable in fuel:	N.A.	4.0.6.
3.1.2.1.	Manufacturer:	Hefei Yoyao Technology Co., LTD	4.0.6.1.
3.1.2.2.	Electric motor code (as marked on the engine or other means of identification):	N.A.	4.0.6.2.
3.3.3.4.	TZ155CA05DYGA/DA202007M8A00262		4.0.6.3.
3.1.3.1.	15-30 minutes power:	7.5 kW	
3.1.3.2.	Manufacturer:	N.A.	
3.3.1.	Application code (as marked on the engine or other means of identification):	N.A.	
3.3.5.2.	Electric vehicle configuration: pure electric/hybrid electric/manpower-electric		
3.9.2.	Category of hybrid electric vehicle: off-vehicle charging/hot off-vehicle charging		
	Maximum assistance factor:	N.A.	
	Maximum speed		
1.8.	Maximum speed of vehicle:	70 km/h (CV*: N.A.)	
3.9.3.	Maximum vehicle speed for which the electric motor gives assistance:	N.A.	
	Drive-train and control		
3.5.3.9.	Transmission (type):	O	
3.5.4.	Gear ratios:	7.961	
3.5.4.1.	Final drive ratio:	7.961	
3.5.4.2.	Overall gear ratio in highest gear:	N.A.	
	Installation of tyres		
6.18.1.1.	Tyre size designation:		
	Axle 1:	155/65R14 (75T)	
	Axle 2:	155/65R14 (75T)	
	Minimum Load capacity index:		
	Axle 1:	47	
	Axle 2:	55	
	Minimum speed category symbol:		
	Axle 1:	F	
	Axle 2:	F	
	Recommended pressure:		
	Axle 1:	220 kPa	
	Axle 2:	230 kPa	
	Rim size:		
	Axle 1:	14x5J	
	Axle 2:	14x5J	
	Sidecar wheel:	N.A.	
	Bodywork		
6.20.2.1.	Door configuration and number of doors:	1L, 1R	
6.16.1.	Number of seating positions:	2	
6.16.1.1.	Location and arrangement:	1L, 1R, 1L	
	Coupling devices		
7.2.8.	Type-approval number of coupling-device:	N.A.	

2-60128
GR 835 199

