

EC CERTIFICATE OF CONFORMITY

Side 1

The undersigned Production Manager Tuomas Heilala hereby certifies that the vehicle:

0.1.	Make (Trade name of manufacturer)	DINO
0.2.	Type	T/XT
	Variant	160XTB II
	Version	A
0.2.1.	Commercial name	160XTB II
0.4.	Vehicle category	O ₂
0.5.	Company name and address of manufacturer	Dinolift Oy, Raikkolantie 145, 32210 Loimaa, FINLAND
0.6.	Location and method of attachment of the statutory plates	The statutory plates are located on right hand side of the chassis. They are fixed by rivets.
	Location of the vehicle identification number	The vehicle identification number is stamped on the center of chassis on the right hand side of the vehicle and on the drawbar on the right hand side.
0.9.	Name and address of the manufacturer's representative (if any)	N/A
0.10.	Vehicle identification number	YGC160XTBJ0160383

conforms in all respects to the type described in approval *e17*2007/46*0010*04* issued on *20.10.2016*

and can be permanently registered in Member States having right/left hand traffic



(Place) (Date): Loimaa 03.04.2018

Signature: _____

Production Manager Tuomas Heilala

Osoite/Address
Dinolift Oy
Raikkolantie 145
FI-32210 LOIMAA
Finland

Puhelin/Telephone
+358 20 1772 400
Faksi/Telefax
+358 2 7627 160
www.dinolift.com

Y-tunnus/Business ID
2031176-2
VAT
FI 20311762
Kotipaikka/Domicile
Loimaa, Finland

Pankki/Bank account
Nordea Loimaa
IBAN: FI24 1097 3000 0486 41
BIC (SWIFT): NDEAFIHH



START-UP TESTS:

Inspection place: Dinolift Oy

Inspector's signature: 

385

Järvinen Janne-Matti NT1519-2

BASIC INFORMATION

Manufacturer: Dinolift OY Place of manufacture: Finland
 Address: Raikkolantie 145
32210 LOIMAA
 Importer: _____
 Type of lift: Boom platform Scissor platform Mast platform
 Chassis: Car Self propelled Trailer mounted
 Boom: Articulated boom Telescopic boom Articulated telescopic boom
 Fixed mast Telescopic mast Scissor
 Outriggers: Hydraulic turning Hydraulic pushing Mechanical

TECHNICAL SPECIFICATIONS

Machine and type: DINO 160XTB Max. platform height: 14,0 m
 Number of manufacture: YGC160XTBJ0160383 Max. outreach: Depend on load
 Year of manufacture: 2018
 Max. lifting capacity: 215 kg Boom rotation: Continuous
 Max. person number: 2 Support width: 3,8 m
 Max. additional load: 55 kg Transport width: 1,80 m
 Power supply: 24 VDC Transport length: 6,15 m
 Lowest temperature: -20 °C Transport height: 2,31 m
 Weight: 2196 kg Basket size: 0,7 x 1,3 m

INSPECTION POINTS: (Y = meet standards N = do not meet standards)

	Y	N		Y	N
A. GENERAL REQUIREMENTS			C. STRUCTURES		
1. Suitability for use	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1. Transport position / transp. equipment	<input checked="" type="checkbox"/>	<input type="checkbox"/>
2. Certificate of conformity	<input checked="" type="checkbox"/>	<input type="checkbox"/>	2. Driving/towing equipment	<input checked="" type="checkbox"/>	<input type="checkbox"/>
3. User manual and storage	<input checked="" type="checkbox"/>	<input type="checkbox"/>	3. Chassis	<input checked="" type="checkbox"/>	<input type="checkbox"/>
4. Machine plate - inspection plate	<input checked="" type="checkbox"/>	<input type="checkbox"/>	4. Turning device	<input checked="" type="checkbox"/>	<input type="checkbox"/>
5. Instructional and safety plates	<input checked="" type="checkbox"/>	<input type="checkbox"/>	5. Boom system	<input checked="" type="checkbox"/>	<input type="checkbox"/>
6. Safety colours	<input checked="" type="checkbox"/>	<input type="checkbox"/>	6. Structure and position of work platform	<input checked="" type="checkbox"/>	<input type="checkbox"/>
			7. Hydraulic system	<input checked="" type="checkbox"/>	<input type="checkbox"/>
B. STABILITY			D. ELECTRIC SYSTEM		
1. Load plate and reach diagram	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1. Electric system	<input checked="" type="checkbox"/>	<input type="checkbox"/>
2. Supports / outriggers	<input checked="" type="checkbox"/>	<input type="checkbox"/>	2. Electric appliances	<input checked="" type="checkbox"/>	<input type="checkbox"/>
3. Indicator for horizontal position	<input checked="" type="checkbox"/>	<input type="checkbox"/>	3. Lights	<input checked="" type="checkbox"/>	<input type="checkbox"/>

EC-Declaration of Conformity for Machinery

Manufacturer

Dinolift Oy
Raikkolantie 145
FI-32210 Loimaa, FINLAND

declares that

DINO 160XTB Access Platform no YGC160XTBJ0160383

is in conformity with the provisions of Machinery Directive **2006/42/EC** as amended and with national implementing legislation.

Inspection according to 2006/42/EC appendix IX carried out by notified body nr. 0537

VTT
P.O.Box 1300
FI-33101 Tampere, FINLAND

which has granted the certificate No. **VTT 176/524/14**

Access platform also fulfils the requirements of the following EEC directives:
2014/35/EU, 2014/30/EU

Following harmonized standards have been applied in designing the machine:
SFS-EN 280:2013; SFS-EN 60204-1/A1; SFS-EN-ISO 12100

Person authorized to draw up the Technical File:

Santtu Siivola
Chief Engineer
Dinolift Oy, Raikkolantie 145,
32210 Loimaa, FINLAND

Loimaa

03.04.2018



Santtu Siivola
Chief Engineer

