

EC CERTIFICATE OF CONFORMITY

Side 1

The undersigned Production Coordinator Matti Jalonen hereby certifies that the vehicle:

0.1. Make (Trade name of manufacturer): DINO

0.2. Type: T/XT

Variant : 160XTB

Version : A

0.2.1. Commercial name: DINO

0.4. Vehicle category: O₂

0.5. Name and address of manufacturer: Dinolift Oy, Raikkolantie 145, 32210 Loimaa, FINLAND

0.6. Location and method of attachment of the statutory plates: The statutory plates are located on right hand side of the drawbar. They are fixed by rivets.

Location of the vehicle identification number: The vehicle identification number is stamped on the center of chassis on the right hand side of the vehicle behind the axle as well as on the drawbar on the right hand side.

0.9. Name and address of the manufacturer's representative (if any): N/A

0.10. Vehicle identification number: YGC160XTBE0160069

conforms in all respects to the type described in approval **e17*2007/46*0010*00** issued on **13.12.2010**

and can be permanently registered in Member States having right/left hand traffic

(Place) (Date): 14.04.2014

(Signature): 
Matti Jalonen



Side 2

General construction characteristics

1. Number of axles: 1 and wheels: 2

1.1. Number and position of axles with twin wheels: N/A

Main dimensions

4. Wheelbase : N/A mm

4.1. Axle spacing: 1-2: N/A mm 2-3: N/A mm 3-4: N/A mm

5. Length: 6010 mm

6. Width: 1800 mm

7. Height: 2310 mm

10. Distance between the centre of the coupling device and the rear end of the vehicle: 5975 mm

11. Length of the loading area: N/A mm

12. Rear overhang: 1700 mm

Masses

13. Mass of the vehicle in running order: 2175 kg

13.1. Distribution of this mass amongst the axles: 1. 2095 kg 2. N/A kg 3. N/A kg

16. Technically permissible maximum masses

16.1. Technically permissible maximum laden mass: 2175 kg

16.2. Technically permissible mass on each axle: 1. 2500 kg 2. N/A kg 3. N/A kg

16.3. Technically permissible mass on each axle group: 1. N/A kg 2. N/A kg 3. N/A kg

19. Technically permissible maximum static mass on the coupling point of a semi-trailer or centre-axle trailer: 100 kg

Maximum speed

29. Maximum speed: 140 km/h

Axles and suspension

30.1. Track of each steered axle: N/A mm

30.2. Track of all other axles: 1480 mm

31. Position of retractable axle: N/A

32. Position of loadable axle: N/A

34. Axle(s) fitted with air suspension or equivalent: No

35. Tyre/wheel combination : 225/70R15C, 112/110 N, Rim 6JX15 ET-0

Brakes

36. Trailer brake connections: mechanical

Bodywork

38. Code for bodywork : DC Centre-axle trailer

Coupling device

44. Approval number or approval mark of coupling device (if fitted): Coupling head: AK300, e1 00-0131

Over run device: AL-KO 251S, e1 00-0227

45.1. Characteristics values : Coupling head D: 26.9 kN / V: N/A / S: 120 kg / U: N/A

Over run device D: 23.6 kN / V: N/A / S: 100 kg / U: N/A

Miscellaneous

50. Type-approved according to the design requirements for transporting dangerous goods: yes/class(es): No

51. For special purpose vehicles: designation in accordance with Annex II Section 5: N/A

52. Remarks : N/A

