

- 7-7-15 - REPLACE ALL FAN BELTS FRONT + REAR
8721HRS - SERVICE BOTH ENG. MAJOR AIR FILTER
- REPLACE A/C COMPRESOR + DRYER, VACUUM
+ RECHARGE A/C
- CHANGE FRONT + REAR TRANS FILTERS ONLY
- REPLACE GREASE HOSE FOR FRONT FAN HUB
- INSTALL OIL SUCKER FITTINGS
- REPLACE AIR LINE FOR REAR THROTTLE
FROM GOOSE NECK TO REAR ENG.
- CHANGE RETURN FUEL LINE FOR FRONT
ENG., GOOSE NECK TO FUEL TANK
- REPLACE REAR ENG. HARMONIC BALANCER
- ADJ BRAKES

- NOTE: - R.F. BRAKE OVER CAM, R.R. SLACK ADJ.
BAD
- ADJ. EJECTOR DOOR, GAP ON BOTTOM
- TURN CUTTING EDGES
- WELD CRACKS ON TOP FUEL TANK
- STEAM FRONT + REAR RADIATORS

10-26-15 - NEW HOUR METER AT 8865 HRS
8865HRS

627F #7

3/15/16 - Repin and Bush Main Pins in Goose neck

110 HRS - Repin and Bush all steer Pins and Bushings in goose neck and steer cly.

- Remove Goose neck from tractor and Repin and Bush two lower pins
- Repin and Bush H-links for cushion Hitch w/new thrust washers (pins are cat classic)
- Replaced all hoses from main control valve to Goose neck
- Replaced Both steering hoses from valve under cab to Bottom of Goose neck
- Accessory Drive for Air Compressor leaking oil - remove Compressor drain anti-freeze - in order to remove drive acc. must remove front timing cover and all accessories (fan hub, water pump, A/c comp, balancer)
Reseal Air compressor drive and Reinstall, New gaskets on front timing cover and front Crank seal and Reinstall with oil pan down inspected main and Rod Bearings Both looked good Reinstall oil pan / changed oil and Filter / Fuel Filter / New Anti-freeze
- changed Hyd oil and Filter
- Removed Left and Right wheels to replaced Brakes
Reman shoes from cat and new Drums New wheel seals
Right side got New cam / Left fender Bracket removed and Reinstalled (3) studs that were leaking trans oil from trans case / ~~the~~ Changed oil in front Diff and Both front finals

next Page

- Replaced A/C Line from Comp to Condenser add oil and Recharge
- Service Rear Engine oil/fuel/Air
- Replaced Rear Engine Batteries
- Changed hose for ~~pilot~~ control on Bail valve
- Remove clean and Reseal front steering filter

8/23/16 - Remove and Replaced Rear Eng starter w/ Rebuilt
140 HRS

9/17 - Remove and Replaced Rear Eng Oil Cooler
650 HRS - Flush Radiator w/ cleaner and Fill w/
NAPS Free Coolant
- Flip Cutting Edges

2/18 - Remove Rear Power Pack and send to Lance for Rear
838 HRS Eng Rebuild (HES)

4/20 - Replaced front Eng oil Cooler w/ CAT Reman
1,658 HRS flushed Radiator w/ Steam Cleaner filled w/ New
coolant