

**ROADTEC RP-195e - 10' (3M) Rubber Track Asphalt Paver, 2022 Model**

Serial Number 4501

Cummins QSB 6.7 230 HP Tier 4f/Stage IV Diesel Engine

¾" (19 mm) Thick Continuous Side Sheet Frame Construction

2" (50 mm) Thick Front Cross Frame Member

Oscillating Push Rollers

Direct Hydraulic Planetary Drive

15.5 Ton (14 mt) Capacity/ 290 Cubic Feet Self Dumping Hopper

Electric Flow Gates

Independently driven variable speed feeder conveyors

1/2" (12.5 mm) 550 BHN cast head and tail plates and chromium carbide clad floor plates

Conveyor By-Pass - Operation of Augers Independent of Feeders

16" (355 mm) Cast ¾" Thick Ni-hard Augers

Hydraulically Raise, Lower and Tilting Auger Assembly

Friction Drive Undercarriage with Three sets of Oscillating Bogies

18" (457 mm) Wide Reinforced Smooth Tread Rubber Track

Two (2) Comfort Drive Operators Stations, Finger Tip Paver Control with Total Control Joystick

Dual Comfort Drive Operators stations hydraulically swing out past edge of machine for increased visibility

Total Control Joystick combines all tractor propel controls into single joystick

Display at each operators station for engine diagnostics, paver diagnostics as well as speed and flow gate position

24 Volt Starting System with Master Disconnect Switches

95 Amp Alternator

Clearview FXS Fume Extraction System

Hydraulic Engine Hood Raise with Manual Back Up

Amber Warning Beacon, Back Up Alarm and Fire Extinguisher

1 Umbrella for operator station and brackets for installation

Lighted Dual Screed Control Stations for head of material and screed control with Fixed Remotes and lockable vandal covers

Retractable wash-down hose reel system with 30' (9.1 m) hose length

100-gallon (378 l) fuel tank capacity

18" hydraulic tunnel extensions

Road Light Package - Includes six 24V lights (2 hopper, 2 screed, 2 tunnel)

Electrical wiring and hydraulic hoses for connection to screed

1 Year factory warranty

Guardian Telematic System

#### EZ-IV-10 Front Extendable Screed

10' (3 m) to 19' (5.8 m) Hydraulically Extendable Carlson Easy Screed IV with Wide Blade Electric Heat

One 5' (1.5 m) Long & One 4' (1.2 m) Long Front Mounted Extensions

Extensions Move on High Composite Bushings & Chrome Slide Track

Extensions are 8" (203 mm) Wide, with Heat, Vibration and Adjustable Angle of Attack

Extensions Provide 9% Positive Slope

Electric Valves Control In/Out, Slope & Vertical Height

Carlson's Patented "Front Taper Design" Main Screed

Main Screed is 26" (660 mm) Long, ½" (12.5 mm) Thick 400 BHN Screed Plate

Power Crown, 2½" (63 mm) Positive to ¾" (19 mm) Negative

Electric Screed Heat Provided by Continuous Duty 34 kW Generator and Dedicated Hydraulic Pump

Thermostatically Controlled Plate Temperature with Analog Display

5.5 KW @ 120 Volts Available for Accessory Use in 8 Outlets

Heater Hold Down System Allows Heater Change Without Removing the Screed Plate

Electrically Heated Oven for Warming Meals

Spring Loaded Two Piece End Gates

20" (508 mm) Wide Main Screed Hinged Heavy Duty Walkway

12" (304 mm) Wide Hinged Extension Walkways

Sonic Feeder Control System

Tow arms with mounting locations for automatic grade controls

#### Options Included in Our Price

24V LED Night Light Package - Includes Six 24V Lights

Auger Extension Remotes - Remotes attached to fixed remote on left and right sides to controls augers and extensions. Includes a 6 ft cord and can be disconnected for storage.

Pair of Heated End Gates

Hydraulic Screed Boost