P07-1

Alberta Government

CV8678824

80087500008678824

CERTIFICATE NUMBER

Commercial Vehicle Inspection Certificate
Traffic Safety Act

PART 1 - VEHICLE OWNER AND VEHICLE IDENTIFICATION

Vehicle Type:	Truck	**Seating Capacity:**			
GVW:	63500 kg	**Brake Type:**	Air		
Owner Name:	2570247 AB LTD				
Address:	PO BOX 323				
City:	VAUXHALL	**Province:**	AB	**Postal Code:**	T0K 2K0
Telephone Number:	(403) 654-7680				
Vehicle Identification Number:	1XKAD40X88J935452				
Make:	**Kenworth**	**Model:**	**Construct**		
Year:	**2008**	**Unit Number:**	**8**		
Odometer:	1443322 KM	**Licence Plate Number:**	U96096	**Province:**	AB

IT IS AN OFFENCE TO FALSIFY AN INSPECTION CERTIFICATE

PART 2 - CERTIFICATION

I certify the vehicle described in Part 1 has passed the inspections and tests established under the Traffic Safety Act for a Commercial Vehicle.

Inspection Facility Name:	**Facility Number:**
Arden Myers	**10809**
Inspection Technician Name:	**Technician Number:**
Franz Klassen	**D2130**
Inspection Technician Signature:	
Inspection Date:	**2026/09/10**

2027/09/30

Version No:1

Alberta Government

COMMERCIAL VEHICLE RECORD OF INSPECTION
TRUCK AND TRUCK-TRACTOR

The original Record of Inspection must be given to the customer regardless of whether the vehicle passes or not.

Type of Vehicle	Gross Vehicle Weight registered
Truck	63500 kg

Vehicle Information

VIN	1	X	K	A	D	4	0	X	8	8	J	9	3	5	4	5	2

Unit Number	Year	Make	Model	Odometer
8	2008	Kenworth	Construct	1,443,322

Registered Owner's Name	Plate Number
2570247 AB LTD	U96096

Address	Postal Code	Phone Number
PO BOX 323	T0K 2K0	(403) 654-7680

Drum Brakes: A-Full Inspection with Drum Removed Disc Brakes:

	LEFT		FRONT	RIGHT		
110 psi / 12 mm	392.3 384.1	mm	Drums/Rotors	383.7	mm	110 psi / 13 mm
	14.5 7.4	mm	Linings/Pads	9.5	mm	
	35	mm	Push Rod Travel	35	mm	
50 psi / 4 mm; 80 psi / 2 mm	419.5 422.3	mm	Drums/Rotors	419.9	mm	75 psi / 3 mm; 75 psi / 3 mm
	21.5 7.7	mm	Linings/Pads	17.6	mm	
	35	mm	Push Rod Travel	35	mm	
10 psi / 5 mm; 95 psi / 2 mm	420.2	mm	Drums/Rotors	421.5	mm	90 psi / 5 mm; 90 psi / 3 mm
	15.4	mm	Linings/Pads	9.1	mm	
	35	mm	Push Rod Travel	35	mm	
___ psi / ___ mm; ___ psi / ___ mm	___	mm	Drums/Rotors	___	mm	___ psi / ___ mm; ___ psi / ___ mm
	___	mm	Linings/Pads	___	mm	
	___	mm	Push Rod Travel	___	mm	
___ psi / ___ mm; ___ psi / ___ mm	___	mm	Drums/Rotors	___	mm	___ psi / ___ mm; ___ psi / ___ mm
	___	mm	Linings/Pads	___	mm	
	___	mm	Push Rod Travel	___	mm	
___ psi / ___ mm; ___ psi / ___ mm	___	mm	Drums/Rotors	___	mm	___ psi / ___ mm; ___ psi / ___ mm
	___	mm	Linings/Pads	___	mm	
	___	mm	Push Rod Travel	___	mm	

Park Brake Lining Left NA mm Right NA mm Trans NA mm

Wheel Torque Checked ✓ Inner NA ft lbs Outer 500 ft lbs

COMMERCIAL VEHICLE RECORD OF INSPECTION
TRUCK AND TRUCK-TRACTOR

Section 1 - Power Train

Component	P	F	NA	Component	P	F	NA
1.1. Accelerator Pedal/Throttle Actuator	✓			1.8. Engine Start Safety Feature	✓		
1.2. Exhaust System	✓			1.9. Gear Position Indicator			✓
1.3. Emission Control Systems and Devices	✓			1.10. Engine or Accessory Drive Belt	✓		
1.4. Drive Shaft	✓			1.11. Hybrid Electric Vehicle & Electric Vehicle Power Train System			✓
1.5. Clutch and Clutch Pedal	✓			1.12. Gasoline or Diesel Fuel System	✓		
1.6. Engine/Transmission Mount	✓			1.13. Pressurized or Liquefied Fuel System (LPG, CNG, & LNG) * SEE APPENDIX A*			✓
1.7. Engine/Shut Down	✓						

NOTES:
FAN BELT IS CUT . COOLANT LEAK ON ENGINE .
REPLACED FAN BELT . TIGHTENED COOLANT DRAIN VALVE.

APPENDIX "A"

Component	P	F	NA	Component	P	F	NA
A.1. Liquefied Petroleum Gas (LPG or Propane) Fuel System			✓	A.3. Liquefied Natural Gas (LNG) Fuel System			✓
A.2. Compressed Natural Gas (CNG) Fuel System			✓				

NOTES:

Section 2 - Suspension

Component	P	F	NA	Component	P	F	NA
2.1. Suspension & Frame Attachments	✓			2.5. Air Suspension	✓		
2.2. Axle Attaching & Tracking Components	✓			2.6. Self-Steer and Controlled-Steer Axle			✓
2.3. Axle & Axle Assembly	✓			2.7. Shock Absorber/Strut Assembly	✓		
2.4. Spring & Spring Attachment	✓						

NOTES:

Section 3H - Hydraulic Brakes

Component	P	F	NA	Component	P	F	NA
3H.1. Hydraulic System Components			✓	3H.13. Disc Brake System Components			✓
3H.2. Brake Pedal/Actuator			✓	3H.14. Mechanical Parking Brake			✓
3H.3. Vacuum Assist (Boost) System			✓	3H.15. Spring-Applied Air-Released Parking Brake			✓
3H.4. Hydraulic Assist (Boost) System			✓	3H.16. Spring-Applied Hydraulic-Released Parking Brake			✓
3H.5. Air Assist (Boost) System			✓	3H.17. Anti-Lock Brake System (ABS)			✓
3H.6. Air-Over-Hydraulic Brake System			✓	3H.18. Stability Control System			✓
3H.11. Brake System Indicator Lamps			✓	3H.19. Brake Performance			✓
3H.12. Drum Brake System Components			✓				

NOTES:

Section 3A - Air Brakes

Component	P	F	NA	Component	P	F	NA
3A.1. Air Compressor	✓			3A.13. Air System Components	✓		
3A.2. Air Supply System	✓			3A.14. Brake Chamber	✓		
3A.4. Air Tank	✓			3A.15. Drum Brake System Components	✓		
3A.5. Air Tank Check Valves	✓			3A.16. S-Cam Drum Brake System	✓		
3A.6. Brake Pedal/Actuator	✓			3A.17. Brake Shoe Travel (Wedge Brakes)	✓		
3A.7. Treadle Valve and Trailer Hand Valve	✓			3A.18. Disc Brake System Components			✓
3A.8. Brake Valves & Controls	✓			3A.19. Anti-Lock Brake System (ABS)	✓		
3A.9. Proportioning, Inversion or Modulation Valve	✓			3A.21. Stability Control System			✓
3A.10. Towing Vehicle (Tractor) Protection System	✓			3A.23. Brake Performance			✓

COMMERCIAL VEHICLE RECORD OF INSPECTION
TRUCK AND TRUCK-TRACTOR

Section 3A - Air Brakes							
Component	P	F	NA	Component	P	F	NA
3A.11. Parking Brake & Emergency Application	✓						

NOTES:
AXLE 2 LEFT HAND BRAKE SHOE WORE OUT AND DRUM IS OVERSIZE. INSTALLED NEW BRAKE SHOES AND DRUM ON AXLE 2 LEFT HAND SIDE .
STEERING AXLE LEFT HAND BRAKE LINE CUT . REPLACED CUT BRAKE LINE .
STEERING AXLE LEFT HAND BRAKE SHOE WORE OUT AND DRUM IS OVERSIZE. INSTALLED NEW BRAKE SHOES AND DRUM ON STEERING AXLE LEFT HAND SIDE.

Section 4 - Steering							
Component	P	F	NA	Component	P	F	NA
4.1. Steering Control and Linkage	✓			4.4. Kingpin	✓		
4.2. Power Steering System (Hydraulic and Electric)	✓			4.5. Self-Steer and Controlled-Steer Axle			✓
4.3. Steering Operation (Active Steer Axle)	✓						

NOTES:
LEFT HAND KING PIN HAS 3.5 mm OF PLAY , MAX IS 5mm. CUSTOMER IS NOTIFIED .

Section 5 - Instruments and Auxiliary Equipment							
Component	P	F	NA	Component	P	F	NA
5.1. Fire Extinguisher	✓			5.8. Heater & Windshield Defroster	✓		
5.2. Hazard Warning Kit	✓			5.9. Fuel-Burning Auxiliary Heater			✓
5.3. Horn	✓			5.10. Chain/"Headache" Rack			✓
5.5. Speedometer	✓			5.11. Auxiliary Controls and Devices			✓
5.6. Odometer	✓			5.12. Auxiliary Drive Controls			✓
5.7. Windshield Wiper/Washer	✓						

NOTES:
NO FIRE EXTINGUISHER IN THE TRUCK . PLACED NEW FIRE EXTINGUISHER IN THE TRUCK.

Section 6 - Lamps							
Component	P	F	NA	Component	P	F	NA
6.1. Required Lamps	✓			6.4. Instrument Panel Lamps	✓		
6.2. Reflex Reflector	✓			6.5. Headlamp Aim	✓		
6.3. Retro-Reflective Marking	✓						

NOTES:
LEFT HAND WORK LIGHTS DONT WORK . FIXED WIRING FOR WORK LIGHTS.

Section 7 - Electrical System							
Component	P	F	NA	Component	P	F	NA
7.1. Wiring	✓			7.3. Trailer Cord (output to towed vehicle)	✓		
7.2. Battery	✓						

NOTES:

Section 8 - Body							
Component	P	F	NA	Component	P	F	NA
8.1. Hood or Engine Enclosure	✓			8.12. Bumper	✓		
8.2. Tilt Cab			✓	8.13. Windshield	✓		
8.3. Air-Suspended Cab	✓			8.14. Side Windows	✓		
8.4. Cab and Passenger-Vehicle Body	✓			8.15. Rear Window	✓		
8.5. Cargo Body	✓			8.16. Interior Sun Visor	✓		
8.6. Frame, Rails & Mounts	✓			8.17. Exterior Windshield Sun Visor	✓		
8.7. Unitized Body Elements	✓			8.18. Rear-View Mirror	✓		

COMMERCIAL VEHICLE RECORD OF INSPECTION
TRUCK AND TRUCK-TRACTOR

Section 8 - Body

Component	P	F	NA	Component	P	F	NA
8.8. Cab or Cargo Door	✓			8.19. Seat	✓		
8.9. Cargo Tank or Vessel			✓	8.20. Seat Belt/Occupant Restraint	✓		
8.10. Body, Device or Equipment Attached or Mounted to the Vehicle	✓			8.21. Fender/Mud Flap	✓		
8.11. Refrigeration/Heater Unit Fuel System (Reefer or Auxiliary Power Unit (APU))	✓			8.24. Aerodynamic Device & Attachment			✓

NOTES:
RIGHT REAR MUD FLAP BOLTS MISSING . INSTALLED NEW BOLTS THAT WERE MISSING .

Section 9 - Tires and Wheels

Component	P	F	NA	Component	P	F	NA
9.1. Tire Tread Depth	✓			9.7. Wheel/Rim (Applies to all wheel types)	✓		
9.2. Tire Tread Condition	✓			9.8. Multi-Piece Wheel/Rim			✓
9.3. Tire Sidewall & Manufacturer Markings	✓			9.9. Spoke Wheel/Demountable Rim System			✓
9.4. Tire Inflation Pressure	✓			9.10. Disc Wheel System	✓		
9.5. Wheel Hub	✓			9.11. Wheel Fasteners (Nuts, Bolts and Studs)	✓		
9.6. Wheel Bearing	✓						

NOTES:
AXLES 2-3 LEFT HAND INSIDE TIRES ARE BELOW SPEC . CUSTOMER HAS TRUCK BOOKED IN FOR NEW TIRES AT TIRE SHOP.
TIRE PRESSURES ARE UNEVEN. ENENED UP ALL TIRE PRESSURES TO 90 lbs.

Section 10 - Couplers and Hitches

Component	P	F	NA	Component	P	F	NA
10.1. Hitch Assembly, Structure & Attaching Components			✓	10.5. Roll-Coupling Hitch			✓
10.2. Secondary Attachment (Safety Chain or Cable)			✓	10.6. Automated Coupling Device			✓
10.3. Pintle Hook, Pin Hitch, or Coupler Hitch			✓	10.7. Fifth Wheel Coupler	✓		
10.4. Ball Type Hitch			✓	10.8. Oscillating Fifth Wheel Coupler			✓

NOTES:

Certification

The Vehicle for which this Record of Inspection is issued has PASSED (Certificate #8678824) the inspection and I certify it has been inspected in accordance with the Vehicle Inspection Regulation, Alberta Regulation 211/2006 and the applicable Inspection Manual.

Date of Inspection	Technician Number	Facility Number	Signature
2026/09/10	D2130	10809	

Customer Acknowledgment

I understand if a vehicle inspection identifies defects and repairs are required, once repaired, the vehicle and this Record of Inspection (ROI) may be presented to any Vehicle Inspection Facility within 10 days of the initial inspection and only the failed items noted on this ROI are required to be re-inspected. If the vehicle is not returned for re-inspection within 10 days of the initial date of inspection, a new inspection must be conducted.

Date (Year/Month/Day)
2026/09/10

Customer Signature