

2016 JD 8345R

1RW8345RCFD108727

Description

Canada

English

Performance Package

AutoPower™ Infinitely Variable Transmission (IVT™) 42 km/h (26 mph)

One 10 in. CommandCenter™ Display with GreenStar™ 3 2630 Display

Less John Deere ActiveCommand™ Steering (ACS)

StarFire™ 3000 Receiver - SF1 with Deluxe Shroud

AutoTrac™ Activation - GreenStar™ 3 (GS3)

4600 Processor

Premium CommandView™ III Cab with ActiveSeat™

Premium Radio Package with XM Radio

Right-hand Reverser Linear-Type Transmission Controls

John Deere PowerTech™ 9.0 L (549 cu. in.) 6 Cylinder Tier 4/Stage V Compliant Diesel Engine

321 L/min (85 gpm) Dual Hydraulic Pump

Six Premium Rear Remote SCVs with Electrohydraulic (EH) Controls, Premium Couplers, and High Pr

45 mm (1-3/4 in.) 1,000 rpm (20-spline) PTO

9,072 kg (20,000 lb) capacity 3-Point Hitch (Cat 4N/3) Hitch with Sway Blocks and Quik-Coupler

Category 4 adjustable Swinging Drawbar with 50 mm (2 in.) Pin with heavy duty support

120 mm (4.72 in.) diameter by 3010 mm (118.5 in.) length with Double Taper Wheel Hubs

380/90R54 152A8 R1W Radial in Dual Wheel Configuration

Firestone™ Brand Only

ILS™ with hydraulic differential lock, fully-enclosed driveline and Group 48 Rear Tires

380/80R38 142A8 R1W Radial in Dual Wheel Configuration - Eight Position

Premium Lighting

Fenders, Pivoting Front - 480 mm (18.9 in.) Wide

Fenders, Rear Extensions 2.55 m (100 in.) Width

Outside Mirrors - Power Telescoping, Heated, Electrically Adjustable Right-hand and Left-hand

Radar, Dual Beam Sensor

Antenna Mount and Wiring for Business Band (2-Way) Radio

Foot Operated Speed Control

Cold Weather Start Kit

Fuel/Water Separator, Severe Duty

Auxiliary Hydraulic Connections - 1/2 in.

Battery Disconnect

3743 kg (8252 lb) Ballast Package with Rear Duals

Ethernet Switch

JDLink™ Connect - 3 Year Subscription