

2018 JD 8345R

1RW8345RCJS132683

Canada

English

No Package

e23™ Transmission 42 km/h (26 mph) with Efficiency Manager™

4600 CommandCenter™

Less John Deere ActiveCommand™ Steering (ACS)

CommandCenter™ AutoTrac™ Activation

4600 Processor

Premium CommandView™ III Cab with Cab Suspension

Premium Radio Package

Left-hand Reverser Bump-Shift-Type Transmission Controls

John Deere PowerTech™ 9.0 L (549 cu. in.) 6 Cylinder Tier 4/Stage V Compliant Diesel Engine

321 L/min (85 gpm) Dual Hydraulic Pump

Five (One High Flow) Premium Rear Remote SCVs with EH Controls, Premium Couplers, and High Pr 45 mm (1-3/4 in.) 1,000 rpm and 1,000 Economy rpm PTO, electronically shiftable in cab

9,072 kg (20,000 lb) capacity 3-Point Hitch (Cat 4N/3) Hitch with Sway Blocks and Quik-Coupler

Category 4 adjustable Swinging Drawbar with 50 mm (2 in.) Pin with heavy duty support

120 mm (4.72 in.) diameter by 3010 mm (118.5 in.) length with Double Taper Wheel Hubs

480/80R50 159A8 R1W Radial in Dual Wheel Configuration

Firestone™ Brand Only

1500 Series MFWD with hydraulic differential lock and Group 48 Rear Tires

380/80R38 142A8 R1W Radial in Dual Wheel Configuration - Eight Position

Premium Lighting

Fenders, Pivoting Front - 480 mm (18.9 in.) Wide

Fenders, Rear Extensions 2.55 m (100 in.) Width

Intelligent Power Management

Antenna Mount and Wiring for Business Band (2-Way) Radio

Actively Cooled Refrigeration Unit 6.4 L³ (391 cu. in.)

Cold Weather Start Kit

Auxiliary Hydraulic Connections - 3/4 in.

Rear Hydraulic Center Link - Category 4 (120 mm)

Battery Disconnect

Weight, front support with twenty-two suitcase weights

Ethernet Switch

StarFire™ 6000 Receiver - SF3 and RTK (Modem/Radio Not Included)

JDLink™ Connect 5 Year subscription