

**Designation characteristic value**

Front attachment drive 80 kW, fixed speed	Steering axle tyres 28 LR26 165 A8 8Lx275 R1
HP feeder housing AUTO CONTOUR with cutterbar brake	Ground speed 30 km/h
Dust extraction for HP feeder housing	Mercedes-Benz OM470 LA - 300 kW/408 hp (T4)
CRUISE PILOT, prepared	Fuel consumption measurement
Top link, hydraulic for HP feeder housing	Fuel tank 800 litres
Wide guide plates, HP feeder housing	Tier 4/M
APS threshing system - grain (6.5x40/7/18)	Radio with MP3 function
Centre risers for straw walker, fitted	Refrigeration unit for storage box M/L
Side risers for straw walker, fitted	Roller blinds for side windows
Standard cleaning, incl. 3D	Camera - grain tank unloading tube, PROFI CAM display
Fan panels	Camera screen - PROFI CAM
GRAINMETER incl. returns volume measurement with CEBIS displ	Preparation for terminal
Upper and lower sieve, TM6	QUANTIMETER yield measurement
Grain tank 11,500 litres	Printer
Grain tank unloading tube 4XL, PREMIUM LINE	Crop log
Grain tank unloading 2XL	TELEMATICS basic licence – 1 year
Power spreader - SPECIAL CUT, PREMIUM LINE	Comfort seat, leather, air-suspended
Drive axle W L - 10-hole	Work lighting LED - Premium incl. long-range work light
Twin tyres 620/70 R42, 10-hole	Trimble prepared
Steering axle, adjustable (8-hole)	CLAAS CAN bus interface
CEMOS AUTOMATIC - AUTO CLEANING	
CEMOS AUTOMATIC - AUTO CROP FLOW	
CEMOS AUTOMATIC - CRUISE PILOT	
CMOTION multifunction control lever	
Control module	
Inclination sensor	
Communication module (UMTS)	
Locking system, standard	
Central lubrication system incl. steering axle, straw choppe	
Discharge direction adjustment, automatic	
Straw chopper - static knife/friction concave plate adj., ma	
Steering valve, prop. XL, for GPS PILOT, LASER PILOT, AUTO P	
AUTO PILOT module	
Rear view mirrors, electrically adjustable	
Statutory equipment for right-hand side traffic	
Tool kit – Basic	
Technical documentation, English	
Fire extinguisher bracket	
Cutterbar greater than 9.0 m	