

April 8, 2026

Subject: Tigercat 1085C (10850572) Temporary Absence of Emissions Label

To Whom It May Concern:

The diesel engine installed in the following equipment is fully certified to U.S. EPA Tier 4 Final emission standards and meets applicable California Air Resources Board (CARB) requirements.

Equipment Information:

Manufacturer: Tigercat Industries, Inc.
Model: 1085C Forwarder
Serial Number: 10850572
Model Year: 2020
Manufactured Date: August 20, 2020

Engine Information:

Manufacturer: FPT Industrial S.p.A.
Model: F4HFE613F*B016
EPA Engine Family: LFPXL06.7SDA
Power Rating: 284 bhp (Peak) @ 2200rpm
Serial Number: 1764591
Model Year: 2020
Manufactured Date: March 19, 2020

The engine used in this equipment is certified under the EPA Certificate of Conformity No. LFPXL06.7SDA-025 and CARB Executive Order U-R-015-0425.

Please note that a replacement EPA emissions control information label has been ordered from the engine manufacturer and will be installed immediately upon receipt. This is expected to be completed by May 15, 2026.

This equipment is permitted to enter the United States based on the referenced certificates which demonstrate the engine's full compliance with EPA and CARB emissions requirements.

If there are any questions, concerns, or a need for further documentation, please contact me directly.

Sincerely,



Dan Gordon
Diesel Engine Systems Specialist
Tigercat Industries, Inc.
Phone: 226-220-3673 (mobile) or 519-622-6000 ext. 6230 (office)
Email: dgordon@tigercat.com

Pursuant to the authority vested in California Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2020	LFPXL06.7SDA	4.5, 6.7	Diesel	8,000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Electronic Direct Injection, Engine Control Module, Turbocharger, Charge Air Cooler, Diesel Oxidation Catalyst, Selective Catalytic Reduction - Urea, Ammonia Oxidation Catalyst			Tractor, Loader, Generator Set, and Other Industrial Equipment	

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			NMHC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
75 ≤ kW ≤ 560	Tier 4 Final	OPTIONAL STD	0.19	0.40	-	3.5	0.02	N/A	N/A	N/A
		CERT	0.02	0.39	-	0.01	0.02	-	-	-


BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has complied with the more stringent set of standards from the various power categories in conformance with Section 1039.230 (e) of the "California Exhaust Emission Standards and Test Procedures for New 2011 and Later Tier 4 Off-Road Compression-Ignition Engines, Parts I-D" adopted October 20, 2005 and last amended October 25, 2012.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 21ST day of August 2019.



Allen Lyons, Chief
 Emissions Certification and Compliance Division

Engine Model Summary Template

Eo#: U-R-015-0425

Attachment#: Pg 1/3

Date: 8/13/19

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
LFPXL06.7SDA	F4HFE613R*B	F4HFE613R*B	245 @ 2000	130	N/A	963 @ 1300	488	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE613X*B	F4HFE613X*B	226 @ 2000	111	N/A	742 @ 1500	135	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE613S*B	F4HFE613S*B	226 @ 2000	116	N/A	877 @ 1300	162	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE613J*B	F4HFE613J*B	221 @ 2200	106	N/A	767 @ 1500	144	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4DFE613J*B	F4DFE613J*B	221 @ 2200	106	N/A	767 @ 1500	144	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE613G*B	F4HFE613G*B	210 @ 2200	102	N/A	678 @ 1600	127	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE613K*B	F4HFE613K*B	202 @ 2200	97	N/A	696 @ 1500	129	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4DFE613K*B	F4DFE613K*B	202 @ 2200	97	N/A	696 @ 1500	129	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4DFE613M*B	F4DFE613M*B	188 @ 2200	94	N/A	648 @ 1500	122	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE613D*B	F4HFE613D*B	235 @ 2100	115	N/A	781 @ 1500	144	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE613B*B	F4HFE613B*B	256 @ 2200	118	N/A	859 @ 1500	157	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4DFE613B*B	F4DFE613B*B	256 @ 2200	118	N/A	859 @ 1500	157	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE613E*B	F4HFE613E*B	268 @ 2100	130	N/A	867 @ 1800	163	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE613C*B	F4HFE613C*B	275 @ 2100	133	N/A	881 @ 1800	164	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4DFE613H*B	F4DFE613H*B	236 @ 2200	106	N/A	815 @ 1500	148	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE613H*B	F4DHE613H*B	236 @ 2200	106	N/A	815 @ 1500	148	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE613F*B	F4HFE613F*B	284 @ 2200	131	N/A	859 @ 1500	155	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE613A*B	F4HFE613A*B	251 @ 2200	115	N/A	789 @ 1600	143	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE613U*B	F4HFE613U*B	251 @ 2200	118	N/A	859 @ 1500	157	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE613I*B	F4HFE613I*B	281 @ 2200	130	N/A	852 @ 1500	154	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE6134*B	F4HFE6134*B	295 @ 2200	139	N/A	881 @ 1700	163	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE413V*B	F4HFE413V*B	173 @ 2100	129	N/A	526 @ 1500	148	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE413W*B	F4HFE413W*B	162 @ 2100	120	N/A	519 @ 1500	146	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE413H*B	F4HFE413H*B	150 @ 2200	111	N/A	489 @ 1600	137	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4DFE413H*B	F4DFE413H*B	150 @ 2200	111	N/A	489 @ 1600	137	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4HFE4134*B	F4HFE4134*B	129 @ 2200	91	N/A	437 @ 1500	124	N/A	DDI ECM TC CAC DOC SCR-U AMOX
LFPXL06.7SDA	F4DFE4134*B	F4DFE4134*B	129 @ 2200	91	N/A	437 @ 1500	124	N/A	DDI ECM TC CAC DOC SCR-U AMOX

Engine Model Summary Template

EO#: U-R-015-0425

Attachment: pg 2/3

Date: 8/13/19

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
LFPXL06.7SDA	F4HFE4133*B	F4HFE4133*B	138 @ 2200	98	N/A	471 @ 1500	132	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4DFE4133*B	F4DFE4133*B	138 @ 2200	98	N/A	471 @ 1500	132	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4HFE4131*B	F4HFE4131*B	158 @ 2200	112	N/A	519 @ 1500	145	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4DFE4131*B	F4DFE4131*B	158 @ 2200	112	N/A	519 @ 1500	145	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4HFE4132*B	F4HFE4132*B	153 @ 2200	109	N/A	519 @ 1500	145	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4DFE4132*B	F4DFE4132*B	153 @ 2200	109	N/A	519 @ 1500	145	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4HFE413X*B	F4HFE413X*B	142 @ 2100	105	N/A	453 @ 1500	127	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4HFE413K*B	F4HFE413K*B	168 @ 2200	120	N/A	526 @ 1500	149	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4DFE413K*B	F4DFE413K*B	168 @ 2200	120	N/A	526 @ 1500	149	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4HFE6136*B	F4HFE6136*B	176 @ 2200	83	N/A	616 @ 1500	114	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4DFE6136*B	F4DFE6136*B	176 @ 2200	83	N/A	616 @ 1500	114	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4HFE6137*B	F4HFE6137*B	208 @ 2100	100	N/A	685 @ 1500	125	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4DFE414B*B	F4DFE414B*B	133 @ 2200	97	N/A	448 @ 1500	127	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4DFE414C*B	F4DFE414C*B	123 @ 2200	90	N/A	415 @ 1500	118	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4DFE414D*B	F4DFE414D*B	114 @ 2200	85	N/A	391 @ 1500	111	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4DFE414E*B	F4DFE414E*B	143 @ 2200	101	N/A	481 @ 1500	132	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4DFE617L*B	F4DFE617L*B	296 @ 2100	142	N/A	950 @ 1400	179	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4DFE617M*B	F4DFE617M*B	267 @ 2100	128	N/A	884 @ 1400	167	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4HFE613M*B	F4HFE613M*B	188 @ 2200	94	N/A	648 @ 1500	122	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4HFE615B*B	F4HFE615B*B	194 @ 1800	99	N/A	570 @ 1500	99	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4HFE615C*B	F4HFE615C*B	224 @ 1800	114	N/A	656 @ 1500	114	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4HFE615D*B	F4HFE615D*B	261 @ 1800	130	N/A	767 @ 1500	130	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4HFE615E*B	F4HFE615E*B	299 @ 1800	150	N/A	876 @ 1500	150	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4HFE617M*B	F4HFE617M*B	267 @ 2100	128	N/A	884 @ 1400	167	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4HFE617L*B	F4DFE617L*B	296 @ 2100	142	N/A	950 @ 1400	179	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4HFE414C*B	F4DFE414C*B	123 @ 2200	90	N/A	412 @ 1500	118	N/A	DDI ECM TC CAC DOC SCR-u AMOX
LFPXL06.7SDA	F4HFE415A*B	F4HFE415A*B	169 @ 1800	141	N/A	493 @ 1800	141	N/A	DDI ECM TC CAC DOC SCR-u AMOX

Engine Model Summary Template

Eo#: U-R-015-0425

Attachment: pg 3/3

Date: 8/13/19

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
LFPXL06.7SDA	F4HFE6138*B	F4HFE6138*B	190 @ 2550	84	N/A	630 @ 1400	119	N/A	DDI ECM TC CAC DOC SCR-ii AMOX
LFPXL06.7SDA	F4HFE614A*B	F4HFE614A*B	284 @ 2500	125	N/A	859 @ 1500	155	N/A	DDI ECM TC CAC DOC SCR-ii AMOX
LFPXL06.7SDA	F4DFE414Z*B	F4DFE414Z*B	172 @ 2200	125	N/A	519 @ 1500	145	N/A	DDI ECM TC CAC DOC SCR-ii AMOX
LFPXL06.7SDA	F4HFE414Z*B	F4HFE414Z*B	172 @ 2200	125	N/A	519 @ 1500	145	N/A	DDI ECM TC CAC DOC SCR-ii AMOX
LFPXL06.7SDA	F4DFE414Y*B	F4DFE414Y*B	165 @ 2200	120	N/A	519 @ 1500	145	N/A	DDI ECM TC CAC DOC SCR-ii AMOX
LFPXL06.7SDA	F4HFE414Y*B	F4HFE414Y*B	165 @ 2200	120	N/A	519 @ 1500	145	N/A	DDI ECM TC CAC DOC SCR-ii AMOX
LFPXL06.7SDA	F4DFE414X*B	F4DFE414X*B	151 @ 2200	112	N/A	471 @ 1500	132	N/A	DDI ECM TC CAC DOC SCR-ii AMOX
LFPXL06.7SDA	F4HFE414X*B	F4HFE414X*B	151 @ 2200	112	N/A	471 @ 1500	132	N/A	DDI ECM TC CAC DOC SCR-ii AMOX
LFPXL06.7SDA	F4DFE414W*B	F4DFE414W*B	142 @ 2200	106	N/A	437 @ 1500	124	N/A	DDI ECM TC CAC DOC SCR-ii AMOX
LFPXL06.7SDA	F4HFE414W*B	F4HFE414W*B	142 @ 2200	106	N/A	437 @ 1500	124	N/A	DDI ECM TC CAC DOC SCR-ii AMOX
LFPXL06.7SDA	F4DFE614Z*B	F4DFE614Z*B	173 @ 2200	129	N/A	594 @ 1500	114	N/A	DDI ECM TC CAC DOC SCR-ii AMOX
LFPXL06.7SDA	F4HFE415C*B	F4HFE415C*B	115 @ 1800	96	N/A	334 @ 1800	96	N/A	DDI ECM TC CAC DOC SCR-ii AMOX
LFPXL06.7SDA	F4HFE615F*B	F4HFE615F*B	196 @ 1800	99	N/A	570 @ 1800	99	N/A	DDI ECM TC CAC DOC SCR-ii AMOX
LFPXL06.7SDA	F4HFE615G*B	F4HFE615G*B	225 @ 1800	114	N/A	656 @ 1800	114	N/A	DDI ECM TC CAC DOC SCR-ii AMOX