

Serial No: CE026145

Agrifac Condor IV consisting of:

CONDOR ENDURANCE II-St. V-J-298KW-TRACK 267-367 + 140 mm
133,33/90 Ft 20" J-boom 17S pneum. contr. nozzleh.

50 km/h in road mode
Pivoting mudguards 710 mm wide
GPS skidd correction of application rate
Trimble GFX-750 range point RTX (<15, pass to pass) installed
HighTechAirPlus System 133/90 Ft 20"
HTA with larger application rate
Droplet control for automatic droplet size
Elec-pneum.contr end nozzle right
Elec-pneum.contr end nozzle left
StrictHeightPlus
Anti Slip Regulation (ASR)
Automatic greasing chassis and centre frame (24 greasing p.)
Anti-corrosion treatment (liquid fertilisers)
Automatic fill stop
Tapping connection on pressure side
EcoFillPlus connection on inductionhopper
Cab suspension
GreenFlowPlus with Hypro centrifugal spray pump
Electrical drain valve under the tank
Induction hopper incl canister cleaning system
Agrifac cab floor mat
Headland management
2x3" hose from top of spray tank for overflow stream to soil
2 Blue LED lights for boom/spray pattern illumination
Camera system: 1x monitor, 1x camera
External filling clean water tank
Leather seat with heating and ventilation
Full LED package
Bluetooth function integrated in radio FM/AM
Supply machine with antifreeze
ENSIS treatment
Flowmeter for large application rates, 20-400 l/min, mounted
BKT 750/75R46