

Additional Options

Quant. RA-885 Options

- | | | |
|---|--|---|
| 1 | Dual Product w/micro hopper with 348 cu. ft. capacity, adjustable wall for 50/50 or 60/40 bin split, dual 304SS mesh chains for each bin, electric tarp w/ground remote. | J |
| 1 | 90' Boom, on-center - 30"
Raven XRT Auto-boom (90' only) | / |
| 1 | Roll Tarp - Agri-Cover SRT-2 Electric Closure (Black)
Tarp Bin Divider - Single Bin - 304SS w/window (between main & micro) | J |
| 1 | Tarp Bin Divider - Multi Bin - 304SS w/window (between main/mid/second/micro) | / |

Quant. Precision Products

- | | | |
|---|--|---|
| 1 | Viper 4+ Controller | / |
| 1 | Raven RS1 GPS Receiver (auto-steer & slingshot ready) | / |
| 1 | RS1 Smart-Trax Kit
Raven VSN (Visual Guidance System)
Dickey John Radar (ILOS of GPS ground speed) | / |

Quant. Chassis Options

- | | | |
|---|--|---|
| 1 | Extended Engine & Transmission Warranty Package (Increase to 5 years or 5000 hours)
Crop Guard
Adjustable axles 114" to 144" track, 4 wheel steering, crab steering
Adjustable axles 114" to 144" track, 2 wheel steering
Fixed front axle, rear adjustable axle, 2 wheel steering
Fixed axles, 4 wheel steering, crab steering | / |
| 1 | Electric Airbag Dump | / |
| 1 | LED High Intensity Work Lights (6 mounted on cab, 1 on ea. boom)
Electric & Heated Mirrors | / |
| 1 | Camera - Side Mirrors (exterior side mount cameras/interior monitors)
Leather Operators / Buddy Seat (Standard Cab Only)
<u>Luxury Cab</u> - Leather Heated/Cooled Operators Seat, Leather Buddy Seat, SiriusXM Radio w/Bluetooth, Leather Wrapped Steering Wheel (ILOS of Standard Cab) | / |
| 1 | Rhino Line - Full Frame/Walk-ways/Ladder | / |
| 1 | Stainless Steel Tool Box | / |
| 1 | Window Tint | / |
| 1 | Weather Tech Removable Floormat | / |
| 1 | Back-up Camera - integrates with the MD4 display | / |
| 1 | Front and Rear Fender brackets with 24" wide poly fenders
Front and Rear Fender brackets with 33" wide poly fenders | / |

Quant. Tires and Wheels

- 380/90R46 173D (No Brand Preference)
380/90R46 173D Premium - Michelin Spraybib / Firestone AD2
380/105R50 179D (No Brand Preference)
380/105R50 179D Trelleborg
420/95R50 177D Michelin Spraybib
Row Crop Wheel Off-Set (Choose - 111", 114", 117", or 120")

Click Here for Wh.

2023 Venturi 430

1	Base Unit	Venturi 430 with the following standard features
	Engine	Cummins QSL 9L Stage V - 430 BHP @ 2,100 RPM - 1,250 lbs-ft @ 1500 RPM - 2 stage fuel filters - 2 stage air filter - exhaust muffler - single module SCR/DOC
	Transmission	Allison automatic RDS3060 w/Dual Mode Shift Pattern
	Transfer Case	Marmen-Herrington MVG-760, w/ smart shift, two speed, 1:1 high range, 2:3.9 low range, Integral air shift for front axle engage, 8-speed low range, 4-speed high range
	Rear Axle	Meritor - 36,000# capacity, locking diff, w/HD Air Suspension
	Front Axle	Meritor - 36,000# capacity, locking diff, w/HD Air Suspension
	Frame	10" X 4" X 3/8" high strength tubular steel
	Brakes	S-cam brakes
	Tires	380/80R48 173D 14,300# @40MPH
	Weight	19,300# Chassis, RA-885 add 9,500#
	Dimensions	Wheelbase 163", Overall length 319.25", Overall width 135" (booms folded), Overall height 147 11/16", Crop Clearance 28.5" (w/o Crop Deflector)
	Fuel / DEF Cap.	Diesel 160 gallons / DEF 30 gallons
	Steering	Load Sense Steering - Low RPM Compensated Steering
	Batteries	Two 12-volt, 1000 Ah heavy duty batteries w/manual disconnect switch
	Paint	Catalytic Polyurethane
	Cab	Pressurized, Isolated mounted full-view cab, Heat, A/C, Radio, Fire Ext, Touch Screen Management Center, Remote Telematics System
	Hand Throttle	Standard - Redundant Hand Throttle Control - with Spread & Auto Steer Control, Boom Functions
	Row Spacing	Available Row Crop Wheel Tracks : 111", 114", 117", 120"
	Std. Warranty	Cab and chassis 1 year / 1000 hours -- Cummins Engine 2 year / 2500 hours -- Allison transmission 3 year / Unlimited (see full warranty policy)

Quant.	Standard Application
INC. IN BASE	RBR RA-885 Air Boom Spreader-Single Product w/micro hopper 360 cu. ft. capacity (295 main / 55 micro), 409SS box with 304SS 72' rear booms 3" tubes, dual 304SS mesh chains with LHRH shutoff, 26" outlet centers, hydraulic breakaway tips, full hydraulic suspension.