



**Machine Number:** CE026291 (call for availability)

**Description**

Agrifac Condor Endurance II consisting of:  
stuklijst nog niet bepaald  
160/105 Ft J2 boom, 15", 34s, circulation  
60 km/h in road mode  
104 - 144 inch trackwidth. Black rim  
Pivoting mudguards 710 mm wide  
GPS skidd correction of application rate  
Trimble GFX-1060 range point RTX/center point RTX installed  
FastFoldPlus (max 3 boom parts)  
Elec-pneum. controlled end- & border nozzle right  
Elec-pneum. controlled end- & border nozzle left  
StrictHeightPlus 2.0 Radar  
StrictSpray on machine  
SSP on boom (including individual nozzle control)  
Anti Slip Regulation (ASR)  
Automatic greasing chassis and centre frame (24 greasing p.)  
Anti-corrosion treatment (liquid fertilisers)  
Automatic fill stop  
No HighTechAir  
Tapping connection on pressure side  
EcoFillPlus connection on inductionhopper  
Cab suspension  
GreenFlowPlus with Hypro centrifugal spray pump  
Electrical drain valve under the tank  
Induction hopper incl canister cleaning system  
Agrifac cab floor mat  
Headland management  
Set Sunblinds le+ri  
2x3" hose from top of spray tank for overflow stream to soil  
2 Blue LED lights for boom/spray pattern illumination  
Category 4 cab  
Camera system: 1x monitor, 1x camera  
External filling clean water tank  
Standard radio CD/MP3  
Leather seat with heating and ventilation  
Rear lights right driving traffic  
Full LED package  
Supply machine with antifreeze  
ENSIS treatment  
Flowmeter for large application rates, 20-400 l/min, mounted  
Valve stack front  
AiC Plus - ready  
Upgrade SSP to 10" Nozzle Spacing for AiC  
750/75R46 Michelin  
IF380/105R54 Alliance