

COMPLETE VEHICLE EU CERTIFICATE OF CONFORMITY

The undersigned, Yiting Chen, Managing Director
Hereby certifies that the following complete vehicle:

- 0.1. Make (trade name of the manufacturer): E-MAX, VMOTO
- 0.2. Type: CUX
- 0.2.1. Variant: 3
- 0.2.2. Version: 1
- 0.2.3. Commercial name (if available): Not applicable
- 0.3. Category, subcategory and sub-subcategory of vehicle: L1e-B
- 0.4. Company name and address of manufacturer:
NANJING VMOTO MANUFACTURING CO., LTD.
NO. 15, EAST ZHONGXING ROAD, LISHUI ECONOMIC DEVELOPMENT ZONE,
NANJING CITY, JIANGSU PROVINCE, CHINA

0.4.2. Name and address of manufacturer's authorized representative (if any):

Vmoto Europe B.V.
Boekwijkstraat 97, 2153GK, Nieuw-Vennep, Netherlands

0.5.1. Location of the manufacturer's statutory plate(s): R, X550, Y102, Z168

0.5.2. Method of attachment of the manufacturer's statutory plate(s): Riveted

0.6. Location of the vehicle identification number: R, X347, Y5, Z380

1. Vehicle identification number: ☆1YSCUX319N1003927☆
conforms in all respects to the type described in EU type-approval (e13*168/2013*00522*05 type-approval
number including extension number) issued on (05, 11, 2021 date of issue) and

can be permanently registered in Member States having right/left-hand traffic and using metric/imperial units for the
speedometer.

NANJING, CHINA

(place)

15, 03, 2022

(date)

陈逸婷

(signature)

General construction characteristics

- 1.3. Number of axles: 2 and wheels: 2
- 1.3.1. Axles with twinned wheels: N.A.
- 1.3.2. Powered axles: R
- 6.2.4. Advanced braking system: ABS+CBS+Both-ABS and CBS+None

Main dimensions

- 2.2.1. Length: 1782 mm
- 2.2.2. Width: 727 mm
- 2.2.3. Height: 1087 mm
- 2.2.4. Wheelbase: 1217 mm
- 2.2.4.1. Wheelbase sidecar: N.A.
- 2.2.5. Track width: N.A.
- 2.2.5.1. Track width front: N.A.
- 2.2.5.2. Track width rear: N.A.
- 2.2.5.3. Track width sidecar: N.A.
- 2.2.10.6 Ground clearance between the axles: N.A.
- 2.2.15. Wheelbase to ground clearance ratio: N.A.
- 2.2.17. Seat height: N.A.

Masses

- 2.1.1. Mass in running order: 64 kg
- 2.1.2. Actual mass: 152 kg
- 2.1.3. Technically permissible maximum laden mass: 227 kg
- 2.1.3.1. Technically permissible maximum mass on front axle: 73 kg
- 2.1.3.2. Technically permissible maximum mass on rear axle: 154 kg
- 2.1.3.3. Technically permissible maximum mass on sidecar axle: N.A.
- 2.1.7. Technically permissible maximum towable mass: N.A.
- Braked: N.A. Unbraked: N.A.
- 2.1.7.1. Technically permissible maximum laden mass of the combination: N.A.
- 2.1.7.2. Technically permissible maximum mass at the coupling point: N.A.

Powertrain

- 3.1.1.1. Manufacturer: N.A.
- 3.1.1.2. Engine code (as marked on the engine or other means of identification): N.A.
- 3.2.1.2. Working principle of the combustion engine: internal-combustion engine (ICE)/positive-ignition/
compression-ignition/external-combustion engine (ECE)/turbine/compressed air-N.A.
- 3.2.1.4.1. Number of cylinders: N.A.
- 3.2.1.4.2. Arrangement of cylinders: L+V+O+S-N.A.
- 3.2.1.5. Engine capacity: N.A.
- 1.9. Maximum net power: N.A.
- 1.10. Ratio maximum net power/mass of the vehicle in running order: N.A.
- 3.2.3.1. Fuel type: mono-fuel/bi-fuel/flex-fuel-N.A.
- 3.2.3.2. Vehicle fuel combination: N.A.
- 3.2.3.2.1. Maximum amount of bio-fuel acceptable in fuel: N.A.
- 3.1.2.1. Manufacturer: Manufacturer 2: Taizhou Jinyu Electrical & Mechanical Co., Ltd.
- 3.1.2.2. Electric motor code (as marked on the engine or other means of identification): S02FA4W1300

D40-38

D40-38

3.3.4.	45/30 minutes power: 1.6 kW at 430 min ⁻¹	
3.1.3.1.	Manufacturer: N.A.	
3.1.3.2.	Application code (as marked on the engine or other means of identification):	N.A.
3.3.1.	Electric vehicle configuration: pure electric/hybrid electric/power—electric—	
3.3.5.2.	Category of hybrid electric vehicle: off-vehicle charging/off-vehicle charging	N.A.
3.9.2.	Maximum assistance factor: N.A.	
Maximum speed		
1.8.	Maximum speed of vehicle: 45 km/h	
3.9.3.	Maximum vehicle speed for which the electric motor gives assistance: N.A.	
Drive-train and control		
3.5.3.9.	Transmission (type): W	
3.5.4.	Gear ratios: N.A.	
3.5.4.1.	Final drive ratio: N.A.	
3.5.4.2.	Overall gear ratio in highest gear: N.A.	
Installation of tyres		
6.18.1.1.	Tyre size designation:	
Axe 1:	90/90-12 54J 2.15×12 250 kPa	
Axe 2:	90/90-12 54J 2.15×12 250 kPa	
Sidexcar wheel: N.A.		
Bodywork		
6.20.2.1.	Door configuration and number of doors:	N.A.
6.16.1.	Number of seating positions:	2
6.16.1.1.	Location and arrangement:	N.A.
Coupling devices		
7.2.8.	Type-approval number of coupling-device:	N.A.
Environmental performance		
4.0.1.	Environmental step: Euro (3/4/5/6*)	
4.0.6.	Sound level measured according to: N.A.	
4.0.6.1.	Stationary: N.A. at engine speed: N.A.	
4.0.6.2.	Drive-by: N.A.	
4.0.6.3.	Limit value for L _{urban} : N.A.	
3.2.15.	Exhaust emissions measured according to Regulation (EU) No 134/2014 including all amendments up to (EU) 2018/295	
3.2.15.1.	Type I test: tailpipe emissions after cold start, including the deterioration factor, if applicable:	
	CO:	N.A.
	THC:	N.A.
	MMHC:	N.A.
	NOx:	N.A.
	THC+NOx:	N.A.
	PM:	N.A.
3.2.15.2.	Type II test: tailpipe emissions at (increased) idle and free acceleration:	
	HC: N.A.	
	CO: N.A.	
3.2.15.3.	Smoke corrected absorption coefficient: N.A.	
Energy efficiency		
4.0.2.	Fuel consumption:	N.A.
4.0.3.	CO ₂ emissions:	N.A.
4.0.4.	Energy consumption:	Electric Motor: Jinyu: 30 Wh/km
4.0.5.	Electric range:	Electric Motor: Jinyu: 73 km
Conversion of the performance of the vehicle:		
8.1.	Vehicle appropriate for converting its performance level between subcategories (L3e/L4e)-A3 and vice versa: yes/no-N.A.	
Additional information:		
9.1.	Remarks:	N.A.
9.2.	Exemptions:	N.A.