



<u>Item</u>	<u>Description</u>	<u>Qty</u>
	<u>Unit</u>	
1.	ALTEC Model AT40-G telescopic articulating Aerial device with ISO-Boom.	1
2.	AT40G Unit Model	1
3.	Post style pedestal mounting	1
4.	Poly Hydraulic Reservoir, Pedestal Mounted, 7 Gallon (Includes Sight Gauge)	1
5.	Single One-Man End-Mounted Platform With 180 Degree Rotator, 24 X 30 X 42. Platform is rated at 400 pounds. Control panel on platform dashboard provides controls for auxiliary functions. Includes emergency stop (push-pull) switch and rocker switches, which operate platform leveling, platform rotation, tools, and battery selector (for fiber-optic controls system). Composite fiberglass platform mounting bracket. (AT40G)	1
6.	Platform Leveling At Lower Controls. AT40-G	1
7.	Two (2) Platform Steps	1
8.	Soft nylon reinforced vinyl platform cover for a 24 x 30 inch platform	1
9.	Platform liner for a 24 x 30 x 42 inch platform	1
10.	4-Function Single Handle Fiber-Optic Controller.	1
11.	Engine Start/Stop at the upper controls actuated through the Fiber-Optic controls system with Secondary Stowage System (AT40G)	1
12.	Manual lowering valve located at the boomtip. For use in emergency situations to allow the operator to lower the boom to the ground	1
13.	Powder coat unit Altec White.	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
14.	Additional Unit Option	1
	<p>Sales Text: Manufacture to CSA C225 and Include - Emergency Stop at upper & lower controls per CSA Compliance with CAN/CSA-225 utilizing Red knob selector lever as emergency stop. (ANSI Standard) AND Lanyard Attachment to be rated @ 5,000 lbs. per Ontario OSHA regulation 213. Last Updated By: Dawn Vandel Hr Auto-Ended on 10-SEP-2019 15:10</p>	
15.	Unit to be Manufactured to Canadian Standards per CSA C225	1
	<u>Unit and Hydraulic Acc.</u>	
16.	HVI-22 Hydraulic Oil (Standard).	9
17.	Standard Pump For PTO	1
18.	Hot shift PTO for automatic transmission	1
	<u>Body</u>	
19.	132 Inch Small Aerial Body for an 84 Inch CA Chassis with 29 Inch Long Tailshelf, To Meet The Following Specifications:	1
	<ul style="list-style-type: none"> A. Basic Body Fabricated From Fiberglass B. All Doors Are Full, Double Paneled, Self-Sealed With Hollow Core C. 304 Stainless Steel Door Hinges With 316 Stainless Steel Pin D. All Doors Contain Stainless Steel, Flush Mounted, Paddle Activated Rotary Style Latches With Two-Stage Locking, Including Keyed Locks And Adjustable Strikers. E. 3 Inch Aluminum Tube Body Frame With 3/16 Inch Smooth Aluminum Floor F. Aluminum Door Header Drip Rail At Top For Maximum Weather Protection. G. Automotive Type Non-Porous Door Seals (Double Bulb Style) Fastened To The Door Facing. H. Recessed Doors I. 132 Inch Body Length J. 94 Inch Body Width K. 39 Inch Body Compartment Height L. 20 Inch Body Compartment Depth M. Body Color - White Gelcoat N. Gelcoat Exterior Finish On All Fiberglass Parts O. 6 Inch Tall Composite Tailboard Installed At The Rear Of Body Cargo Area P. Stainless Steel Rotary Paddle Latches With Locks Q. Gas Props On All Vertical Doors R. Chains On All Horizontal Doors S. Standard Gang Locking System T. Fiberglass-Constructed Body Compartment Shelves U. Hotstick Shelf Extending Full Length Of Body On Curbside. V. Drop-Down Hotstick Door For One (1) Shelf W. Two (2) Hotstick Brackets X. 1st Vertical Streetside (SS) - Two (2) Adjustable Shelves With Removable Dividers On 4 Inch Centers Y. 2nd Vertical Streetside (SS) - Two (2) Adjustable Shelves With Removable Dividers On 4 Inch Centers Z. 1st Horizontal Streetside (SS) - One (1) Adjustable Shelf With Removable Dividers On 4 Inch Centers AA. Rear Vertical Streetside (SS) - Six (6) Locking Swivel Hooks On An Adjustable Rail (2-2-2) 	

<u>Item</u>	<u>Description</u>	<u>Qty</u>
AB.	1st Vertical Curbside (CS) - Seven (7) Locking Swivel Hooks On An Adjustable Rail (2-3-2)	
AC.	2nd Vertical Curbside (CS) - One (1) Adjustable Shelf With Removable Dividers On 4 Inch Centers	
AD.	1st Horizontal Curbside (CS) - Vacant	
AE.	Rear Vertical Curbside (CS) - Two (2) Adjustable Shelves With Removable Dividers On 4 Inch Centers	
AF.	Aluminum Rock Guards Installed In Front Of Body At The Bottom	
AG.	29 Inch Aluminum Tailshelf With Integrated Side Access Steps, Two Wheel Chock Holders, One (1) Small Sloped Grab Handle And One (1) U-Shaped Grab Handle At Steps Installed At Rear Of Body	

Body and Chassis Accessories

20.	Aluminum Tailshelf, 94" W x 29" L With Curbside Access Steps, With Wheel Chock Holders	1
-----	--	---

Sales Text: Include block at the rear and chain retainer with lockable hasp to secure wheel chocks in holder.

-Step height must be below 27" per ANSI

Last Updated By: Hannah E Bridges on 18-AUG-2020 13:06

21.	ICC Underride Protection	1
22.	Combination 2 Ball (10,000 LB MGTW) And Pintle Hitch (16,000 LB MGTW)	1
23.	Set Of Eye Bolts for Trailer Safety Chain, installed one each side of towing device mount.	1
24.	Rear Torsion Bar Installed On Chassis	1
25.	Appropriate counterweight added for stability.	1
26.	Platform Rest, Rigid with Rubber Tube	1
27.	Platform to be side stowed	1
28.	Boom Rest for a Telescopic Unit	1
29.	Ratchet Strap For Boom Tie-Down	1
30.	Mud Flaps With Altec Logo (Pair)	1
31.	Wheel Chocks, Rubber, 9.75" L x 7.75" W x 5.00" H, with 4" L Metal Hairpin Style Handle (Pair)	1
32.	Small Grab Handle Installed At Rear	1
33.	Slope Indicator Assembly For Machine Without Outriggers	1
34.	5 LB Fire Extinguisher With Light Duty Bracket, Installed (In Cab or Inside Compartment Only)	1

Sales Text: Installed in the Cab.

Last Updated By: Dawn Vandel Hr Auto-Ended on 10-SEP-2019 15:10

35.	Custom Triangular Reflector Kit	1
-----	---------------------------------	---

<u>Item</u>	<u>Description</u>	<u>Qty</u>
<p>Sales Text: Triangular reflector Kit Containing 3 Reflectors and 3 Fuses, (20 Minutes Each) Installed per DEPS 042. Last Updated By: Dawn Vandel Hr Auto-Ended on 10-SEP-2019 15:10</p>		
36.	Vinyl manual pouch for storage of all operator and parts manuals	1
37.	Additional Body/Chassis Accessory	1
<p>Sales Text: Provide a metal protective heat shield (plate) on the bottom of the body compartment right above the exhaust so it does not blacken the bottom. Last Updated By: Dawn Vandel Hr Auto-Ended on 10-SEP-2019 15:10</p>		
<u>Electrical Accessories</u>		
38.	Lights and reflectors in accordance with FMVSS #108 lighting package. (Complete LED, including LED reverse lights)	1
39.	Altec Standard Amber LED Strobe Light with Brush Guard	1
<p>Sales Text: Mounted on SS front of body visible above the chassis cab. Last Updated By: Dawn Vandel Hr Auto-Ended on 10-SEP-2019 15:10</p>		
40.	Single tone back up alarm installed between the chassis frame rails at the rear of the chassis. To work in conjunction with chassis reverse drive system	1
41.	PTO Hour Meter, Digital, with 10,000 Hour Display	1
42.	7-Way Trailer Receptacle (Pin Type) Installed At Rear	1
43.	Ford Upfitter Switches (Supplied with Chassis)	1
44.	Start/Stop/Throttle Module, 12 Volt System	1
45.	Install secondary stowage system.	1
46.	PTO Indicator Light Installed In Cab	1
<u>Finishing Details</u>		
47.	Powder Coat Unit Altec White	1
48.	Altec Standard; Components mounted below frame rail shall be coated black by Altec. i.e. step bumpers, steps, frame extension, pintle hook mount, dock bumper mounts, D-rings, receiver tubes, accessory mounts, light brackets, under-ride protection, etc. Components mounted to under side of body shall be coated black by Altec. i.e. Wheel chock holders, mud flap brackets, pad carriers, boxes, lighting brackets, steps, and ladders.	1
49.	Apply Non-Skid Coating to all walking surfaces	1
50.	English Safety And Instructional Decals	1
51.	Vehicle Height Placard - Installed In Cab	1
<p>Sales Text: Metric and Imperial Last Updated By: Dawn Vandel Hr Auto-Ended on 10-SEP-2019 15:10</p>		

<u>Item</u>	<u>Description</u>	<u>Qty</u>
52.	Install Canada Specific Completed Vehicle Sticker. (Reference Chassis Bulletin T33)	1
53.	Placard, HVI-22 Hydraulic Oil	1
54.	Custom Inspection	1
<p>Sales Text: The aerial device shall be manufactured and installed in accordance with CSA-C225. Last Updated By: Dawn Vandell Hr Auto-Ended on 10-SEP-2019 15:10</p>		
55.	Dielectric test unit according to ANSI requirements.	1
56.	Stability test unit according to ANSI requirements.	1
57.	Focus Factory Build	1
58.	Delivery Of Completed Unit	1
59.	Inbound Freight	1
60.	Unit to be Manufactured to Canadian Standards per CSA C225, Final Assembly	1
61.	AT40G FA Installation	1
62.	Stock Unit	1
<u>Chassis</u>		
63.	Altec Supplied Chassis	1
64.	Chassis	1
65.	2019 Model Year	1
66.	Ford F550	1
67.	4x4	1
68.	84 Clear CA (Round To Next Whole Number)	1
69.	Regular Cab	1
70.	Chassis Cab	1
71.	Chassis Color - White	1
72.	Chassis Wheelbase Length - 169	1
73.	Ford 6.7L Power Stroke Diesel	1
74.	Ford Torqshift 6-Speed (6R140) Automatic Transmission (w/PTO Provision)	1
75.	GVWR 19,500 LBS	1
76.	7,000 LBS Front GAWR	1
77.	Spring Suspension	1
78.	14,706 LBS Rear GAWR	1

