

[EXTERNAL VISUAL INSPECTION REPORT VK1]

Date: Aug 17 25

CK Inspections

TC Reg: 25-1009; Exp: 2027-12-01
 164075 Twp. Rd. 542
 Mundare, Alberta T0B 3H0
 780-722-4462

Client: MFP Resources CorpAddress: 5920 76 Ave NWCity: EdmontonPostal Code: T6B 0A6Phone: 780-465-9668

- ☐ Lined ☐ Insulated
☐ Loaded by vacuum ☐ Corrosive service

- ☐ Both lined and insulated
☐ Dedicated service:

Tank serial number: ST-10136-09VIN: LRNAT39369R010136Tank Spec: Det 406-ALOrig. test date: 11/08

Lining Material: _____

Unit Number: 317Date of MFR: 11/08Comp/Cert date: 11/08CTMV orig. Test date: 11/08CTMV Cert Date: 11/08Manufacturer: BealAssembler: Beal

TCRN: _____

MDIN: _____

MAWP: 22.5 kPa/PsiDesign Pressure: 5 Kpa/PsiMan. Thickness Head: 4.98mmMin. Thickness Head: 4.39mmMan. Thickness Shell: 4.76mmMin. Thickness Shell: 4.06mmExposed surface area: 35.35m²Volumetric Capacity: 16550 / 16550Design Temp. Range: -29 C to 66 CMax Lading Density: 1.9 kg/lShell Material: SA-516-1132Head Material: SA-516Weld Material: SA-516Max Load Rate: 2839 lpm at 6.8 kPaMax Payload: 22650kgMax Unload Rate: 1703 lpm at _____ kPaTank Design Pressure: 36psi

Heating Sys. Pressure: _____ kPa/psi

Retest Pressure: 34.5kpa

Heating Sys. Temperature: _____ C/F

Inspect jacketing for dents, digs, scrapes, gouges, perforations, stains or other defects or signs of damage to the inner vessel or any other condition that might make it unsafe as per 7.2.1(a)	Pass ☐	Fail ☐	Rep. ☐	NA ☒
Inspect the entire area of head and shell for dents, gouges, bulges, corrosion, abrasion, cracks or signs of leakage or other conditions that might render it unsafe for transport as per 7.2.1(a)	Pass ☒	Fail ☐	Rep. ☐	NA ☐
Inspect the entire length of every weld for cracks, defects or signs of leakage as per 7.2.1(a)	Pass ☒	Fail ☐	Rep. ☐	NA ☐
Ensure devices for tightening manhole covers are operative and covers are leak tight as per 7.2.1(b)	Pass ☒	Fail ☐	Rep. ☐	NA ☐
Check all valves, vents, emergency devices and remote closures for corrosion, distortion, cracks, signs of weakness and loose or missing fasteners as per 7.2.1(c)	Pass ☒	Fail ☐	Rep. ☐	NA ☐
Ensure all required markings are legible; including manway, PRV, couplings, Valves and specification plate as per 7.2.1(e)	Pass ☒	Fail ☐	Rep. ☐	NA ☐
Inspect supporting structures, pads, bolsters, tie-downs and protective devices for dents, distortion, cracks, signs of weakness and loose or missing fasteners as per 7.2.1(f)	Pass ☒	Fail ☐	Rep. ☐	NA ☐
Ensure accompanying or mounted hoses comply with inspection and marking requirements as per 7.2.10.4	Pass ☐	Fail ☐	Rep. ☐	NA ☒
Check to ensure voids are unplugged and show no signs of leakage as per 7.2.1.2	Pass ☒	Fail ☐	Rep. ☐	NA ☐
Corroded or abraded areas are thickness tested as per 7.2.1.3	Pass ☒	Fail ☐	Rep. ☐	NA ☐

[EXTERNAL VISUAL INSPECTION REPORT VK1]

2

All pressure relief devices are inspected for corrosion or damage as per 7.2.1.4	Pass ☒	Fail ☐	Rep. ☐	NA ☐
If lading is corrosive to PRV: re-closing pressure relief valves are replaced or tested as per 7.2.1.4(b)	Pass ☐	Fail ☐	Rep. ☐	NA ☒
Gaskets on full opening rear head is inspected and replaced if cut, cracked or split as per 7.2.1.5	Pass ☐	Fail ☐	Rep. ☐	NA ☒
Internal self-closing valve and off-truck emergency shut down system tested as per 7.2.1.6	Pass ☒	Fail ☐	Rep. ☐	NA ☐
Ensure that all bolts or nuts on any flanged connection or blank flange are in place and properly tightened as per 7.2.1(d)	Pass ☒	Fail ☐	Rep. ☐	NA ☐

PRV: Tested Y / (N)

PRV type	Set to discharge	Opening pressure	Re-seat pressure	Disposition: Reinstalled/Repaired/Replaced

*PRV's should be numbered from front to rear of tank

Leakage Test

Compartment #	Test Start psi	Test Finish psi	Hold time
1	2.5	2.5	5 min
2	2.5	2.5	5 min
3			
4			
5			

Testing

Venting devices hold pressure as required, if removed, they are bench tested and hold pressure as required	Pass ☒	Fail ☐	Rep. ☐	NA ☐
Manways and closures inspected for leaks and deformation	☒	☐	☐	☐
Flanged connections checked for leakage	☒	☐	☐	☐
Inspect the entire area of the head, shell and welds for leaks or deformation including voids and adjacent compartments	☒	☐	☐	☐
Test pressure maintained for a minimum of 5 minutes	☒	☐	☐	☐
All leaks are repaired before the tank is marked	☒	☐	☐	☐

Defects found

1 vic off Internal pipe Replaced
Pump off line vic Replaced

Constructed of: ☐ Quenched and Tempered steel (QT) ☐ Non-quenched (NQT)
☐ Stress relieved after Mfr.
☐ Stress relieved after repair: ☐ Local stress relief ☐ Complete stress relief

Tank Disposition

☒ Pass ☐ Repaired/Re-tested/Returned to service
☐ Fail/removed from service ☐ Removed from facility

Services Provided by:
Standard Solutions

[EXTERNAL VISUAL INSPECTION REPORT VK1]

3

Inspector name: Kevin Jones
Inspector Signature: [Signature]
Date signed: Aug 11 25
Inspection expires: Aug 2026

Tester name: Kevin Jones
Tester Signature: [Signature]
Date signed: Aug 12 25
Markings applied: 08/25 VK 1009

Internal Visual Inspections - ST-10136-09 - 2023-12-04

Authoring Information

Created By	Kevin Jamieson 7804649612
Facility	A.R.S. Trucking & Welding Ltd. 780-464-9612 10-40 Challenger Crescent Sherwood Park, AB T8H 2J6
Created	2023-12-04 11:31:37
Updated	2023-12-04 11:31:37

Client

Company	MFP MOHAWK FUEL PRODUCTS 5920 76 AVE NW EDMONTON, AB T6B0A6
Contact	MFP PRODUCTS 7804659668

Tank Data

Ser. No.	ST-10136-09
Unit Number	P1085
TC Spec.	DOT 406
Date of mfr.	2008-11
Cert. date	2008-11
VIN	1BN2T39369B010136
Tank mfr.	Beall
Assembler	Beall
MAWP	22.8 Kpa
Test P.	34.5 Kpa
Mfd. head thick	4.98 mm
Min. head thick	4.39 mm
Mfd. shell thick	4.78 mm
Min. shell thick	4.39 mm
Exposed Surface	70 m2
Cap.	33100 litres
Original Test Date	2008-11

Internal Visual Inspection

Inspection Date	2023-12-04
-----------------	------------

Inspection Expiry Date 2028-12-04**Inspection** Lining test completed if lined as per 7.2.2.1(c)
PassEnter the tank and inspect for: dents, gouges, cracks, corrosion, abrasions or signs of leakage in the shell or heads including bulkheads as per 7.2.2.1(a)
PassInspect piping, valves and gaskets for damage as per 7.2.2.1(a)
PassInspect every weld for cracks, defects or signs of leakage as per 7.2.2.1(b)
PassCorroded areas are thickness tested if found as per 7.2.2.1(d)
Not Applicable**Defects** No defects found.**PRV List**

Type of PRV	Manufacturer	PRV Criteria	Discharge Pressure	Opening Pressure	Reseating Pressure	Disposition
-------------	--------------	-----------------	-----------------------	---------------------	-----------------------	-------------

Tank Disposition**Current Disposition** Passed / No Defects Found**Approval****Inspector**
Kevin Jamieson**Tester**
Kevin jamieson

Service provided by eStandard Solutions.

Pressure Tests - ST-10136-09 - 2023-12-04

Authoring Information

Created By	Kevin Jamieson 7804649612
Facility	A.R.S. Trucking & Welding Ltd. 780-464-9612 10-40 Challenger Crescent Sherwood Park, AB T8H 2J6
Created	2023-12-04 11:33:14
Updated	2023-12-04 11:33:14

Client

Company	MFP MOHAWK FUEL PRODUCTS 5920 76 AVE NW EDMONTON, AB T6B0A6
Contact	MFP PRODUCTS 7804659668

Tank Data

Ser. No.	ST-10136-09
Unit Number	P1085
TC Spec.	DOT 406
Date of mfr.	2008-11
Cert. date	2008-11
VIN	1BN2T39369B010136
Tank mfr.	Beall
Assembler	Beall
MAWP	22.8 Kpa
Test P.	34.5 Kpa
Mfd. head thick	4.98 mm
Min. head thick	4.39 mm
Mfd. shell thick	4.78 mm
Min. shell thick	4.39 mm
Exposed Surface	70 m2
Cap.	33100 litres
Original Test Date	2008-11

Pressure Test

Inspection Date	2023-12-04
Inspection Expiry Date	2028-12-04
Test Medium	Air

No. of Compartments

1

Compartment 1**Start (psi)****End (psi)****Hold Time**

5

5

10

Test Results

When venting devices are removed, they are bench tested and meet the requirements for the tank

Pass

Product piping with all valves and accessories in place and operative must be pressure tested at not less than 80% MAWP

Pass

When removed from the pressure supply, the test pressure is retained for the specified time for the pneumatic or hydrostatic test

Pass

Inspect the entire area of the head, shell and welds for leaks or deformation. If defects found note the location on the report

Pass

Defects

No defects found.

PRV List

Type of PRV	Manufacturer	PRV Criteria	Discharge Pressure	Opening Pressure	Reseating Pressure	Disposition
-------------	--------------	--------------	--------------------	------------------	--------------------	-------------

Tank Disposition**Current Disposition** Passed / No Defects Found**Approval****Inspector**

Kevin Jamieson

Tester

Kevin jamieson

Upper Coupler Inspections - ST-10136-09 - 2023-12-04

Authoring Information

Created By	Kevin Jamieson 7804649612
Facility	A.R.S. Trucking & Welding Ltd. 780-464-9612 10-40 Challenger Crescent Sherwood Park, AB T8H 2J6
Created	2023-12-04 11:35:23
Updated	2023-12-04 11:35:23

Client

Company	MFP MOHAWK FUEL PRODUCTS 5920 76 AVE NW EDMONTON, AB T6B0A6
Contact	MFP PRODUCTS 7804659668

Tank Data

Ser. No.	ST-10136-09
Unit Number	P1085
TC Spec.	DOT 406
Date of mfr.	2008-11
Cert. date	2008-11
VIN	1BN2T39369B010136
Tank mfr.	Beall
Assembler	Beall
MAWP	22.8 Kpa
Test P.	34.5 Kpa
Mfd. head thick	4.98 mm
Min. head thick	4.39 mm
Mfd. shell thick	4.78 mm
Min. shell thick	4.39 mm
Exposed Surface	70 m2
Cap.	33100 litres
Original Test Date	2008-11

Upper Coupler Inspection

Inspection Date	2023-12-04
------------------------	------------

Inspection Expiry Date 2028-12-04

Inspection Corroded or abraded areas
Pass

Cracks or defects in welds
Pass

Dents or distortions
Pass

Defects No defects found.

PRV List

Type of PRV	Manufacturer	PRV Criteria	Discharge Pressure	Opening Pressure	Reseating Pressure	Disposition
# 1						

Tank Disposition

Current Disposition Passed / No Defects Found

Approval



Inspector
Kevin Jamieson

Tester
Kevin jamieson

Service provided by eStandard Solutions.

[EXTERNAL VISUAL INSPECTION REPORT VK1]

Date: Aug 11, 25

CK Inspections

TC Reg: 25-1009; Exp: 2027-12-01

164075 Twp. Rd. 542

Mundare, Alberta T0B 3H0

780-722-4462

Client: MFP Resources CorpAddress: 5920 76 Ave NWCity: EdmontonPostal Code: T6B-0A6Phone: 780-465-9668☐ Lined☐ Loaded by vacuum☐ Insulated☐ Corrosive service☐ Both lined and insulated☐ Dedicated service:Tank serial number: ST-10137-09Tank Spec: Dot 406-A1

Lining Material:

Date of MFR: 11/08CTMV orig. Test date: 11/08Manufacturer: Beull

TCRN:

MAWP: 22.5 Kpa/PsiMan. Thickness Head: 4.98mmMan. Thickness Shell: 4.78mmExposed surface area: 57m²Design Temp. Range: -29 C to 66 CShell Material: SA54-H32Head Material: SA54-Q Weld Material: SA56A1Max Load Rate: 2839 lpm at 6.8 kPaMax Unload Rate: 1703 lpm at kPaHeating Sys. Pressure: kPa/psiHeating Sys. Temperature: C/FVIN: 1BN2T99269B010137Orig. test date: 11/08Unit Number: 318Comp/Cert date: 11/08CTMV Cert Date: 11/08Assembler: Beull

MDIN:

Design Pressure: 5 Kpa/PsiMin. Thickness Head: 4.39mmMin. Thickness Shell: 4.06mmVolumetric Capacity: 25998LMax Lading Density: 9 kg/lMax Payload: 25422kgTank Design Pressure: 36psiRetest Pressure: 34.5kpa

Inspect jacketing for dents, digs, scrapes, gouges, perforations, stains or other defects or signs of damage to the inner vessel or any other condition that might make it unsafe as per 7.2.1(a)

Pass	Fail	Rep.	NA
☐	☐	☐	☒

Inspect the entire area of head and shell for dents, gouges, bulges, corrosion, abrasion, cracks or signs of leakage or other conditions that might render it unsafe for transport as per 7.2.1(a)

Pass	Fail	Rep.	NA
☒	☐	☐	☐

Inspect the entire length of every weld for cracks, defects or signs of leakage as per 7.2.1(a)

Pass	Fail	Rep.	NA
☒	☐	☐	☐

Ensure devices for tightening manhole covers are operative and covers are leak tight as per 7.2.1(b)

Pass	Fail	Rep.	NA
☒	☐	☐	☐

Check all valves, vents, emergency devices and remote closures for corrosion, distortion, cracks, signs of weakness and loose or missing fasteners as per 7.2.1(c)

Pass	Fail	Rep.	NA
☒	☐	☐	☐

Ensure all required markings are legible; including manway, PRV, couplings, Valves and specification plate as per 7.2.1(e)

Pass	Fail	Rep.	NA
☒	☐	☐	☐

Inspect supporting structures, pads, bolsters, tie-downs and protective devices for dents, distortion, cracks, signs of weakness and loose or missing fasteners as per 7.2.1(f)

Pass	Fail	Rep.	NA
☒	☐	☐	☐

Ensure accompanying or mounted hoses comply with inspection and marking requirements as per 7.2.10.4

Pass	Fail	Rep.	NA
☐	☐	☐	☒

Check to ensure voids are unplugged and show no signs of leakage as per 7.2.1.2

Pass	Fail	Rep.	NA
☒	☐	☐	☐

Corroded or abraded areas are thickness tested as per 7.2.1.3

Pass	Fail	Rep.	NA
☐	☐	☐	☐

[EXTERNAL VISUAL INSPECTION REPORT VK1]

2

All pressure relief devices are inspected for corrosion or damage as per 7.2.1.4	Pass	Fail	Rep.	NA
If lading is corrosive to PRV: re-closing pressure relief valves are replaced or tested as per 7.2.1.4(b)	Pass	Fail	Rep.	NA
Gaskets on full opening rear head is inspected and replaced if cut, cracked or split as per 7.2.1.5	Pass	Fail	Rep.	NA
Internal self closing valve and off truck emergency shut down system tested as per 7.2.1.6	Pass	Fail	Rep.	NA
Ensure that all bolts or nuts on any flanged connection or blank flange are in place and properly tightened as per 7.2.1(d)	Pass	Fail	Rep.	NA

PRV: Tested Y/(N)

PRV type	Set to discharge	Opening pressure	Re-seat pressure	Disposition: Reinstalled/Repaired/Replaced

*PRV's should be numbered from front to rear of tank

Leakage Test

Compartment #	Test Start psi	Test Finish psi	Hold time
1			
2			
3	2.5 psi	2.5 psi	5 min
4			
5			

Testing

Venting devices hold pressure as required, if removed, they are bench tested and hold pressure as required	Pass	Fail	Rep.	NA
Manways and closures inspected for leaks and deformation	Pass	Fail	Rep.	NA
Flanged connections checked for leakage	Pass	Fail	Rep.	NA
Inspect the entire area of the head, shell and welds for leaks or deformation including voids and adjacent compartments	Pass	Fail	Rep.	NA
Test pressure maintained for a minimum of 5 minutes	Pass	Fail	Rep.	NA
All leaks are repaired before the tank is marked	Pass	Fail	Rep.	NA

Defects found

No defects Found

Constructed of: ☐ Quenched and Tempered steel (QT) ☐ Non-quenched (NQT)
☐ Stress relieved after Mfr.
☐ Stress relieved after repair: ☐ Local stress relief ☐ Complete stress relief

Tank Disposition

☒ Pass ☐ Repaired/Re-tested/Returned to service
☐ Fail/removed from service ☐ Removed from facility

Services Provided by:
 Standard Solutions

[EXTERNAL VISUAL INSPECTION REPORT VK1]

3

Inspector name: Kevin Jones
Inspector Signature: [Signature]
Date signed: 08/12/25
Inspection expires: Aug 2026

Tester name: Kevin Jones
Tester Signature: [Signature]
Date signed: Aug 12-25
Markings applied: 08/25 VK 1009

Internal Visual Inspections - ST-10137-09 - 2023-12-04

Authoring Information

Created By	Kevin Jamieson 7804649612
Facility	A.R.S. Trucking & Welding Ltd. 780-464-9612 10-40 Challenger Crescent Sherwood Park, AB T8H 2J6
Created	2023-12-04 10:35:41
Updated	2023-12-04 10:35:41

Client

Company	MFP MOHAWK FUEL PRODUCTS 5920 76 AVE NW EDMONTON, AB T6B0A6
Contact	MFP PRODUCTS 7804659668

Tank Data

Ser. No.	ST-10137-09
Unit Number	P1005A 318
TC Spec.	DOT 406
Date of mfr.	2008-11
Cert. date	2008-11
VIN	1BN2T29269B010137
Tank mfr.	Beall
Assembler	Beall
MAWP	22.5 psi
Test P.	34.5 psi
Mfd. head thick	4.98 mm
Min. head thick	4.39 mm
Mfd. shell thick	4.78 mm
Min. shell thick	4.06 mm
Exposed Surface	57 m2
Cap.	25998 litres
Original Test Date	2008-11

Internal Visual Inspection

Inspection Date	2023-12-04
-----------------	------------

Inspection Expiry Date 2028-12-04**Inspection** Lining test completed if lined as per 7.2.2.1(c)
Not Applicable**Enter the tank and inspect for: dents, gouges, cracks, corrosion, abrasions or signs of leakage in the shell or heads including bulkheads as per 7.2.2.1(a)**

Pass

Inspect piping, valves and gaskets for damage as per 7.2.2.1(a)

Pass

Inspect every weld for cracks, defects or signs of leakage as per 7.2.2.1(b)



Pass

Corroded areas are thickness tested if found as per 7.2.2.1(d)

Pass

Defects No defects found.**PRV List**

Type of PRV	Manufacturer	PRV Criteria	Discharge Pressure	Opening Pressure	Reseating Pressure	Disposition
-------------	--------------	--------------	--------------------	------------------	--------------------	-------------

Tank Disposition**Current Disposition** Passed / No Defects Found**Approval****Inspector**
Kevin Jamieson**Tester**
Kevin jamieson

Service provided by eStandard Solutions.

Upper Coupler Inspections - ST-10137-09 - 2023-12-04

Authoring Information

Created By	Kevin Jamieson 7804649612
Facility	A.R.S. Trucking & Welding Ltd. 780-464-9612 10-40 Challenger Crescent Sherwood Park, AB T8H 2J6
Created	2023-12-04 10:42:41
Updated	2023-12-04 10:42:41

Client

Company	MFP MOHAWK FUEL PRODUCTS 5920 76 AVE NW EDMONTON, AB T6B0A6
Contact	MFP PRODUCTS 7804659668

Tank Data

Ser. No.	ST-10137-09
Unit Number	P1005A 318
TC Spec.	DOT 406
Date of mfr.	2008-11
Cert. date	2008-11
VIN	1BN2T29269B010137
Tank mfr.	Beall
Assembler	Beall
MAWP	22.5 psi
Test P.	34.5 psi
Mfd. head thick	4.98 mm
Min. head thick	4.39 mm
Mfd. shell thick	4.78 mm
Min. shell thick	4.06 mm
Exposed Surface	57 m2
Cap.	25998 litres
Original Test Date	2008-11

Upper Coupler Inspection

Inspection Date	2023-12-04
-----------------	------------

Inspection Expiry Date 2028-12-04**Inspection**
Corroded or abraded areas
Pass**Cracks or defects in welds**
Pass**Dents or distortions**
Pass**Defects** No defects found.**PRV List**

Type of PRV	Manufacturer	PRV Criteria	Discharge Pressure	Opening Pressure	Reseating Pressure	Disposition
# 1						

Tank Disposition**Current Disposition** Passed / No Defects Found**Approval****Inspector**
Kevin Jamieson**Tester**
Kevin jamieson

Service provided by eStandard Solutions.

Pressure Tests - ST-10137-09 - 2023-12-04

Authoring Information

Created By	Kevin Jamieson 7804649612
Facility	A.R.S. Trucking & Welding Ltd. 780-464-9612 10-40 Challenger Crescent Sherwood Park, AB T8H 2J6
Created	2023-12-04 10:41:4
Updated	2023-12-04 11:4:24
Client	
Company	MFP MOHAWK FUEL PRODUCTS 5920 76 AVE NW EDMONTON, AB T6B0A6
Contact	MFP PRODUCTS 7804659668

Tank Data

Ser. No.	ST-10137-09
Unit Number	P1085A
TC Spec.	DOT 406
Date of mfr.	2008-11
Cert. date	2008-11
VIN	1BN2T29269B010137
Tank mfr.	Beall
Assembler	Beall
MAWP	22.5 psi
Test P.	34.5 psi
Mfd. head thick	4.98 mm
Min. head thick	4.39 mm
Mfd. shell thick	4.78 mm
Min. shell thick	4.06 mm
Exposed Surface	57 m2
Cap.	25998 litres
Original Test Date	2008-11

Pressure Test

Inspection Date	2023-12-04
Inspection Expiry Date	2028-12-04
Test Medium	Air

No. of Compartments 2

Compartment 1	Start (psi)	End (psi)	Hold Time
	5	5	10

Test Results When venting devices are removed, they are bench tested and meet the requirements for the tank
Pass

Product piping with all valves and accessories in place and operative must be pressure tested at not less than 80% MAWP
Pass

When removed from the pressure supply, the test pressure is retained for the specified time for the pneumatic or hydrostatic test
Pass

Inspect the entire area of the head, shell and welds for leaks or deformation. If defects found note the location on the report
Pass


Defects No defects found.

PRV List

Type of PRV	Manufacturer	PRV Criteria	Discharge Pressure	Opening Pressure	Reseating Pressure	Disposition
-------------	--------------	--------------	--------------------	------------------	--------------------	-------------

Tank Disposition

Current Disposition Passed / No Defects Found

Approval

Inspector
Kevin Jamieson

Tester
Kevin Jamieson