

X3

 1840 Kryczka Pl. Kamloops, BC V1S 1S4	TC Reg. No. 25-0704	External Visual Inspection Report	
	Work Order No.	R001012	
	Client Name	G & B Fuels Incorporated.	
	Client Ph. Number	403-273-5111	
	Date	02-18-2025	

Address:	59 Technology Way SE	Unit Number:	241A
	Calgary, AB	License Plate Number:	5KD5 39
	T3S 0B9	Tank Manufacturer:	Advance
Tank VIN Num.:	2AEABSAH1AR000116	Tank Assembler:	Advance
Truck VIN Num.:	N/A	Tank Specification:	TC 406
TCRN:	N/A	MDIN:	8053

	Top	Sides	Bottom		
Min. Shell Thickness:	4.39	4.39	5.97	Tank Lined:	No
Min. Head Thickness:	5.97			Tank Insulated:	No
				Special Service (Corrosive Etc.):	No


MAWP:	22.7	kPa	Month	Year	Configuration
Test Pressure:	34.5	kPa	Cert Date:	11	9
Design Pressure	N/A	PSI	Mfg Date:	11	9
					B Train Lead

Comp 1	Comp 2	Comp 3	Comp 4	Comp 5	Comp 6	Total
18500	5000	12000	N/A	N/A	N/A	35500

Volumetric Capacity In Litres

Items Inspected	N/A	Repairs Required	Corrected	Complies
7.2.1.1(e) Ensuring that specification and other markings on the tank are legible; if metal identification plates are missing or illegible, the requirements of Clause 7.7 shall apply.	Tank Attachment	☐	☐	☒
	Legible	☐	☐	☒
	Data Complete	☐	☐	☒
	Manhole Lid Markings	☐	☐	☒
	Emergency Shutoff	☐	☐	☒
7.2.1.1(a) Without removing insulation or jacketing, checking for corroded areas, dents, distortions, defects in welds, defects in piping, and any other condition, including leakage, that indicates weakness in the tank that might render it unsafe for transportation.	Barrel	☐	☐	☒
	Attachments	☐	☐	☒
	Piping	☐	☐	☒
	Flexible Couplings	☐	☐	☒
	Pump Bearings	☒	☐	☐
7.2.1.1(b) Ensuring that devices for tightening manhole covers are operative and that the covers are leaktight.	Clamping Ring	☐	☐	☒
	Attachments	☐	☐	☒
	Coagulation	☐	☐	☒
7.2.1.1(c) Ensuring proper functioning of all valves, vents, emergency devices, excess-flow valves, remote closure devices, ensuring that they are free of corrosion, distortion, or any other damage that would prevent their normal operation.	Vapour Vent Operation	☐	☐	☒
	Emergency Valve	☐	☐	☒
	Piping Valves	☐	☐	☒
	Remote Closure Device	☐	☐	☒
	Manifold Valves	☒	☐	☐
7.2.1.1(d) Ensuring that all bolts or nuts on any flanged connection or blank flange are in place and properly tightened.	Manifold Flanges	☒	☐	☐
	Pump & Meter Flanges	☒	☐	☐
	Piping Flanges	☐	☐	☒

Items Inspected		N/A	Repairs Required	Corrected	Complies
7.2.1.1(f) Ensuring that all major appurtenances and attachments, connecting structures, and those elements of the upper coupler (fifth wheel) assembly that can be inspected without dismantling that assembly are not damaged or corroded so as to affect safe operation of the vehicle.	Reach Assembly	☒	☐	☐	☐
	Turn Table & Ring	☒	☐	☐	☐
	Dolley Frame	☒	☐	☐	☐
	Upper Fifth Wheel Plate	☐	☐	☐	☒
	Fifth Wheel Plate	☐	☐	☐	☒
	Sub Frame	☐	☐	☐	☒
	Truck Apron & Pintle	☒	☐	☐	☐
	Cabinets & Fenders	☐	☐	☐	☒
	PTO Shaft Assy	☒	☐	☐	☐
7.2.1.2 For multi-compartment vehicles, the drain shall be uncapped or unplugged. If there is no evidence of leakage from the drain or void space, the external inspection for the tank wall in that void space shall be deemed to be satisfied.	Unplugged/Uncapped	☒	☐	☐	☐
	Coagulation	☒	☐	☐	☐
	Damage	☒	☐	☐	☐
7.2.1.4 (a) All reclosing pressure-relief devices shall be externally inspected for any corrosion or damage that could prevent their safe operation.	Hinge & Dome Assy.	☐	☐	☐	☒
	PPV Inspection	☐	☐	☐	☒
	Vacuum Vent Insp.	☒	☐	☐	☐
7.2.1.1(g) Ensuring that hose assemblies mounted on or accompanying the tank do not display any defects listed in clause 7.2.10.4 and have legible markings meeting the requirements of clause 7.2.10.6 and where applicable,	Condition	☐	☐	☐	☒
	Couplings	☐	☐	☐	☒
	Markings	☐	☐	☐	☒
	Inspection Current	☐	☐	☐	☒
B621-20 7.1 (h) Brake Interlock 7.1 (h) Wheel Chocks 7.1 (i) Fire Extinguishers 7.1 (j) Automatic Engine Air Intake Shut-off Device	Present & Operational	☒	☐	☐	☐
	Present	☐	☒	☐	☐
	Compliant	☐	☐	☐	☒
	Present	☒	☐	☐	☐
Clause	List Defects: Location, Nature, Severity and Describe Repair		No Defects Found ☐		
B621-20	Location:				Initial
	Reason:	No wheel chocks			Repaired
	Repair:				
	Location:				Initial
	Reason:				Repaired
	Repair:				
	Location:				Initial
	Reason:				Repaired
	Repair:				
	Location:				Initial
	Reason:				Repaired
	Repair:				

Clause	List Defects: Location, Nature, Severity and Describe Repair		
	Location:		Initial Repaired
	Reason:		
	Repair:		
	Location:		Initial Repaired
	Reason:		
	Repair:		
	Location:		Initial Repaired
	Reason:		
	Repair:		
	Location:		Initial Repaired
	Reason:		
	Repair:		
	Location:		Initial Repaired
	Reason:		
	Repair:		
	Location:		Initial Repaired
	Reason:		
	Repair:		
	Location:		Initial Repaired
	Reason:		
	Repair:		
	Location:		Initial Repaired
	Reason:		
	Repair:		
Tank Disposition	Compliant and Returned to Service ☒	Non-compliant, Repairs to Complete ☐	Non-compliant, Removed from Service ☐
Name of Inspector:	Todd Arden	Inspector Signature:	
This External Visual Inspection meets the requirements of the CSA B620-20 and CSA B621-20			

 1840 Kryczka Pl. Kamloops, BC V1S 1S4	TC Reg. No. 25-0704	Leakage Test	
	Work Order No.	R001012	
	Client Name	G & B Fuels Incorporated.	
	Client Ph. Number	403-273-5111	
	Date	02-18-2025	

Address:	59 Technology Way SE	Unit Number:	241A
	Calgary, AB	License Plate Number:	5KD5 39
	T3S 0B9	Tank Manufacturer:	Advance
Tank VIN Num.:	2AEABSAH1AR000116	Tank Assembler:	Advance
Truck VIN Num.:	N/A	Tank Specification:	TC 406
TCRN:	N/A	MDIN:	8053

	Top	Sides	Bottom	
Min. Shell Thickness:	4.39	4.39	5.97	Tank Lined: No
Min. Head Thickness:	5.97			Tank Insulated: No
				Special Service (Corrosive Etc.): No

MAWP:	22.7	kPa	Month	Year	Configuration
Test Pressure:	34.5	kPa	Cert Date:	11	9
Design Pressure	N/A	PSI	Mfg Date:	11	9
					B Train Lead

Comp 1	Comp 2	Comp 3	Comp 4	Comp 5	Comp 6	Total
18500	5000	12000	N/A	N/A	N/A	35500

Volumetric Capacity In Litres

Items Inspected	N/A	Repairs Required	Corrected	Complies
7.2.5.1 (a) Any venting devices set to relieve at less than the test pressure shall be removed or rendered inoperative.	PPVs removed	☐	☐	☒
7.2.5.1 (b) Product piping and all associated valves and accessories shall be in place and operative.	Compliant	☐	☐	☒
7.2.5.1 (c) Each valve and closure shall be tested in sequence. (e) One of the following shall be used as the test medium: (i) the normal lading of the tank; (iii) water; (v) air; or (vi) vacuum. (f) When air is used as the test medium, (i) a soapy water mixture shall be used to locate leaks (h) The pressure shall be not less than 80% of the tank design pressure or MAWP, whichever is less (i) The test pressure shall be maintained for at least 5 min.				
Test Medium :	Air/Soap	Test Pressure:	3.3 psi	Test Hold Time 5 Minutes: ☒
Test Results:	Comp. 1	Comp. 2	Comp. 3	Comp. 4
Compartment	☒	☒	☒	☐
Piping/Manifold	☒	☒	☒	☐
7.2.5.1 The leakage test shall ensure that the tank closures, piping, valves and gaskets are in good condition and do not leak within the piping or to the exterior.	Compliant	N/A	Repairs Required	Corrected
		☐	☐	☒

Clause	List Defects: Location, Nature, Severity and Describe Repair		No Defects Found ☒
	Location:		Initial Repaired
	Reason:		
	Repair:		
	Location:		Initial Repaired
	Reason:		
	Repair:		
	Location:		Initial Repaired
	Reason:		
	Repair:		
	Location:		Initial Repaired
	Reason:		
	Repair:		
	Location:		Initial Repaired
	Reason:		
	Repair:		
	Location:		Initial Repaired
	Reason:		
	Repair:		
Tank Disposition	Compliant and Returned to Service ☒		Non-compliant, Repairs to Complete ☐
			Non-compliant, Removed from Service ☐
Name of Tester:	Kyle Thomas	Tester Signature:	

This Leakage Test meets the requirements of the CSA B620-20



1840 Kryczka Place, Kamloops, B.C., Canada, V1S 1S4
Telephone (250) 372-2725 Telefax (250) 372-8127

Customer: G & B Fuels Inc.	Unit: 241A	Date: Feb 18/25
----------------------------	------------	-----------------

**METHOD 27 – Determination of vapor tightness of Gasoline delivery tank using pressure vacuum test
CAN/CGSB-3.1000-2019-7.2 Vapour control systems in gasoline distribution networks**

1. Ground tank.
2. Pail check to ensure tank is empty.

Pressure Decay Test

The purpose of this test is to verify that both the compartments and VR system have minimal leaks to atmosphere.

1. Open all emergency valve switches to allow air to equalize between compartments.
2. Connect test cap & Manometer to vapor return valve.
3. Visually inspect manhole lids and pressure devices for deficiencies.
4. Perform a sensor "wet test" on each compartment.
5. Through test cap pressurize compartments to a minimum of 18" H₂O.
6. Let air pressure stabilize in compartments, close test cap isolation valve, record measurement & begin the pressure test. Record the pressure decay after 5-minutes duration.
7. Perform a second pressure decay test recording both initial & final pressures.
8. Continue performing these tests until two consecutive final pressure tests are within 0.5" H₂O.
9. Take an average of the two tests & refer to chart to determine if allowable decay has been met.
10. If the pressure decay test passes continue to the internal vapor test.
11. If pressure decay is more than the allowable limits, make necessary repairs and perform two more consecutive pressure decay tests. Continue this process until unit passes.

Capacity in Litres	Capacity in U.S. Gal.	Initial Pressure (H ₂ O)	Final Pressure (H ₂ O)	Pressure Decay (H ₂ O)	Pass/Fail
35500		18	17.75	.25	Pass
		18	17.75	.25	Pass

Capacity in Litres	Capacity (Gal.)	Max. Decay (H ₂ O)
>9459	>2499	1.0"
5676 to 9458	1500 to 2499	1.5"
3785 to 5675	1499 to 1000	2.0"

Internal Vapor Valve Test

The purpose of this test is to verify that the vapour vents have minimal leaks under pressure.

1. With compartments charged to a minimum of 18" H₂O, close emergency valve switches.
2. Bleed air from vapor return valve to return to atmospheric pressure using test cap isolation valve.



1840 Kryczka Place, Kamloops, B.C., Canada, V1S 1S4
Telephone (250) 372-2725 Telefax (250) 372-8127

3. With testing apparatus still connected to vapor return valve, close testing apparatus isolation valve to isolate vapor recovery system from tank compartments. After a 5-minute duration record pressure build up.
4. Passing criterial will be maximum 5" H2O.
5. If the internal vapor valve test passes continue to the vacuum test.
6. If the Internal vapor valve test pressure is more than the allowable limit, make necessary repairs and perform the test again. Continue this process until unit passes.

Initial Vapor Recovery System Pressure (H2O)	Final Vapor Recovery System Pressure (H2O)	Pressure Decay (H2O)	Pass/Fail
0" H2O	0	0	Pass

Vacuum Test

The purpose of this test is to verify that the vapour vents have minimal leaks under vacuum..

1. Open vapor return valve to atmosphere using the test cap isolation valve.
2. Open all emergency valve switches to allow air in compartments to bleed off through vapor recovery to atmospheric pressure.
3. Connect vacuum pump to test cap apparatus.
4. Initialize pump and pull a vacuum of 6" H2O.
5. Let vacuum stabilize in compartments, close isolation valve on test cap, record measurement & begin the vacuum test. Record the pressure increase in the vapor recovery system if any after a 5-minute duration.
6. Perform a second vacuum test recording both initial & final pressures.
7. Continue performing these tests until two consecutive final vacuum tests are within 0.5" H2O.
8. Take an average of the two tests & refer to the chart on page 1 to determine if allowable vacuum decay has been met.
9. If vacuum test is more than the allowable limits, make necessary repairs and perform two more consecutive vacuum tests. Continue this process until unit passes.

Capacity in Litres	Capacity in U.S. Gal.	Initial Vacuum (H2O)	Final Vacuum (H2O)	Vacuum Decay (H2O)	Pass/Fail
35500		6	5.75	.25	Pass
		6	5.75	.25	Pass

Repairs required To Pass Inspection:

This unit has passed all the requirements as outlined under EPA Method 27

Inspector: Kyle Thomas	Signature: 	Date: Feb 18/25
------------------------	--	-----------------

 1840 Kryczka Pl. Kamloops, BC V1S 1S4	TC Reg. No. 25-0704	Hose Assembly Inspection and Testing	
	Work Order No.	R001012	
	Client Name	G & B Fuels Incorporated.	
	Client Ph. Number	403-273-5111	
	Date	02-18-2025	

Address:	59 Technology Way SE Calgary, AB T3S 0B9	Unit Number:	241A
Tank VIN Num.:	2AEABSAH1AR000116	License Plate Number:	5KD5 39
Truck VIN Num.:	N/A	Tank Manufacturer:	Advance
TCRN:	N/A	Tank Assembler:	Advance
		Tank Specification:	TC 406
		MDIN:	8053

	Top	Sides	Bottom		
Min. Shell Thickness:	4.39	4.39	5.97	Tank Lined:	No
Min. Head Thickness:	5.97			Tank Insulated:	No
				Special Service (Corrosive Etc.):	No

MAWP:	22.7	kPa	Month	Year	Configuration
Test Pressure:	34.5	kPa	Cert Date:	11	9
Design Pressure	N/A	PSI	Mfg Date:	11	9
					B Train Lead

Comp 1	Comp 2	Comp 3	Comp 4	Comp 5	Comp 6	Total
18500	5000	12000	N/A	N/A	N/A	35500

Volumetric Capacity In Litres

Items Inspected	N/A	Repairs Required	Corrected	Complies
7.2.10.4 Hose assemblies shall be inspected annually for				
(a) damage to the hose cover that exposes the reinforcement;	☐	☐	☐	☒
(b) kinked, flattened or permanently deformed wire braid;	☐	☐	☐	☒
(c) soft spots when not under pressure, bulging under pressure or loose outer covering;	☐	☐	☐	☒
(d) damaged, slipping or excessively worn hose couplings;	☐	☐	☐	☒
(e) loose or missing bolts or fastenings on bolted hose coupling assy's	☒	☐	☐	☐
(f) deteriorated legibility or absence of the serial or identification number and HAWP	☐	☐	☐	☒
7.2.10.5 (a) A hose assembly having any damage identified 7.2.10.4 shall be taken out of service and not pressure tested until repaired				
7.2.10.5 (b) The test pressure shall be (i) for CSA-certified hose assemblies, not less than 350 psi (ii) for gravity off-load hose assemblies (drop hoses), not less than 10 psi (iii) for vapour recovery hose assemblies, not less than 10 psi (vi) for all other hose assemblies, the greater of 120% of the marked HAWP of the hose assembly and 75 psi				

Hose Serial Number	Hose Model Number	HAWP	Test Pressure	Test Medium
241A-1	NL3010-300	115	140	Water
241A-2	NL3327-300	115	140	Water
241A-3	NL3325-300	100	120	Water

Items Inspected	N/A	Repairs Required	Corrected	Complies
7.2.10.5 (f) to pass the pressure test, the hose assembly shall hold the pressure without bulging, distortion or leaks for at least 5 min when isolated from the pressure supply.	☐	☐	☐	☒

Attention!			<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="text-align: left;">Hose Serial Number</th> <th style="text-align: left;">Continuity (ohms)</th> </tr> <tr><td style="text-align: center;">241A-1</td><td style="text-align: center;"><</td></tr> <tr><td style="text-align: center;">241A-2</td><td style="text-align: center;"><</td></tr> <tr><td style="text-align: center;">241A-3</td><td style="text-align: center;"><</td></tr> <tr><td style="text-align: center;">0</td><td></td></tr> <tr><td style="text-align: center;">0</td><td></td></tr> <tr><td style="text-align: center;">0</td><td></td></tr> <tr><td style="text-align: center;">0</td><td></td></tr> <tr><td style="text-align: center;">0</td><td></td></tr> </table>	Hose Serial Number	Continuity (ohms)	241A-1	<	241A-2	<	241A-3	<	0		0		0		0		0	
Hose Serial Number	Continuity (ohms)																				
241A-1	<																				
241A-2	<																				
241A-3	<																				
0																					
0																					
0																					
0																					
0																					
All hose assemblies have been tested for electrical continuity. As there is no failing criteria at this time, it is NOT recommended to use a hose assembly for gasoline transfer, dispensing, or fueling applications when reading is greater than 100 ohms.																					
Clause	List Defects: Location, Nature, Severity and Describe Repair	No Defects Found ☒																			
Hose Disposition	Compliant and Returned to Service ☒	Non-compliant, Repairs to Complete ☐	Non-compliant, Removed from Service ☐																		
Name of Tester:	Kyle Thomas	Tester Signature:																			
This hose test and inspection meets the requirements of the CSA B620-20																					

 1840 Kryczka Pl. Kamloops, BC V1S 1S4	TC Reg. No. 25-0704	Internal Visual Inspection Report	
	Work Order No.	R000326	
	Client Name	G & B Fuels Incorporated.	
	Client Ph. Number	403-273-5111	
	Date	02-12-2024	

Address:	59 Technology Way SE	Unit Number:	241A
	Calgary, AB	License Plate Number:	5KD5 39
	T3S 0B9	Tank Manufacturer:	Advance
Tank VIN Num.:	2AEABSAH1AR000116	Tank Assembler:	Advance
Truck VIN Num.:	N/A	Tank Specification:	TC 406
TCRN:	N/A	MDIN:	8053

	Top	Sides	Bottom	
Min. Shell Thickness:	4.39	4.39	5.97	Tank Lined: No
Min. Head Thickness:	5.97			Tank Insulated: No
				Special Service (Corrosive Etc.): No

MAWP:	22.7	kPa	Month	Year	Configuration
Test Pressure:	34.5	kPa	Cert Date:	11	9
Design Pressure	N/A	PSI	Mfg Date:	11	9
					B Train Lead

Comp 1	Comp 2	Comp 3	Comp 4	Comp 5	Comp 6	Total
18500	5000	12000	N/A	N/A	N/A	35500

Volumetric Capacity In Litres

Items Inspected		N/A	Repairs Required	Corrected	Complies
7.2.2.1 Internal inspections shall include the following: (a) checking tank shell, heads and baffles for cracks, corroded areas, dents, distortion, defects in welds, defects in piping and any other condition, including leakage that might render the tank unsafe for transportation service.	Tank Shell	☐	☐	☐	☒
	Heads	☐	☐	☐	☒
	Baffles	☐	☒	☒	☒
	Internal Piping	☒	☐	☐	☐
	Sump	☐	☐	☐	☒
	Emergency Valve	☐	☐	☐	☒
(b) in accordance with clause 7.2.6, thickness testing of corroded areas of the tank wall	Compliant	☐	☐	☐	☒
Clause	List Defects: Location, Nature, Severity and Describe Repair	No Defects Found ☐			
7.2.2.1	Location: Inside comp 3.				Initial
	Reason: Single baffle comp 3 cracks PS & DS.				Repaired
	Repair: Gouge & weld cracks				DT

	Location:		Initial
	Reason:		Repaired
	Repair:		

Tank Disposition	Compliant and Returned to Service ☒	Non-compliant, Repairs to Complete ☐	Non-compliant, Removed from Service ☐
Name of Inspector:	Donald Abramson	Inspector Signature:	

This Internal Visual Inspection meets the requirements of the CSA B620-20

 1840 Kryczka Pl. Kamloops, BC V1S 1S4	TC Reg. No. 25-0704	Pneumatic Pressure Test	
	Work Order No.	R000326	
	Client Name	G & B Fuels Incorporated.	
	Client Ph. Number	403-273-5111	
	Date	02-12-2024	

Address:	59 Technology Way SE	Unit Number:	241A
	Calgary, AB	License Plate Number:	5KD5 39
	T3S 0B9	Tank Manufacturer:	Advance
Tank VIN Num.:	2AEABSAH1AR000116	Tank Assembler:	Advance
Truck VIN Num.:	N/A	Tank Specification:	TC 406
TCRN:	N/A	MDIN:	8053

	Top	Sides	Bottom	
Min. Shell Thickness:	4.39	4.39	5.97	Tank Lined: No
Min. Head Thickness:	5.97			Tank Insulated: No
				Special Service (Corrosive Etc.): No

MAWP:	22.7	kPa	Month	Year	Configuration
Test Pressure:	34.5	kPa	Cert Date:	11	9
Design Pressure	N/A	PSI	Mfg Date:	11	9
					B Train Lead

	Comp 1	Comp 2	Comp 3	Comp 4	Comp 5	Comp 6	Total
Volumetric Capacity In Litres	18500	5000	12000	N/A	N/A	N/A	35500

Items Inspected	N/A	Repairs Required	Corrected	Complies		
7.2.7.1 Prior to conducting a pressure test, the tank shall have a satisfactory external visual inspection and a current internal visual inspection	☐ External Visual Insp. ☐ Internal Visual Insp.	☐ ☐	☐ ☐	☒ ☒		
7.2.7.3 (a) Any venting devices set to relieve at less than the test pressure shall be removed or rendered inoperative.	PPVs removed	☐	☐	☒		
7.2.7.8 (a) The pneumatic test shall be used only where (i) there is no suspicion of weakness in the tank (g) Where the test duration is less than 1 hour (i) with the tank pressure at MAWP, the tank shall be inspected for leaks by coating the entire surface of all joints under pressure with a soapy solution of soap and water that will foam to indicate the presence of leaks (h) All piping and accessories shall be tested at not less than 80% of the tank's MAWP (results recorded on leakage test form) 7.2.7.4 A tank shall have successfully completed the test if (a) when isolated from the pressure supply the test pressure is retained for at least 10 min; and (b) a visual examination of all external surfaces reveals no defects, leakage or deformation.						
Test Medium :	Soap/Air	Test Pressure:	5 psi	Test Hold Time 10 Minutes: ☒		
Test Results:	Comp. 1	Comp. 2	Comp. 3	Comp. 4	Comp. 5	Comp. 6
Compartment	☒	☒	☒	☐	☐	☐
Piping/Manifold	☒	☒	☒	☐	☐	☐


7.2.7.6 Reclosing pressure-relief device testing.

(b) Tested to ensure that they open at the required set-to-discharge pressure for the tank's MAWP and reseal at not less than 90% of that pressure or at the tank specification.

Test Medium :	Soap/Air					
Test Results:	Comp. 1	Comp. 2	Comp. 3	Comp. 4	Comp. 5	Comp. 6
Opening Pressure:	3.6 PSI	3.6 PSI	3.6 PSI	PSI	PSI	PSI
Closing Pressure:	3.3 PSI	3.3 PSI	3.3 PSI	PSI	PSI	PSI
Compliant	☒	☒	☒	☐	☐	☐

PPV Pressure Test	A properly functioning 6496AL Normal Vent should open between 1.0 to 1.5 PSI, but not less than 1.0 PSI. A properly functioning 6238AL Normal Vent should open between .08 to 1.0 PSI, but not more than 1.0 PSI.					
Test Results:	Comp. 1	Comp. 2	Comp. 3	Comp. 4	Comp. 5	Comp. 6
Pass	☒	☒	☒	☐	☐	☐
Fail	☐	☐	☐	☐	☐	☐

PPV Vacuum Test	A properly functioning 6496AL Normal Vent should Vacuum between .25 to .375 PSI, but no more than 0.375PSI. A properly functioning 6238AL Normal Vent should Vacuum between .25 to .375 PSI, but no more than 0.375 PSI					
Test Results:	Comp. 1	Comp. 2	Comp. 3	Comp. 4	Comp. 5	Comp. 6
Pass	☒	☒	☒	☐	☐	☐
Fail	☐	☐	☐	☐	☐	☐

Clause	List Defects: Location, Nature, Severity and Describe Repair	No Defects Found ☒
	Location: _____	Initial
	Reason: _____	Repaired
	Repair: _____	
	Location: _____	Initial
	Reason: _____	Repaired
	Repair: _____	
	Location: _____	Initial
	Reason: _____	Repaired
	Repair: _____	
	Location: _____	Initial
	Reason: _____	Repaired
	Repair: _____	
Tank Disposition	Compliant and Returned to Service ☒	Non-compliant, Repairs to Complete ☐
		Non-compliant, Removed from Service ☐
Name of Tester:	Shannon Niemi	Tester Signature: 

This Pneumatic Test meets the requirements of the CSA B620-20

 1840 Kryczka Pl. Kamloops, BC V1S 1S4	TC Reg. No. 25-0704	Upper Coupler Area Inspection	
	Work Order No.	R000326	
	Client Name	G & B Fuels Incorporated.	
	Client Ph. Number	403-273-5111	
	Date	02-12-2024	


Address:	59 Technology Way SE	Unit Number:	241A
	Calgary, AB	License Plate Number:	5KD5 39
	T3S 0B9	Tank Manufacturer:	Advance
Tank VIN Num.:	2AEABSAH1AR000116	Tank Assembler:	Advance
Truck VIN Num.:	N/A	Tank Specification:	TC 406
TCRN:	N/A	MDIN:	8053

	Top	Sides	Bottom		
Min. Shell Thickness:	4.39	4.39	5.97	Tank Lined:	No
Min. Head Thickness:	5.97			Tank Insulated:	No
				Special Service (Corrosive Etc.)	No

MAWP:	22.7	kPa	Month	Year	Configuration
Test Pressure:	34.5	kPa	Cert Date:	11	9
Design Pressure	N/A	PSI	Mfg Date:	11	9
					B Train Lead

Comp 1	Comp 2	Comp 3	Comp 4	Comp 5	Comp 6	Total
18500	5000	12000	N/A	N/A	N/A	35500

Volumetric Capacity In Litres

Items Inspected		N/A	Repairs Required	Corrected	Complies
7.2.4 Areas covered by the upper coupler (i.e. king pin plate) or turntable assembly shall be inspected for corroded or abraded areas, cracks, dents, distortions, defects in welds and any other condition that might render the tank unsafe for use in transportation.	Barrel	☐	☐	☐	☒
	Tank Attachments	☐	☐	☐	☒
	King Pin Plate Assy.	☐	☐	☐	☒
	Turn Table	☒	☐	☐	☐
	Turn Table Ring	☒	☐	☐	☐
Clause	List Defects: Location, Nature, Severity and Describe Repair	No Defects Found			☒
	Location:	Initial			
	Reason:	Repaired			
	Repair:				
	Location:	Initial			
	Reason:	Repaired			
	Repair:				
	Location:	Initial			
	Reason:	Repaired			
	Repair:				
Tank Disposition	Compliant and Returned to Service ☒	Non-compliant, Repairs to Complete ☐	Non-compliant, Removed from Service ☐		
Name of Inspector:	Donald Abramson		Inspector Signature:		

This Upper Coupler Area Inspection meets the requirements of the CSA B620-20

X34-2

 1840 Kryczka Pl. Kamloops, BC V1S 1S4	TC Reg. No. 25-0704	External Visual Inspection Report	
	Work Order No.	R001012	
	Client Name	G & B Fuels Incorporated.	
	Client Ph. Number	403-273-5111	
	Date	02-18-2025	

Address:	59 Technology Way SE	Unit Number:	241B
	Calgary, AB	License Plate Number:	5KD5 40
	T3S 0B9	Tank Manufacturer:	Advance
Tank VIN Num.:	2AEARPAE5AR000117	Tank Assembler:	Advance
Truck VIN Num.:	N/A	Tank Specification:	TC 406
TCRN:	N/A	MDIN:	8054

	Top	Sides	Bottom		
Min. Shell Thickness:	4.39	4.39	5.97	Tank Lined:	No
Min. Head Thickness:	5.97			Tank Insulated:	No
				Special Service (Corrosive Etc.)	No

MAWP:	22.7	kPa	Month	Year	Configuration
Test Pressure:	34.5	kPa	Cert Date:	11	9
Design Pressure	N/A	PSI	Mfg Date:	11	9
					B Train Pup

Comp 1	Comp 2	Comp 3	Comp 4	Comp 5	Comp 6	Total
6500	5000	18500	N/A	N/A	N/A	30000

Volumetric Capacity In Litres

Items Inspected	N/A	Repairs Required	Corrected	Complies
7.2.1.1(e) Ensuring that specification and other markings on the tank are legible; if metal identification plates are missing or illegible, the requirements of Clause 7.7 shall apply.	Tank Attachment	☐	☐	☒
	Legible	☐	☐	☒
	Data Complete	☐	☐	☒
	Manhole Lid Markings	☐	☐	☒
	Emergency Shutoff	☐	☐	☒
7.2.1.1(a) Without removing insulation or jacketing, checking for corroded areas, dents, distortions, defects in welds, defects in piping, and any other condition, including leakage, that indicates weakness in the tank that might render it unsafe for transportation.	Barrel	☐	☐	☒
	Attachments	☐	☐	☒
	Piping	☐	☐	☒
	Flexible Couplings	☐	☐	☒
	Pump Bearings	☒	☐	☐
7.2.1.1(b) Ensuring that devices for tightening manhole covers are operative and that the covers are leaktight.	Clamping Ring	☐	☐	☒
	Attachments	☐	☐	☒
	Coagulation	☐	☐	☒
7.2.1.1(c) Ensuring proper functioning of all valves, vents, emergency devices, excess-flow valves, remote closure devices, ensuring that they are free of corrosion, distortion, or any other damage that would prevent their normal operation.	Vapour Vent Operation	☐	☐	☒
	Emergency Valve	☐	☐	☒
	Piping Valves	☐	☐	☒
	Remote Closure Device	☐	☐	☒
	Manifold Valves	☒	☐	☐
7.2.1.1(d) Ensuring that all bolts or nuts on any flanged connection or blank flange are in place and properly tightened.	Manifold Flanges	☒	☐	☐
	Pump & Meter Flanges	☒	☐	☐
	Piping Flanges	☐	☐	☒

Items Inspected		N/A	Repairs Required	Corrected	Complies
7.2.1.1(f) Ensuring that all major appurtenances and attachments, connecting structures, and those elements of the upper coupler (fifth wheel) assembly that can be inspected without dismantling that assembly are not damaged or corroded so as to affect safe operation of the vehicle.	Reach Assembly	☒	☐	☐	☐
	Turn Table & Ring	☒	☐	☐	☐
	Dolley Frame	☒	☐	☐	☐
	Upper Fifth Wheel Plate	☐	☐	☐	☒
	Fifth Wheel Plate	☒	☐	☐	☐
	Sub Frame	☐	☐	☐	☒
	Truck Apron & Pintle	☒	☐	☐	☐
	Cabinets & Fenders	☐	☒	☒	☒
	PTO Shaft Assy	☒	☐	☐	☐
7.2.1.2 For multi-compartment vehicles, the drain shall be uncapped or unplugged. If there is no evidence of leakage from the drain or void space, the external inspection for the tank wall in that void space shall be deemed to be satisfied.	Unplugged/Uncapped	☒	☐	☐	☐
	Coagulation	☒	☐	☐	☐
	Damage	☒	☐	☐	☐
7.2.1.4 (a) All reclosing pressure-relief devices shall be externally inspected for any corrosion or damage that could prevent their safe operation.	Hinge & Dome Assy.	☐	☐	☐	☒
	PPV Inspection	☐	☐	☐	☒
	Vacuum Vent Insp.	☒	☐	☐	☐
7.2.1.1(g) Ensuring that hose assemblies mounted on or accompanying the tank do not display any defects listed in clause 7.2.10.4 and have legible markings meeting the requirements of clause 7.2.10.6 and where applicable,	Condition	☐	☐	☐	☒
	Couplings	☐	☐	☐	☒
	Markings	☐	☐	☐	☒
	Inspection Current	☐	☐	☐	☒
B621-20 7.1 (h) Brake Interlock 7.1 (h) Wheel Chocks 7.1 (i) Fire Extinguishers 7.1 (j) Automatic Engine Air Intake Shut-off Device	Present & Operational	☒	☐	☐	☐
	Present	☐	☒	☐	☐
	Compliant	☐	☐	☐	☒
	Present	☒	☐	☐	☐
Clause	List Defects: Location, Nature, Severity and Describe Repair		No Defects Found		☐
7.2.1.1(f.)	Location:	PS landing gear support bracket			Initial
	Reason:	Weld cracked			Repaired
	Repair:	Grind & reweld			DB
B621-20	Location:				Initial
	Reason:	No wheel chocks			Repaired
	Repair:				
	Location:				Initial
	Reason:				Repaired
	Repair:				
	Location:				Initial
	Reason:				Repaired
	Repair:				
	Location:				Initial
	Reason:				Repaired
	Repair:				

Clause	List Defects: Location, Nature, Severity and Describe Repair		
	Location:		Initial
	Reason:		Repaired
	Repair:		
	Location:		Initial
	Reason:		Repaired
	Repair:		
	Location:		Initial
	Reason:		Repaired
	Repair:		
	Location:		Initial
	Reason:		Repaired
	Repair:		
	Location:		Initial
	Reason:		Repaired
	Repair:		
	Location:		Initial
	Reason:		Repaired
	Repair:		
	Location:		Initial
	Reason:		Repaired
	Repair:		
Tank Disposition	Compliant and Returned to Service ☒	Non-compliant, Repairs to Complete ☐	Non-compliant, Removed from Service ☐
Name of Inspector:	Todd Arden	Inspector Signature:	
This External Visual Inspection meets the requirements of the CSA B620-20 and CSA B621-20			

 1840 Kryczka Pl. Kamloops, BC V1S 1S4	TC Reg. No. 25-0704	Leakage Test	
	Work Order No.	R001012	
	Client Name	G & B Fuels Incorporated.	
	Client Ph. Number	403-273-5111	
	Date	02-18-2025	

Address:	59 Technology Way SE	Unit Number:	241B
	Calgary, AB	License Plate Number:	5KD5 40
	T3S 0B9	Tank Manufacturer:	Advance
Tank VIN Num.:	2AEARPAE5AR000117	Tank Assembler:	Advance
Truck VIN Num.:	N/A	Tank Specification:	TC 406
TCRN:	N/A	MDIN:	8054

	Top	Sides	Bottom		
Min. Shell Thickness:	4.39	4.39	5.97	Tank Lined:	No
Min. Head Thickness:	5.97			Tank Insulated:	No
				Special Service (Corrosive Etc.):	No

MAWP:	22.7	kPa		Month	Year	Configuration
Test Pressure:	34.5	kPa	Cert Date:	11	9	B Train Pup
Design Pressure	N/A	PSI	Mfg Date:	11	9	

Comp 1	Comp 2	Comp 3	Comp 4	Comp 5	Comp 6	Total
6500	5000	18500	N/A	N/A	N/A	30000

Volumetric Capacity In Litres

Items Inspected		N/A	Repairs Required	Corrected	Complies
7.2.5.1 (a) Any venting devices set to relieve at less than the test pressure shall be removed or rendered inoperative.	PPVs removed	☐	☐	☐	☒
7.2.5.1 (b) Product piping and all associated valves and accessories shall be in place and operative.	Compliant	☐	☐	☐	☒
7.2.5.1 (c) Each valve and closure shall be tested in sequence. (e) One of the following shall be used as the test medium: (i) the normal lading of the tank; (iii) water; (v) air; or (vi) vacuum. (f) When air is used as the test medium, (i) a soapy water mixture shall be used to locate leaks (h) The pressure shall be not less than 80% of the tank design pressure or MAWP, whichever is less (i) The test pressure shall be maintained for at least 5 min.					
Test Medium :	Air/Soap	Test Pressure:	3.3 psi	Test Hold Time 5 Minutes:	☒
Test Results:	Comp. 1	Comp. 2	Comp. 3	Comp. 4	Comp. 5
Compartment	☒	☒	☒	☐	☐
Piping/Manifold	☒	☒	☒	☐	☐
7.2.5.1 The leakage test shall ensure that the tank closures, piping, valves and gaskets are in good condition and do not leak within the piping or to the exterior.	Compliant	N/A	Repairs Required	Corrected	Complies
		☐	☐	☐	☒

Clause	List Defects: Location, Nature, Severity and Describe Repair		No Defects Found ☒
	Location:		Initial Repaired
	Reason:		
	Repair:		
	Location:		Initial Repaired
	Reason:		
	Repair:		
	Location:		Initial Repaired
	Reason:		
	Repair:		
	Location:		Initial Repaired
	Reason:		
	Repair:		
	Location:		Initial Repaired
	Reason:		
	Repair:		
	Location:		Initial Repaired
	Reason:		
	Repair:		
Tank Disposition	Compliant and Returned to Service ☒	Non-compliant, Repairs to Complete ☐	Non-compliant, Removed from Service ☐
Name of Tester:	Kyle Thomas	Tester Signature:	
This Leakage Test meets the requirements of the CSA B620-20			



1840 Kryczka Place, Kamloops, B.C., Canada, V1S 1S4
Telephone (250) 372-2725 Telefax (250) 372-8127

Customer: G & B Fuels Inc.

Unit: 241B

Date: Feb 18/25

**METHOD 27 – Determination of vapor tightness of Gasoline delivery tank using pressure vacuum test
CAN/CGSB-3.1000-2019-7.2 Vapour control systems in gasoline distribution networks**

1. Ground tank.
2. Pail check to ensure tank is empty.

Pressure Decay Test

The purpose of this test is to verify that both the compartments and VR system have minimal leaks to atmosphere.

1. Open all emergency valve switches to allow air to equalize between compartments.
2. Connect test cap & Manometer to vapor return valve.
3. Visually inspect manhole lids and pressure devices for deficiencies.
4. Perform a sensor "wet test" on each compartment.
5. Through test cap pressurize compartments to a minimum of 18" H₂O.
6. Let air pressure stabilize in compartments, close test cap isolation valve, record measurement & begin the pressure test. Record the pressure decay after 5-minutes duration.
7. Perform a second pressure decay test recording both initial & final pressures.
8. Continue performing these tests until two consecutive final pressure tests are within 0.5" H₂O.
9. Take an average of the two tests & refer to chart to determine if allowable decay has been met.
10. If the pressure decay test passes continue to the internal vapor test.
11. If pressure decay is more than the allowable limits, make necessary repairs and perform two more consecutive pressure decay tests. Continue this process until unit passes.

Capacity in Litres	Capacity in U.S. Gal.	Initial Pressure (H ₂ O)	Final Pressure (H ₂ O)	Pressure Decay (H ₂ O)	Pass/Fail
30000		18	17.75	.25	Pass
		18	17.75	.25	Pass

Capacity in Litres	Capacity (Gal.)	Max. Decay (H ₂ O)
>9459	>2499	1.0"
5676 to 9458	1500 to 2499	1.5"
3785 to 5675	1499 to 1000	2.0"

Internal Vapor Valve Test

The purpose of this test is to verify that the vapour vents have minimal leaks under pressure.

1. With compartments charged to a minimum of 18" H₂O, close emergency valve switches.
2. Bleed air from vapor return valve to return to atmospheric pressure using test cap isolation valve.



1840 Kryczka Place, Kamloops, B.C., Canada, V1S 1S4
Telephone (250) 372-2725 Telefax (250) 372-8127

3. With testing apparatus still connected to vapor return valve, close testing apparatus isolation valve to isolate vapor recovery system from tank compartments. After a 5-minute duration record pressure build up.
4. Passing criterial will be maximum 5" H2O.
5. If the internal vapor valve test passes continue to the vacuum test.
6. If the Internal vapor valve test pressure is more than the allowable limit, make necessary repairs and perform the test again. Continue this process until unit passes.

Initial Vapor Recovery System Pressure (H2O)	Final Vapor Recovery System Pressure (H2O)	Pressure Decay (H2O)	Pass/Fail
0" H2O	0	0	Pass


Vacuum Test

The purpose of this test is to verify that the vapour vents have minimal leaks under vacuum..

1. Open vapor return valve to atmosphere using the test cap isolation valve.
2. Open all emergency valve switches to allow air in compartments to bleed off through vapor recovery to atmospheric pressure.
3. Connect vacuum pump to test cap apparatus.
4. Initialize pump and pull a vacuum of 6" H2O.
5. Let vacuum stabilize in compartments, close isolation valve on test cap, record measurement & begin the vacuum test. Record the pressure increase in the vapor recovery system if any after a 5-minute duration.
6. Perform a second vacuum test recording both initial & final pressures.
7. Continue performing these tests until two consecutive final vacuum tests are within 0.5" H2O.
8. Take an average of the two tests & refer to the chart on page 1 to determine if allowable vacuum decay has been met.
9. If vacuum test is more than the allowable limits, make necessary repairs and perform two more consecutive vacuum tests. Continue this process until unit passes.

Capacity in Litres	Capacity in U.S. Gal.	Initial Vacuum (H2O)	Final Vacuum (H2O)	Vacuum Decay (H2O)	Pass/Fail
30000		6	5.75	.25	Pass
		6	5.75	.25	Pass

Repairs required To Pass Inspection:

This unit has passed all the requirements as outlined under EPA Method 27		
Inspector: Kyle Thomas	Signature: 	Date: Feb 18/25

 1840 Kryczka Pl. Kamloops, BC V1S 1S4	TC Reg. No. 25-0704	Hose Assembly Inspection and Testing	
	Work Order No.	R001012	
	Client Name	G & B Fuels Incorporated.	
	Client Ph. Number	403-273-5111	
	Date	02-18-2025	

Address:	59 Technology Way SE	Unit Number:	241B
	Calgary, AB	License Plate Number:	5KD5 40
	T3S 0B9	Tank Manufacturer:	Advance
Tank VIN Num.:	2AEARPAE5AR000117	Tank Assembler:	Advance
Truck VIN Num.:	N/A	Tank Specification:	TC 406
TCRN:	N/A	MDIN:	8054

	Top	Sides	Bottom	
Min. Shell Thickness:	4.39	4.39	5.97	Tank Lined: No
Min. Head Thickness:	5.97			Tank Insulated: No
				Special Service (Corrosive Etc.): No

MAWP:	22.7	kPa	Month	Year	Configuration
Test Pressure:	34.5	kPa	Cert Date:	11	9
Design Pressure	N/A	PSI	Mfg Date:	11	9
					B Train Pup

Comp 1	Comp 2	Comp 3	Comp 4	Comp 5	Comp 6	Total
6500	5000	18500	N/A	N/A	N/A	30000

Volumetric Capacity In Litres

Items Inspected	N/A	Repairs Required	Corrected	Complies
7.2.10.4 Hose assemblies shall be inspected annually for				
(a) damage to the hose cover that exposes the reinforcement;	☐	☐	☐	☒
(b) kinked, flattened or permanently deformed wire braid;	☐	☐	☐	☒
(c) soft spots when not under pressure, bulging under pressure or loose outer covering;	☐	☐	☐	☒
(d) damaged, slipping or excessively worn hose couplings;	☐	☐	☐	☒
(e) loose or missing bolts or fastenings on bolted hose coupling assy's	☒	☐	☐	☐
(f) deteriorated legibility or absence of the serial or identification number and HAWP	☐	☐	☐	☒
7.2.10.5 (a) A hose assembly having any damage identified 7.2.10.4 shall be taken out of service and not pressure tested until repaired				
7.2.10.5 (b) The test pressure shall be				
(i) for CSA-certified hose assemblies, not less than 350 psi				
(ii) for gravity off-load hose assemblies (drop hoses), not less than 10 psi				
(iii) for vapour recovery hose assemblies, not less than 10 psi				
(vi) for all other hose assemblies, the greater of 120% of the marked HAWP of the hose assembly and 75 psi				

Hose Serial Number	Hose Model Number	HAWP	Test Pressure	Test Medium
241B-1	NL3325-300	100	120	Water
241B-2	ST120-LT3	65	80	Water

Items Inspected	N/A	Repairs Required	Corrected	Complies
7.2.10.5 (f) to pass the pressure test, the hose assembly shall hold the pressure without bulging, distortion or leaks for at least 5 min when isolated from the pressure supply.	☐	☐	☐	☒

Attention! All hose assemblies have been tested for electrical continuity. As there is no failing criteria at this time, it is NOT recommended to use a hose assembly for gasoline transfer, dispensing, or fueling applications when reading is greater than 100 ohms.	Hose Serial Number	Continuity (ohms)
	241B-1	<
	241B-2	<
	0	
	0	
	0	
	0	
	0	
	0	

Clause	List Defects: Location, Nature, Severity and Describe Repair	No Defects Found ☒

Hose Disposition	Compliant and Returned to Service ☒	Non-compliant, Repairs to Complete ☐	Non-compliant, Removed from Service ☐
Name of Tester:	Kyle Thomas	Tester Signature:	

This hose test and inspection meets the requirements of the CSA B620-20