



J & J TRAILERS MANUFACTURERS & SALES INC.

345 FINCHdene SQUARE, SCARBOROUGH, ONTARIO M1X 1B9
PHONE: (416) 298-4482, FAX: (416) 298-4480, E-MAIL: info@jjtrailer.com

1313 BOUNDARY Rd. OSHAWA, ONTARIO L1J 6Z7

JJ Proposal #: 9780

Date: 20-Oct-2026

JJ Work Order #: T51199

Customer P.O #:

Customer WO #:

Payment Method Certified Cheque

VIN:

Model No: DD3-JP2-B2
Model Year : 2027
Make: J & J Trailers
G.V.W.R. : 190,920 LB - 86,600 KG
G.A.W.R. : 25,000 LB - 11,340 KG
Estimated Shipping Weight: 50,000 LB - 22,680 KG
Pay Load Capacity: 140,920 LB - 63,920 KG
Shipping Dimensions 102" W x 91'6" L x 26" H
Deck Size: 102" W X 24'3" L
Deck Height Loaded : 26"

Lic. Plate #:
Customer Unit No:
RIN #:
Color: BLACK GLOSS URETHANE I
Tire Size : 275/70R22.5
Tire Load Range: LRJ - 18PLY
Wheel Size : 8.25" x 22.5"
Wheel Type : DualWheel
Number of Stationary Axles : 2+3+2
Number of Lift Steering Axles :
Deck Height Unload: 26"

Specifications:

Trailer Year 2027
Overall Length 91'
GVWR 85 Ton
Payload Capacity` 65 Ton

JEEP SPECS:

- Tandem Axle, with IMT Air Ride Suspension, and suspension dump valve
- Sliding fifth wheel assembly
- Air, Hydraulic & Electrical Connections at front and rear
- 2 King Pin positions (removable)
- Riding on 275/70R22.5
- Tandem Holland Mark V Jacks
- D-Rings at every corner
- Side air tank drain locations
- 100% Grote LED wiring system

RGN SPECS:

- 53' Long with 24'8" Deck x 122" wide with outriggers deployed
- Deck is Modular (shimmable and removable), which allows for a deck insert or deck replacement
- Maximum amount of D-rings and outriggers along sides (outrigger wood planks included)
- 9 Deck-mounted D-rings directly above crossmembers
- 4 container locks to lock a 20' Sea container
- Hardwood flooring
- 5 positions for deck height adjustment

- Tridem Axle, with Dexter Air Ride Suspension, and suspension dump + override valve
- Riding on 275/70R22.5
- Air, Hydraulic & Electrical Connections at front and rear
- 2 King Pin positions (removable)
- Hydraulic Flip Extension for Jeep/Tridem Tractor Use
- Vertical air-operated locking pin
- Spare tire bracket on Gooseneck to hold two full wheel assemblies
- 30,000Lbs Hydraulic Winch mounted on Rear of Gooseneck (Upgrade)
- Honda Engine Power Pack to operate all trailer hydraulics, comes with necessary filters, pumps, gauges, etc. (upgrade)
- Selector Valve to choose between Power pack and Tractor PTO
- D-Rings at every corner for gooseneck and deck
- Boom Well between tires at rear
- Heavy duty deck for loading at rear above wheels
- Heavy duty steel flip ramps at front with traction grip
- 2 aluminum storage toolboxes mounted on gooseneck sides
- 2 storage locations on deck floor (centered at front)
- Rear Strobe lights with switch and additional portable Magnetic strobe lights with plug connection
- Flip out and slide out marker lights for wide loads
- Traction grip and handle bars for climbing gooseneck
- Flag holders and "D" Sign holders
- All pins machined with grooves and grease fittings
- Side air tank drain locations
- 100% Grote LED wiring system
- Hub-meter installed

BOOSTER SPECS:

- Tandem Axle, with IMT Air Ride Suspension, and suspension dump valve
- Air & Electrical Connections at front
- Bars to restrict rotation when in reverse
- Riding on 275/70R22.5
- Multiple different-thickness shims for adjustment
- Single 12k Jack
- Rear Strobe lights with switch
- Flip out and slide out marker lights for wide loads
- Flag holders and "D" Sign holders
- D-Rings at every corner
- All pins machined with grooves and grease fittings
- Side air tank drain locations
- 100% Grote LED wiring system

Every component of this trailer is fully sandblasted before epoxy primer and polyurethane paint applied. Colour is Gloss Black.

WARRANTY:

1-Year pro-rated warranty on this trailer.