



## Annual Inspection Certificate & Safety Standards Certificate



VEHICLE INFORMATION			
Plate#:	Y2822N	Year:	2014
VIN:	2M5931618E1140585	Make:	MANAC
GVWR (kg):	54437	Model:	MANAC TRAILER
Odometer ():		Type:	Trailer

CERTIFICATE INFORMATION	
Annual Inspection Certificate	Expires at the end of: May 2027
Safety Standards Certificate	Expires at the end of: June 11, 2026
Vehicle Inspection Certificate Number	LS20AD42
Inspection Start Date	May 6, 2026 System Time: 11 : 15
Inspection End Date	May 6, 2026 System Time: 12 : 03

VEHICLE INSPECTION CENTRE	
Vehicle Inspection Centre #: 13563	Technician: PAUL DUBAY
	
	Technician Signature
	Technician ID: 317301
	STO ID/Account: 13800214
	Trade Code: 310T, 310S

I certify that I inspected this vehicle on the inspection date in accordance with the inspection procedures established by directive under s. 100.7 of the Highway Traffic Act and that the vehicle meets the required equipment and performance standards as detailed in the Vehicle Inspection Report with the above referenced Vehicle Inspection Certificate Number.

This Certificate is not a warranty on the condition of the vehicle.

Vehicle Inspection Certificate Number: LS20AD42

Start Date / Time: May 6, 2026, 11:15 AM

End Date / Time: May 6, 2026, 12:03 PM

VEHICLE/ENGINE INFORMATION	CHASSIS
Plate#: Y2822N	Year: 2014
VIN: 2M5931618E1140585	Make: MANAC
GVWR(kg): 54437	Model: MANAC TRAILER
Odometer:	Fleet ID: 20

SAFETY INSPECTION RESULT	<b>PASS</b>
--------------------------	-------------

**SAFETY SYSTEM INSPECTION RESULTS**

All Safety System Components Passed Inspection
--

**MANDATORY ITEMS**

Inspection Item	Result
<b>Axle 1, Driver Side Tire</b>	
Tire Tread Depth (mm)	12
Initial Tire Pressure (kPa)	820
<b>Drum Brakes Bolted/riveted block</b>	
Shoe Lining Thickness (mm)	13
Drum Inside Diameter (mm)	418.69
Within OEM specifications?	Yes
<b>S-Cam Drum Brakes</b>	
Chamber Type (size)	30
Brake Stroke (mm)	1

Inspection Item	Result
<b>Axle 1, Passenger Side Tire</b>	
Tire Tread Depth (mm)	12
Initial Tire Pressure (kPa)	820
<b>Drum Brakes Bolted/riveted block</b>	
Shoe Lining Thickness (mm)	14
Drum Inside Diameter (mm)	419.16
Within OEM specifications?	Yes
<b>S-Cam Drum Brakes</b>	
Chamber Type (size)	30
Brake Stroke (mm)	1

Inspection Item	Result
<b>Axle 2, Driver Side, Inner Tire</b>	
Tire Tread Depth (mm)	4
Initial Tire Pressure (kPa)	720
<b>Axle 2, Driver Side, Outer Tire</b>	
Tire Tread Depth (mm)	7
Initial Tire Pressure (kPa)	720
<b>Drum Brakes</b>	

Inspection Item	Result
<b>Axle 2, Passenger Side, Inner Tire</b>	
Tire Tread Depth (mm)	8
Initial Tire Pressure (kPa)	720
<b>Axle 2, Passenger Side, Outer Tire</b>	
Tire Tread Depth (mm)	9
Initial Tire Pressure (kPa)	720
<b>Drum Brakes</b>	

Drum Inside Diameter (mm)	419.14
Within OEM specifications?	Yes
<b>S-Cam Drum Brakes</b>	
Chamber Type (size)	30
Brake Stroke (mm)	1

Drum Inside Diameter (mm)	418.81
Within OEM specifications?	Yes
<b>S-Cam Drum Brakes</b>	
Chamber Type (size)	30
Brake Stroke (mm)	1

Inspection Item	Result
<b>Axle 3, Driver Side, Inner Tire</b>	
Tire Tread Depth (mm)	6
Initial Tire Pressure (kPa)	720
<b>Axle 3, Driver Side, Outer Tire</b>	
Tire Tread Depth (mm)	7
Initial Tire Pressure (kPa)	720
<b>Drum Brakes Bolted/riveted block</b>	
Shoe Lining Thickness (mm)	13
Drum Inside Diameter (mm)	418.9
Within OEM specifications?	Yes
<b>S-Cam Drum Brakes</b>	
Chamber Type (size)	30
Brake Stroke (mm)	1

Inspection Item	Result
<b>Axle 3, Passenger Side, Inner Tire</b>	
Tire Tread Depth (mm)	4
Initial Tire Pressure (kPa)	720
<b>Axle 3, Passenger Side, Outer Tire</b>	
Tire Tread Depth (mm)	4
Initial Tire Pressure (kPa)	720
<b>Drum Brakes Bolted/riveted block</b>	
Shoe Lining Thickness (mm)	13
Drum Inside Diameter (mm)	419.07
Within OEM specifications?	Yes
<b>S-Cam Drum Brakes</b>	
Chamber Type (size)	30
Brake Stroke (mm)	1

Inspection Item	Result
<b>Axle 4, Driver Side, Inner Tire</b>	
Tire Tread Depth (mm)	6
Initial Tire Pressure (kPa)	720
<b>Axle 4, Driver Side, Outer Tire</b>	
Tire Tread Depth (mm)	8
Initial Tire Pressure (kPa)	720
<b>Drum Brakes Bolted/riveted block</b>	
Shoe Lining Thickness (mm)	13
Drum Inside Diameter (mm)	418.59
Within OEM specifications?	Yes
<b>S-Cam Drum Brakes</b>	
Chamber Type (size)	30
Brake Stroke (mm)	1

Inspection Item	Result
<b>Axle 4, Passenger Side, Inner Tire</b>	
Tire Tread Depth (mm)	15
Initial Tire Pressure (kPa)	720
<b>Axle 4, Passenger Side, Outer Tire</b>	
Tire Tread Depth (mm)	12
Initial Tire Pressure (kPa)	720
<b>Drum Brakes Bolted/riveted block</b>	
Shoe Lining Thickness (mm)	13
Drum Inside Diameter (mm)	419.09
Within OEM specifications?	Yes
<b>S-Cam Drum Brakes</b>	
Chamber Type (size)	30
Brake Stroke (mm)	1

Vehicle Inspection Centre #: 13563

Technician #: 317301

Name: PAUL DUBAY

Report Number: 310

613-968-7541


STO ID/Account: 13800214

Software Version: 2025.06.18.1

Trade Code: 310T, 310S

---

Vehicle Inspection Questions? Call the Public Contact Centre 1-833-420-2103 or go to  
<https://www.ontario.ca/page/driveon-emissions-and-safety-inspection-program>



36460

QUAN.	DESCRIPTION	AMOUNT
1	AIR TANK	
1	MOTION RELAY	
8	BRAKE SHOE KITS	
1	170110700 SPRING VALVE	
8	BRAKE DRUMS	
	TOTAL PARTS	
	SUBLET	
	TOTAL SUBLET	

NAME	# RD 4020	DATE	SEPT 9/25	MAKE	MANAC
ADDRESS		TYPE-MODEL	UM	YR	2014
CITY		PHONE		MILEAGE	N/A
				LIC	Y2522N
		SERIAL NO.	ON FILE		
INSTRUCTIONS					AMOUNT
- SAFETY INSPECTION					
- REPLACE LEAKING AIR TANK					
- WELD CRACKS IN SIDE RAIL					
- REPLACE ALL BRAKE SHOES / DRUMS					
- REPLACE SPRING VALVE AND					
REPAIR SERVICE WHEEL ON NEW TANK					
NOTES:					LABOUR
					PARTS
					SUBLET
All estimates are for labour only. Material additional. This company does not assume any responsibility whatever for vehicle or equipment left for repairs, storage or other purposes, or for articles left in same. Vehicle driven by our employees at owner's risk.					HST
I	hereby authorize the above work to be done along with necessary materials.	OUT	I hereby acknowledge my indebtedness in the amount of \$	1,000.00	Real
N					
					TOTAL AMOUNT



# Ontario DriveON

## Annual Inspection Certificate & Safety Standards Certificate



VEHICLE INFORMATION			
Plate#:	Y2822N	Year:	2014
VIN:	2M5931618E1140585	Make:	MANAC
GVWR (kg):	54437	Model:	MANAC TRAILER
Odometer ():		Type:	Trailer

CERTIFICATE INFORMATION	
Annual Inspection Certificate	Expires at the end of: Sep 2026
Safety Standards Certificate	Expires at the end of: October 14, 2025
Vehicle Inspection Certificate Number	LS20AC80
Inspection Start Date	Sep 8, 2025 System Time: 11 : 24
Inspection End Date	Sep 8, 2025 System Time: 13 : 32

VEHICLE INSPECTION CENTRE	
Vehicle Inspection Centre #: 13563	Technician: RICHARD THOMPSON
	
	Technician Signature
	Technician ID: 191215
	STO ID/Account: 13171305
	Trade Code: 310T, 310S

I certify that I inspected this vehicle on the inspection date in accordance with the inspection procedures established by directive under s. 100.7 of the Highway Traffic Act and that the vehicle meets the required equipment and performance standards as detailed in the Vehicle Inspection Report with the above referenced Vehicle Inspection Certificate Number.

This Certificate is not a warranty on the condition of the vehicle.

Vehicle Inspection Questions?

Call the Public Contact Centre 1-833-420-2103 or go to

<https://www.ontario.ca/page/driveon-emissions-and-safety-inspection-program>.

MTO Office use only: 21P3S0990220609XY533

Vehicle Inspection Certificate Number: LS20AC80

Start Date / Time: Sep 8, 2025, 11:24 AM

End Date / Time: Sep 8, 2025, 1:32 PM

VEHICLE/ENGINE INFORMATION	CHASSIS
Plate#: Y2822N	Year: 2014
VIN: 2M5931618E1140585	Make: MANAC
GVWR(kg): 54437	Model: MANAC TRAILER
Odometer:	Fleet ID: QD4020

SAFETY INSPECTION RESULT	PASS
--------------------------	------

SAFETY SYSTEM INSPECTION RESULTS

All Safety System Components Passed Inspection
--

MANDATORY ITEMS

Inspection Item	Result
<b>Axle 1, Driver Side Tire</b>	
Tire Tread Depth (mm)	15
Initial Tire Pressure (kPa)	720
<b>Drum Brakes Bonded/riveted continuous strip</b>	
Shoe Lining Thickness (mm)	Over 15
Drum Inside Diameter (mm)	418.8
Within OEM specifications?	Yes
<b>S-Cam Drum Brakes</b>	
Chamber Type (size)	30
Brake Stroke (mm)	31

Inspection Item	Result
<b>Axle 1, Passenger Side Tire</b>	
Tire Tread Depth (mm)	14
Initial Tire Pressure (kPa)	720
<b>Drum Brakes Bonded/riveted continuous strip</b>	
Shoe Lining Thickness (mm)	Over 15
Drum Inside Diameter (mm)	418.8
Within OEM specifications?	Yes
<b>S-Cam Drum Brakes</b>	
Chamber Type (size)	30
Brake Stroke (mm)	31

Inspection Item	Result
<b>Axle 2, Driver Side, Inner Tire</b>	
Tire Tread Depth (mm)	7
Initial Tire Pressure (kPa)	720
<b>Axle 2, Driver Side, Outer Tire</b>	
Tire Tread Depth (mm)	6
Initial Tire Pressure (kPa)	720
<b>Drum Brakes Bonded/riveted continuous strip</b>	
Shoe Lining Thickness (mm)	Over 15

Inspection Item	Result
<b>Axle 2, Passenger Side, Inner Tire</b>	
Tire Tread Depth (mm)	7
Initial Tire Pressure (kPa)	720
<b>Axle 2, Passenger Side, Outer Tire</b>	
Tire Tread Depth (mm)	9
Initial Tire Pressure (kPa)	720
<b>Drum Brakes Bonded/riveted continuous strip</b>	
Shoe Lining Thickness (mm)	Over 15

Drum Inside Diameter (mm)	418.8
Within OEM specifications?	Yes
<b>S-Cam Drum Brakes</b>	
Chamber Type (size)	30
Brake Stroke (mm)	31

Drum Inside Diameter (mm)	418.8
Within OEM specifications?	Yes
<b>S-Cam Drum Brakes</b>	
Chamber Type (size)	30
Brake Stroke (mm)	31

Inspection Item	Result
<b>Axle 3, Driver Side, Inner Tire</b>	
Tire Tread Depth (mm)	9
Initial Tire Pressure (kPa)	720
<b>Axle 3, Driver Side, Outer Tire</b>	
Tire Tread Depth (mm)	8
Initial Tire Pressure (kPa)	720
<b>Drum Brakes</b>	
<b>Bonded/riveted continuous strip</b>	
Shoe Lining Thickness (mm)	Over 15
Drum Inside Diameter (mm)	418.8
Within OEM specifications?	Yes
<b>S-Cam Drum Brakes</b>	
Chamber Type (size)	30
Brake Stroke (mm)	31

Inspection Item	Result
<b>Axle 3, Passenger Side, Inner Tire</b>	
Tire Tread Depth (mm)	14
Initial Tire Pressure (kPa)	720
<b>Axle 3, Passenger Side, Outer Tire</b>	
Tire Tread Depth (mm)	10
Initial Tire Pressure (kPa)	720
<b>Drum Brakes</b>	
<b>Bonded/riveted continuous strip</b>	
Shoe Lining Thickness (mm)	Over 15
Drum Inside Diameter (mm)	418.8
Within OEM specifications?	Yes
<b>S-Cam Drum Brakes</b>	
Chamber Type (size)	30
Brake Stroke (mm)	31

Inspection Item	Result
<b>Axle 4, Driver Side, Inner Tire</b>	
Tire Tread Depth (mm)	5
Initial Tire Pressure (kPa)	720
<b>Axle 4, Driver Side, Outer Tire</b>	
Tire Tread Depth (mm)	5
Initial Tire Pressure (kPa)	720
<b>Drum Brakes</b>	
<b>Bonded/riveted continuous strip</b>	
Shoe Lining Thickness (mm)	Over 15
Drum Inside Diameter (mm)	418.8
Within OEM specifications?	Yes
<b>S-Cam Drum Brakes</b>	
Chamber Type (size)	30
Brake Stroke (mm)	31

Inspection Item	Result
<b>Axle 4, Passenger Side, Inner Tire</b>	
Tire Tread Depth (mm)	5
Initial Tire Pressure (kPa)	720
<b>Axle 4, Passenger Side, Outer Tire</b>	
Tire Tread Depth (mm)	5
Initial Tire Pressure (kPa)	720
<b>Drum Brakes</b>	
<b>Bonded/riveted continuous strip</b>	
Shoe Lining Thickness (mm)	Over 15
Drum Inside Diameter (mm)	418.8
Within OEM specifications?	Yes
<b>S-Cam Drum Brakes</b>	
Chamber Type (size)	30
Brake Stroke (mm)	31

Vehicle Inspection Centre #: 13563

Technician #: 191215

Name: RICHARD THOMPSON

Report Number: 163

Tablet ID: 2923