

T12K5 Two Speed Drive

X11-182



Motor Mount	SAE "C" 4 Bolt
Motor	211.5cc
	Bidirectional Speed
Min. Hydraulic Flow	30 GPM
Max. Hydraulic Flow	65 GPM
Max. Continuous Pressure	2500 PSI
Output Shaft	2 1/2" & 2 5/8" Hex

OUTPUT SPEED (LOW SPEED)

FLOW/ GPM (LPM)	SPEED/ RPM
30 (113)	15
35 (133)	17
40 (151)	20
45 (170)	22
50 (189)	25
55 (208)	27
60 (227)	30
65 (246)	32

OUTPUT SPEED (HIGH SPEED)

FLOW/ GPM (LPM)	SPEED/ RPM
30 (113)	33
35 (133)	38
40 (151)	43
45 (170)	48
50 (189)	54
55 (208)	59
60 (227)	65
65 (246)	70

OUTPUT TORQUE (HIGH TORQUE)

PRESSURE/ PSI	TORQUE/ FT/LBS (Nm)
1000	4851 (6578)
1250	6064 (8222)
1500	7277 (9868)
1750	8489 (11511)
2000	9702 (13156)
2250	10915 (14800)
2500	12128 (16445)

OUTPUT TORQUE (LOW TORQUE)

PRESSURE/ PSI	TORQUE/ FT/LBS (Nm)
1000	2239 (3036)
1250	2799 (3795)
1500	3358 (4553)
1750	3918 (5313)
2000	4477 (6070)
2250	5038 (6831)
2500	5597 (7590)