

J17-1  
MAY



Prestige Peterbilt (R400)  
1736 Rue Atmec  
Gatineau, Quebec J8R3Y4



### Vehicle Summary

	<b>Unit</b>		<b>Chassis</b>	<b>13200</b>
Model:		Model 389	Fr Axle Load (lbs):	<del>12350</del>
Type:		Tractor	Rr Axle Load (lbs):	40000
Description 1:		[Redacted]	G.C.W. (lbs):	80000
Description 2:		HWY TRACTOR		
	<b>Application</b>		<b>Road Conditions:</b>	
Intended Serv.:	Refrigerated Freight		Class A (Highway)	100
Commodity:	Processed Foods		Class B (Hwy/Mtn)	0
			Class C (Off-Hwy)	0
	<b>Body</b>		Class D (Off-Road)	0
Type:			Maximum Grade:	6
Length (ft):	0		Wheelbase (in):	280
Height (ft):	0		Overhang (in):	70
Max Laden Weight (lbs):	0		Fr Axle to BOC (in):	100.6
	<b>Trailer</b>		Cab to Axle (in):	179.4
No. of Trailer Axles:	2		Cab to EOF (in):	249.4
Type:	Van		Overall Comb. Length (in):	913
Length (ft):	53			
Height (ft):	13.5		<b>Special Req.</b>	
Kingpin Inset (in):	36			
Corner Radius (in):	2			
	<b>Restrictions</b>			
Length (ft):	65			
Width (in):	102			
Height (ft):	13.5			

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

Note: All sales are F.O.B. designated plant of manufacture.

Date: August 25, 2020

Quote Number: QUO-575383-C0E4G5



Sales Code	Std/Opt	Description	\$ List	Weight
<b>Base Model</b>				
0003891	S	<b>Model 389</b> The Model 389 embodies the Peterbilt heritage and merges it with a proven design to create a legendary classic for vocational applications. The lightweight, all-aluminum cab with lap seam construction, aircraft grade fasteners and bulkhead style doors is legendary for its durability. The pod-mounted headlamps are durable, corrosion-resistant and cost-effective to replace. Peterbilt's all-aluminum cab is not only extremely durable, it's also lightweight to allow for increased payloads to maximize performance and profitability.	[REDACTED]	14,915
0091030	O	<b>Processed Foods</b>	0	0
0093160	O	<b>Refrigerated Freight</b> Truck or tractor used in over-the-road hauling of refrigerated freight. Pickup to delivery distance is typically over 100 miles and annual mileage is typically over 60,000 miles per year. Operation is typically on-highway.	0	0
0096010	S	<b>Van</b> An enclosed box trailer without temperature control. Designed to carry pallets or boxes of cargo or equipment.	0	0
0098020	O	<b>Canadian Registry</b> Canadian Registry Required for all vehicles registered in Canada.	0	0
<b>Configuration</b>				
0200700	O	<b>Not Applicable</b> Secondary Manufacturer	0	0
<b>Frame &amp; Equipment</b>				
0514020	O	<b>10-3/4" Steel Rails 355-384"</b> 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	[REDACTED]	510
0611330	O	<b>Zinc Coated Anti Corrosion Treated Frame Rails</b> Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common.	[REDACTED]	0
0644000	S	<b>EOF Tractor Tapered with Crossmember</b> Includes Kingpin Cutout	0	0
0651220	O	<b>Furnish Mudflap Hangers Only, Omit Flaps</b> (Mudflap/Hanger option is required)	[REDACTED]	-8
0651800	O	<b>Peterbilt Rear Mudflaps, Stainless Steel Premium</b> Peterbilt Rear Mudflaps, Hangers, Stainless Steel Premium. (Requires two additional inches of overhang for tractors). Mudflaps aid in protecting the frame and undercarriage from road salt, grime and debris that can cause rust and corrosion. Mud flaps also shield other vehicles from gravel, rocks and road spray.	[REDACTED]	10
0721210	O	<b>Standard A-Brace for Tractor Taper EOF</b>	[REDACTED]	29

Price Level: January 1, 2020

Date: August 25, 2020

Printed On: 8/25/2020 5:34:28 AM

Quote Number: QUO-575383-C0B4G5



Sales Code	Std/Opt	Description	\$ List	Weight
0835860	O	<b>Holland FW35 Fifth Wheel Top Plate</b> One of the top selling topplates on the market. The FW35 is designed for years of guaranteed performance and is the world's most versatile and proven fifth wheel.	2,026	240
0870020		<b>Rear Or Fixd Setting Bhd C/L Bogie 002.</b>	0	0
0890090	O	<b>LH Fifth Wheel Release</b>	0	0
0890540	O	<b>6.6in - 7in Fifth Wheel Height</b>	0	79
0890641	O	<b>Holland Lightweight Air Slide</b> Not available with suspensions > 40k.	0	-20
0890830	O	<b>48" Air Slide</b>		265
0940330	S	<b>No Access Package or Deckplate Desired</b> Use with tractors without access package or deckplate	0	0
<b>Front Axle &amp; Equipment</b>				
1012160	O	<b>Meritor MFS+13B 13,200 lb, 3.5 in. Drop</b> Axle is designed for applications with a gross axle weight rating (GAWR) of 13,200 pounds. Axles include special low-friction bushings, double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service.		10
1111100	O	<b>Peterbilt Front Air Leaf, Shocks 13,200 lb</b> Peterbilt front air leaf suspension offers lightweight components, that handle with the performance of a taper leaf suspension without the added weight. Compatible with air disc or drum brakes.		29
1243000	S	<b>Power Steering Sheppard M100</b> For use with 10,000 to 13,200 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	0	0
1250180	S	<b>Power Steering Reservoir Frame Mounted</b> The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1353540	O	<b>PHP10 Aluminum PreSet PLUS Hubs</b> PHP10 aluminum PreSet PLUS hubs have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug on drive and trailer hubs for inspection of metal particles in lubricant, with a long life oil seal and bearings are pre-adjusted. Use with Front Axle.		-187
1380070	O	<b>Greasable Front Spring Pins</b>		0
1380350	O	<b>Bendix Air Cam Front HP Drum Brakes 16.5x5</b> Complies with reduced stopping distance regulations. For use with 10,000-13,200 lb steer axles, up to and including 40,000 lb drive axles and up to 20,000 lb lift axles. Includes high performance drum brakes, automatic slack adjusters, outboard mounted brake drums.		-25
1380470	O	<b>Meritor Wide Track IPO Standard, Front Axle</b> Meritor wide track front axle offers greater turning radius and ease of service. MFS+ 3.5" Drop / MFS 3.74" Drop. 71in KPI IPO 69in with MFS and MFS+ axles.	0	15
1390540	O	<b>Dust Shields, Cam Brakes, Front Axle</b>		4

Price Level: January 1, 2020

Date: August 25, 2020

[Redacted]

Quote Number: QUO-575383-C0B4G5

Printed On: 8/25/2020 5:34:28 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
1391410	O	Gusseted Cam Brackets, Steer Axle		0
1392520		Omit Front Spring Spacers - Front Air Leaf Only	0	0
1392970	O	Heavy Duty Cam Bushings, Steer Axle		0
<b>Rear Axle &amp; Equipment</b>				
1526150	O	<b>Meritor MT40-14X 40,000 lb</b> Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.		174
1616300	O	PHP10 Iron PreSet PLUS Hubs		0
1660000	O	Dust Shields For Cam Brakes, Drive Axle(s)		4
1680390	S	<b>Bendix ESP Electronic Stability Program With ATC</b> Tractor service only. The Bendix ESP system is designed to continuously monitor a variety of vehicle parameters and sensors to determine if the vehicle is reaching a critical stability threshold. If such a situation develops, the system will quickly and automatically intervene to assist the driver by selectively applying tractor and trailer brakes, and de-throttling the engine.	0	0
1680460	O	Heavy Wall, Drive Axle(s)		88
1680490	O	Gusseted Cam Brackets, Drive Axle(s)		2
1682710	S	<b>Anti-Lock Braking System (ABS) 6S6M</b> ABS-6. Includes air braking system.	0	0
1684200	S	<b>Synthetic Axle Lubricant All Axles</b> Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687010	S	<b>Bendix Air Cam Rear Drum Brakes 16.5x7</b> Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0	0
1687090	O	Diff Lock Tandem Axles		60

Price Level: January 1, 2020

Date: August 25, 2020

Quote Number: QUO-575383-C0B4G5

Printed On: 8/25/2020 5:34:28 AM



Sales Code	Std/Opt	Description	\$ List	Weight
		With Speed Interlock. Automatically Disengages Wheel Diff Lock at Speeds Above 25 mph.		
1703700	O	Ratio 3.70 Rear Axle	0	0
1821980	O	Peterbilt Low Air Leaf 40,000 lb, 54in Axle Spacing, Light Weight		-59
1921040	O	(4) Heavy-Duty Truckmaster Shocks Use with Peterbilt Air Leaf, Low Air Leaf, or Air Trac tandem suspensions.		0
1922260	O	Dash Mtd Dump Switch with Indicator Light Dash mounted dump switch with indicator light for suspension.		2

### Engine & Equipment

2059978	O	X15 565@1950 GOV@2000 2050@1150 Performance Series (2017 Emissions) Includes aluminum flywheel housing. Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life. N21350 C121 65....Maximum Accelerator Vehicle N21370 C128 65....Maximum Cruise Control Speed N21460 C132 1400..PTO Maximum Engine Speed N21520 C133 5.....Idle Shutdown Timer N21610 C188 40....Idle Shutdown Cold Ambient A N21630 C190 80....Idle Shutdown Hot Ambient Ai N21510 C225 NO....Idle Shutdown with Parking B N21450 C231 NO....Gear Down Protection N21570 C233 NO....Idle Shutdown Manual Overrid N21440 C234 NO....Engine Protection Shutdown N21480 C238 NO....Cruise Control and Engine Br N21470 C239 NO....Cruise Control Auto-Resume N21590 C382 YES...Idle Shutdown Hot Ambient Au N21530 C396 YES...Idle Shutdown Warning Period N21540 C397 60....Idle Shutdown Warning Period N21320 C399 120...Green House Gas Vehicle Spee N21620 C189 60....Idle Shutdown Intermediate A N21550 C206 35....Idle Shutdown Percent Engine N21340 C209 120...Maximum Vehicle Speed N21430 C333 0.....Driver Initiated OverrideMax N21410 C334 0.....Driver Initiated Override Ma N21500 C395 300...Green House Gas Automatic En N21400 C400 474...Driver Initiated Override Re N21420 C401 10....Green House Gas Vehicle Spee N21330 C402 0.....Green House Gas Vehicle Spee		340
2091300	O	Enable Preferred EIST Settings	0	0
2091305	S	Engine Idle Shutdown Timer Enabled	0	0
2091315	O	Enable EIST Ambient Temp Overrule	0	0

Price Level: January 1, 2020

Date: August 25, 2020

Printed On: 8/25/2020 3:34:28 AM

Quote Number: QUO-575383-C0B4G5



Sales Code	Std/ Opt	Description	\$ List	Weight
2091376		Eff EIST 300000 Expiration Miles (CAN)	0	0
2091760		Effective VSL Setting 65.0 MPH or Greater (CAN)	0	0
2092016	O	Typical Operating Speed 62 MPH	0	0
2092031	O	<b>Powertrain Optimized for Fuel Economy</b> Best analysis for vehicles which operate at or near cruise speed 90 plus percent of time.	0	0
2140200	S	<b>CARB Engine Idling Compliance</b> PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2511400	O	<b>160 Amp Alternator, 36 SI Brushless</b> The 33SI is a heavy duty brushless alternator that provides more output and service life for today's diesel powered vehicles with large electrical load requirements. The 33SI is offered in 12 volt and 24 volt models with a J180 hinge mount.		10
2516070	O	<b>Remote Voltage Sense Wiring</b>		0
2521090	S	<b>Immersion Type Block Heater 110-120V</b> Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0	0
2522090	O	<b>PACCAR Premium Starter - X15 Engines Only</b> PACCAR Premium 12 volt. Better cranking power, lower current draw and improved warranty to 5-yr/500K miles.		0
2538050	O	<b>4 PACCAR Premium 12V Dual Purpose Batt 2920 CCA</b> Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.		62
2539640	O	<b>LVD (Low Voltage Disconnect)</b> Connected to cab & sleeper for conventional models. Designed to preserve battery life to maintain adequate starting voltage. Equipped with both audible and visual alarms which are activated prior to disconnecting the battery load.		4
2621090	S	<b>DM Advantage ON/OFF Fan Clutch</b> Horton DM Advantage Two-Speed Fan Clutch On/Off for heavy-duty, medium-duty and a variety of off-highway equipment.	0	0
2723220	O	<b>Naturally Aspirated 18.7 CFM Air Compressor</b> X15 Only	0	17
2812170	O	<b>Intebrake (Furnished on Engine)</b> Features a dedicated cam lobe design for optimum power and three-stage engine brake operation.	0	0
2921110	S	<b>PACCAR Fuel/Water Separator Standard Service</b> PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components.	0	0
2921220	O	<b>Fuel Heat for Fuel Filter</b>		0

Price Level: January 1, 2020

Date: August 25, 2020

Quote Number: QUO-575383-C0B4G5

Printed On: 8/25/2020 5:34:28 AM



Sales Code	Std/Opt	Description	\$ List	Weight
2921310	S	No Electric Heat Option for Fuel Filter	0	0
3010400	O	<b>Engine Protection Shutdown</b> Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	6	0
3114270	S	<b>High Efficiency Cooling System</b> Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0	0
3211040	O	<b>(2) 15" Premium SS Air Cleaners, Cowl Mtd SS Cap</b>		68
3365290	O	<b>Exhaust Single RH Horizontal</b> DPF/SCR RH Under Frame.		-187
3382520	U	<b>Dual Cab Mounted Brackets Only, Vertical Exhaust</b> <i>Narr LOCAL EXHAUST STACK INSTULATION</i>	0	0
<b>Transmission &amp; Equipment</b>				
4021920	O	<b>Eaton RTLO20918B 18-Speed</b> Includes oil-to-water cooler, rear transmission support, direct shift pattern. Synthetic lubricant to reduce friction, improve efficiency, & extend component life. Magnetic transmission oil drain plug captures & holds any metal fragments in transmission oil to extend service life. Torque limiting clutch brake. Forward ratios: LL-14.4, L-12.29, 1st-8.51, 2nd-7.26, 14th-1.00, 15th-0.86, 16th-0.73. Reverse ratios: R1-15.06, R2-12.85, R3-4.03, R4-3.43		125
4211280	O	<b>SPL350 HD-XL Driveline, 1 Midship Bearing</b>		145
4216520	O	<b>SPL250 XL Driveline Interaxle</b> Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles.		28
4233030	O	<b>(1) Dash Mounted Single Acting Air PTO Control</b> Standard with PTO engaged indicator light on Class 8 units. Occupies the space of one gauge. Specing PTO switch does not ensure the PTO will fit.		0
4256100	S	<b>Manual Shifter, Black</b>	0	0
4321000	O	<b>Self-Adjust Clutch IPO Easy Pedal</b>		0
4380220	O	<b>Pre-Damped Clutch</b> Pre-damped feature consists of a set of small springs around the hub, which dampen the engine torsional vibrations at idle speeds before they can reach the transmission and cause gear rattle. Option required on		0

Price Level: January 1, 2020

Date: August 25, 2020

Printed On: 8/25/2020 5:34:28 AM

Quote Number: QUO-575383-C0B4G5



Sales Code	Std/ Opt	Description	\$ List	Weight
		configurations specifying an ISX15 Family 1 engine and a manual transmission with torque ratings of 1650 lb-ft torque or higher.		
4380290	O	<b>Remote Lube Hoses For Release Bearing, Cross Shafts</b> mounted under hood left-hand rail		6
<b>Air &amp; Trailer Equipment</b>				
4510320	S	<b>Bendix AD-IS Air Dryer, Heater</b> Bendix Air Treatment Oil Coalescing filter, extended purge. Collects and removes solid, liquid and vapor contaminants before they enter the air brake system.	0	0
4520420	O	<b>Pull Cords All Air Tanks</b>		1
4540420	S	<b>Nylon Chassis Hose</b>	0	0
4541490	O	<b>Tractor Air System, Spring Brake Relay IPO QR-1C</b> Functions as a quick release valve for the emergency side of the spring brakes.		0
4543320	S	<b>Steel Painted Air Tanks</b> All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4543330	O	<b>Aluminum Polished Air Tanks Outside Frame Rails</b> Exposed air tanks outside the frame rails will be polished aluminum. Air tanks mounted inside the frame rails or covered by other components will be either painted aluminum (4543340) or painted steel (4543320) air tanks depending on air tank option selected.		0
4543530	O	<b>Clear Outside Frame of All Air System Components</b> LH BOC		0
4543540	O	<b>Clear Outside Frame of All Air System Components</b> RH BOC		0
4610070	O	<b>Self Returning Brake Hand Valve, Column Mounted</b>		0
4610910	O	<b>15' AE Lines Straight, 3 in 1, (2) 7-Way Plugs</b> QCP socket, without QCMS, with Quick Clamp.		0
4611460	O	<b>AE Connections Mounted On LH Rail</b>		0
4614810	S	<b>AE Connections BOC/BOS, Hose Tenna</b>	0	0
<b>Tires &amp; Wheels</b>				
5056830	O	<b>FF: MN 14ply 11R22.5 X Line Energy Z</b> Efficiency Rating: Fair The MICHELIN X LINE ENERGY Z tire is a line haul steer tire built for high miles and better rolling resistance. Diameter= 41.3 inches; SLR= 19.3 inches		8

Price Level: January 1, 2020

Date: August 25, 2020

Printed On: 8/25/2020 5:34:28 AM

Quote Number: QUO-575383-C0B4G5



Sales Code	Std/Opt	Description	\$ List	Weight
5169190	O	<b>RR: MN 16ply 11R22.5 XDS2</b> Diameter = 41.8 inches; SLR = 19.5 inches. Compares to Goodyear G244 MSD and Bridgestone L320 tread.	[REDACTED]	160
5190008	S	<b>Code-rear Tire Qty 08</b>	0	0
5220710	O	<b>FF: Alcoa 882677 22.5 X 8.25 Clean Buff Finish</b> Aluminum	[REDACTED]	-50
5320710	O	<b>RR: Alcoa 882677 22.5X8.25 Clean Buff Finish</b> Aluminum. Clean buff finish on boths sides as applicable. Finish options for heavy-duty trucks, 2.5 lbs. weight savings, new hub bore with less metal to metal contact to hinder corrosion with a maintained half dual space and load rating.	[REDACTED]	-200
5390008	S	<b>Code-rear Rim Qty 08</b>	0	0
5409300	O	<b>Wheel Guards, Tandem Axle</b> Wheel guards provide a protective barrier to maintain the integrity between the brake drums and wheels to ensure the maximum life for your polished wheels.	[REDACTED]	0
5409310	O	<b>Wheel Guards, Steer Axle</b> Wheel guards provide a protective barrier to maintain the integrity between the brake drums and wheels to ensure the maximum life for your polished wheels.	[REDACTED]	0
<b>Fuel Tanks</b>				
5552400	O	<b>26" Aluminum 150 Gallon Fuel Tank RH BOC</b> Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	[REDACTED]	42
5556400	O	<b>26" Aluminum 150 Gallon Fuel Tank LH BOC</b> Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	[REDACTED]	42
5603150	O	<b>Location RH BOC 150 Gallon</b>	0	0
5604150	O	<b>Location LH BOC 150 Gallon</b>	0	0
5650140	O	<b>Fuel Tank Fill Rear</b> Not available on under cab fuel tanks	0	0
5650490	O	<b>Fuel Cooler</b> Required with single fuel tank	[REDACTED]	15
5651700	O	<b>(4) Straps Per Tank, (2) Tanks</b> Subject to frame review	[REDACTED]	101
5652830	O	<b>Polish All Fuel / Hydraulic Tank Straps</b> Does not apply to rectangular DEF tank straps	[REDACTED]	0
5652890	S	<b>DEF Tank Mounted LH BOC</b> Models 220 and 520 mounted left hand back-of-cab.	0	0

Price Level: January 1, 2020

Date: August 25, 2020

Printed On: 8/25/2020 5:34:28 AM

Quote Number: QUO-575383-C0B4G5



Sales Code	Std/Opt	Description	\$ List	Weight
5652980	O	DEF To Fuel Ratio Between 1:1 And 2:1	0	0
5653000	O	Polished Stainless Steel Cover For DEF Tank		0
5655029	O	DEF Tank Medium 20.7 Gallon Capacity		22
<b>Battery Box &amp; Bumper</b>				
6010030	S	Aluminum Battery Box LH Under Cab, Non-Slip Step Includes diamond pattern block shaped cover in traditional/vocational models and a smooth finish tapered cover on aerodynamic models	0	0
6030150	O	Rubber Battery Pad In Bottom of (1) Battery Box Mat in box that holds batteries only		4
6030540	O	Polish Battery/Tool Box(s), Aftertreatment Cab Entry complete		0
6034620	O	Heavy Duty Battery Box Step Reinforcement		2
6040030	O	Aluminum Tool Box, Non-Slip Step RH Under Cab Includes diamond pattern block shaped cover in Traditional/Vocational models and a smooth finish tapered cover on Aerodynamic Models.		45
6122910	O	Steel Texas Style Bumper Chromed Steel Texas styled bumper chromed with two tow points.		-55
6132040	O	Omit Front Tow Pin(s)		-2
<b>Cab &amp; Equipment</b>				
6510130	O	Alum Cab 131in BBC Alum Hood SFFA fenders w/polished crown, spring tilt assist. Proprietary anti-blow-down locking mechanism that keeps hood open during servicing & prevents unintentional closing. Hood latch each side secures hood to cowl. Proprietary all-alum cab is light weight & durable for long service life. One-piece roof reduces potential for leaks. Two-piece windshield for cost effective windshield replacement. Lap seam construction & aircraft fasteners has greater clamp load than rivets. Bulkhead style doors provide virtually water-tight, rattle-free performance. Extruded alum door frames for strength & durability. Full length, heavy-duty piano-type stainless steel door hinges & pins provide durability. View window in RH door for safety. Electric windshield wipers & washers w/intermittent wiper function. Grab handles mtd on cab LH & RH for cab access. Convex mirror over RH door & below each rear view mirror for improved visibility & safety.		90
6540160	O	Thermal Insulation Package in Cab Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure.		2
6701870	O	78" UltraCab Sleeper w/Prestige Interior Includes raised roof cab, raised wide walk-through opening between cab and sleeper, full-width baggage compartment with LH/RH access doors, tilt-up bunk with 42 in x 77 in coil spring mattress, LH/RH enclosed closets with overhead storage, (2) two-way vents, roofline		1,385

Price Level: January 1, 2020

Date: August 25, 2020

Printed On: 8/25/2020 5:34:28 AM

Quote Number: QUO-575383-C0B4G5



Sales Code	Std/Opt	Description	\$ List	Weight
		storage pockets, storage space in cab header, (2) storage bins, storage tray, heater/air conditioner with air filter and controls in sleeper, cigar lighter and ashtray, additional 12v power outlet, digital alarm clock, sleeper curtain, bunk restraint, floor carpet, (2) door-actuated baggage compartment lights, rubber floor mats in baggage compartment, (3) local reading/spot lights, overhead Xenon incandescent light, and cab/sleeper air suspension.		
6810080	O	<b>Refrigerator- 72/78in UltraCab Sleeper</b> The refrigerator may be turned ON/OFF with the temperature control inside the refrigerator. Refrigerator is 1.8 cu ft.		30
6810240	O	<b>Power Lock on Sleeper Door</b> For use with Prestige Sleeper Interior only. The power sleeper door lock is standard in Platinum Sleeper Interior.		2
6810290	O	<b>Sleeper Door Diaphragm (Curtain)</b>		2
6812560	O	<b>Adjustable Appliance/TV Shelf-RH Upper Cabinet</b> For use with 72in/78in UltraCab Sleeper with Prestige Interior. Includes TV Antenna, tie-down strap, and 12V power outlet. (standard with 72in/78in UltraCab with Platinum Interior)		15
6814220	O	<b>(2) Sleeper Closet Doors</b> For use with 72/78in UltraCab with Prestige Interior.		2
6814270	O	<b>Thermal Insulation Pkg - UltraCab 72", 78" &amp; 80"</b> The thermal insulation package is designed to make the compartment(s) thermally efficient in extreme temperatures. Models 579 and 567 include thick closed-cell foam in the floor carpet and fiber insulation in the walls and roof structure. Models 389, 367 and 365 include thick closed-cell foam in the floor and special mylar-faced foam in the walls and roof structure.		4
6911710	O	<b>National Premium Driver Seat</b>		4
6921710	O	<b>National Premium Passenger Seat</b>		4
6930580	O	<b>Drivers Armrests - LH &amp; RH</b>		4
6930590	O	<b>Passenger Armrest - LH only</b> Required with Evolution LX seats, optional with Evolution ST Seats.		2
6930800	O	<b>Black Seat Color IPO Standard Color</b>		0
6933010	O	<b>Passenger Seat Swivel, 180 Degree Front To Rear</b> Not available with Evolution non-adjustable seat, code 6921740		11
6939400	S	<b>Air Ride Driver</b>		0
6939420	S	<b>High Back Driver</b>	0	0
6939450	O	<b>Leather Driver</b>		0
6939500	O	<b>Air Ride Passenger</b>		43
6939520	S	<b>High Back Passenger</b>	0	0

Price Level: January 1, 2020

Date: August 25, 2020

Printed On: 8/25/2020 5:34:28 AM

Quote Number: QUO-575383-C0B4G5



Sales Code	Std/ Opt	Description	\$ List	Weight
6939550	O	Leather Passenger	[REDACTED]	0
7000350	S	Power Door Locks Both Doors	0	0
7001520	O	Adjustable Steering Column - Tilt/Telescope	[REDACTED]	11
7001580	O	Vanity Mirror on Inside Sunvisors For use with ProBilt 1.9, Prestige (1.9 & 2.1) or Premier (2.1) interiors.	15	0
7001590	O	Doors on Header Mounted Cabinets For use with UltraCab with Prestige Interior.	[REDACTED]	0
7001620	S	Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0	0
7039070	O	Prestige Interior - Arctic Gray Includes innovative charcoal A & B instrument panels and color-matched C & D instrument panels, monochromatic color-coordinated dash with glare-resistant, charcoal soft-touch upper, black bezel on gauges, cigar lighter and ashtray with power port, burlwood insert on contoured doorpads, LH and RH door mounted map pockets with built-in courtesy lights, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, padded vinyl headliner and wall panels, extruded rubber floor covering, (2) inside sunvisors, (2) coat hooks, header-mounted domelight, driver and passenger dome/reading lights, footwell lighting, integrated "dead pedal", (5) inside entry grab handles, cup holder and map bin in dash.	[REDACTED]	22
7040310	O	Black Floor Carpet IPO Interior Color	0	0
7230350	O	2-Piece Flat Windshield	[REDACTED]	0
7230680	S	Power Lift Windows - Both Doors For use with ProBilt or Prestige Interior	0	0
7310260	O	D2 Fuel Fired Sleeper Heater W/Digital Controller Digital display shows ambient temperature and temperature settings, diagnostic read-out shows fault codes and ventilation mode which allows fan to be on without heater. Offers 4 heat levels, compact size, CARB compliant, runs approximately 15-20 hours per gallon of diesel fuel.	[REDACTED]	8
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7330160	O	Arctic Wrap on Sleeper Heater Water Supply Lines (Requires sleeper heater on conventionals)	[REDACTED]	0
7330700	S	Peterbilt Comfort Control - Cab	0	0
7330710	O	Peterbilt Comfort Control - Sleeper	[REDACTED]	2
7330770	O	Air Conditioning Excise Tax - Canada	[REDACTED]	0

Price Level: January 1, 2020

Date: August 25, 2020

Printed On: 8/25/2020 5:34:28 AM

Quote Number: QUO-575383-C0B4G5



Sales Code	Std/Opt	Description	\$ List	Weight
7410040	O	<b>Outside Sunvisor - Stainless Steel</b> Not available with 2.1M high roof sleeper.		4
7560100	O	<b>Mirrors SSTL Each Side Heated and Motorized</b> with Switch on Door.		2
7560850	S	<b>(2) Convex 8 Inch SSTL Mirrors</b> Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops.	0	0
7610020	O	<b>(1) Air Horn 15" Painted</b> Mounted under cab.		0
7722120	O	<b>ConcertClass, AM/FM, Weatherband, 3.5 Aux</b>		10
7725740	O	<b>Midlevel Speaker Package For Cab</b> (4) Speakers		6
7725780	O	<b>Midlevel Speaker Package For Sleeper</b> (2) Speakers w/Subwoofer		34
7728040	O	<b>Bluetooth Phone and Audio</b>		0
7728050	O	<b>USB Port</b>		0
7740100	O	<b>Cobra 40 Channel CB Radio w/Integral Speaker</b> Includes illuminated front panel		11
7748520	O	<b>CB Antenna Mounting, Vertical, Center BOC/BOS</b>		1
7749110	O	<b>Mount CB Speaker LH Rear Corner Cab Headliner</b>		2
7788055	S	<b>SmartLINQ Remote Diagnostics</b> SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or Cummins Westport natural gas engine.	0	0
7788058	O	<b>24 Months SmartLINQ Subscription</b> Cummins Engines.	0	0
7788260	O	<b>Radio Antenna Mounted on RH Mirror Bracket</b>		0
7850560	O	<b>Additional 12V Power Outlet-Dash Mounted</b> For use with ProBilt or Prestige Interior (Standard on Platinum Interior).		0
7851040	O	<b>Removable Bugscreen Behind Grille</b>		2

Price Level: January 1, 2020

Date: August 25, 2020

Quote Number: QUO-575383-C0B4G5

Printed On: 8/25/2020 5:34:28 AM



Sales Code	Std/Opt	Description	\$ List	Weight
7851480	S	<b>Peterbilt Electric Windshield Wipers</b> With Intermittent Feature.	0	0
7870320	O	<b>Sleeper Side Extenders Not Desired</b> 78 inch UltraCab Only		-33
7900040	O	<b>Fire Extinguisher, Ship Loose</b> Hazmat approved UL listed/rated ABC.		7
7900090	O	<b>Triangle Reflector Kit, Ship Loose</b> Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.		13
7901140	O	<b>Backup Alarm (87-112 DB)</b> Variable adjusting		6
8011100	O	<b>Main Transmission Temperature Gauge</b> 52mm Round, backlit		0
8011220	O	<b>Axle Temperature Gauges, Tandem Drive</b>		2
8011390	O	<b>Engine Oil Temperature Gauge</b>		0
8021010	O	<b>Air Application Gauge</b>		0
8021380	S	<b>Air Restriction Indicator</b> Mounted on air cleaner, intake piping, or firewall	0	0
8022150	O	<b>Fuel Filter Restriction Gauge</b>		0
8032420	O	<b>Buzzer On Air Suspension Dump Valve</b> Requires dash mounted dump valve (1922260)		0
8041170	O	<b>Speedometer KPH IPO MPH</b>		0
8070000	O	<b>Disable Brake Light With Engine Brake</b>		0
8070260	O	<b>Switch To Deactivate Bendix ATC Traction Control</b> Bendix ATC is required on the specification. Switch is to temporarily disable the Traction Control in extreme conditions such as snow, ice or mud. The ATC warning light will display in a constant state.	0	0
8071020	O	<b>Manifold Pressure Gauge</b>		2
8071280	O	<b>Suspension Pressure Gauge</b>		2
8071310	O	<b>Ammeter</b> 52mm Round, backlit		0
8071870	S	<b>Main Instrumentation Panel, Graphics Display</b> Includes speedometer with trip odometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights with audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder, rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes	0	0

Price Level: January 1, 2020

Date: August 25, 2020

Quote Number: QUO-575383-C0B4G5

Printed On: 8/25/2020 5:34:28 AM



Sales Code	Std/Opt	Description	\$ List	Weight
		headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.		
8072910	O	Up to (6) Additional Rocker Switches In D Panel		0
8075000	O	Custom Nameplate Use narrative, maximum 2 lines, 25 characters per line		0
8111140	S	Headlights Projector Module Pod Integral Turn Signals	0	0
8120600	O	Marker Light, Mid-Frame Mounted Per Federal regulations (FMVSS 108), all complete tractors over 30/360 in overall length require intermediate marker lights (with reflex reflector) mounted as close as possible to mid-frame. Marker lights can be mounted on sleeper extender, fuel tank bracket, fuel tank step, or side sensor bracket. Dealers can choose to shorten chassis length to eliminate requirement for marker lights or choose between frame mounted or sleeper extender mounted, (if applicable), marker lights. If frame mounted, engineering will decide which of the three mounting locations to use.		5
8121170	O	(5) Marker Lights, Bus LED Bullet		0
8131420	O	Switch & Wiring For F/O Fog Lights With bumper cutouts		0
8133110	O	Switch & Wiring F/O Auxiliary Light Under cab/sleeper (15 amp max), includes switch on the dash that will power metri-pack sealed connections at the left-hand / right-hand side of cab at base of the firewall. Bundle panel light harness break outs with firewall harness.		2
8133120	O	Switch & Wiring F/O Aux Light On Air Cleaners Includes switch on the dash which will power metri-pack sealed connections at the left-hand / right-hand air cleaner outlets		2
8133500	O	Switch On Dash For Light In Sleeper In addition to standard switch		2
8133960	O	Daytime Running Lights The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.		0
8140000	S	Incandescent Oval Stop/Turn/Tail/Backup In tractor taper end of frame crossmember	0	0
8140490	O	Additional LED Round Turn Signal Mirror mounted		2
8141150	O	Additional LED Turn Signals Mounted lower rear corners back of cab / back of sleeper		7
8151130	O	(2) Load Lights, Flush Mounted Low Inboard Loc A		4
8151140	O	(2) Load Lights, Flush Mounted Low Outboard Loc B		4
8153100	O	(1) F/O Load Light, Switch, 10' Wire Coil Under / in cab / sleeper baggage compartment		2

**Paint**

Price Level: January 1, 2020

Date: August 25, 2020

Quote Number: QUO-575383-C0B4G5

Printed On: 8/25/2020 9:34:28 AM



Sales Code	Std/ Opt	Description	Price	Weight
8530780	O	(1) Color Axalta Two Stage - Cab/Hood/Sleeper Base Coat/Clear Coat N85020 A - P3230EY VIPER BLUE N85500 CAB ROOF P3230EY VIPER BLUE N85300 FENDER P3230EY VIPER BLUE N85200 FRAME L0001EA BLACK N85400 HOOD TOP P3230EY VIPER BLUE N85720 SK FAIRINGS P3230EY VIPER BLUE N85600 SLEEPER ROOF P3230EY VIPER BLUE		0
8531320	O	Axalta Two Stage Effect - Metallic/Pearl Cab/Hood & Sleeper Only		0

**Shipping Destination**

**Options Not Subject To Discount**

9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0	0
<b>Miscellaneous</b>				
9409013	O	78in Sleeper / Prestige Interior (7M)	0	0
9409800	S	2017 EPA Emissions Engine Warranty Only	0	0
9409869	O	Presentation Created With SmartSpec	0	0

**Promotions**

**Order Comments**

<b>Total List Price (W/O Freight &amp; Warranty &amp; Surcharges )</b>	\$266,348
Marketing and Service Support Fee	\$875
Prepaid Freight	\$2,725
<b>Total Surcharge/Options Not Subject To Discount</b>	\$0
<b>Total Weight</b>	18,634

**Prices and Specifications Subject to Change Without Notice.**

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

Price Level: January 1, 2020  
[Redacted]  
Printed On: 8/25/2020 5:34:28 AM

Date: August 25, 2020  
Quote Number: QUO-575383-C0B4G5



**PRICING DISCLAIMER**

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*