



S20-2
MAY

INLAND - LANGLEY (I018)
26770 GLOUCESTER WAY
LANGLEY, British Columbia V4W 3V6

SPRUCE HOLLOW HEAVY HAUL
2511 GUILDFORD DR
ABBOTSFORD, British Columbia V2S
5L9
Canada

Bill Coutts
Cell Phone: 778-808-2044
Office Phone: 604-607-0300
Email: bcoutts@inland-group.com

Ron Madil
Email:
ron@sprucehollowheavyhaul.com

Vehicle Summary

	Unit		Chassis	
Model:	W900 Series Conventional.	Fr Axle Load (lbs):		16000
Type:	TRACTOR	Rr Axle Load (lbs):		69000
Description 1:	W900 B LOWBED UNIT	G.C.W. (lbs):		140000
Description 2:	Special 100 Anniversary Edition			
	Application	Road Conditions:		
Intended Serv.:	Heavy equipment transport. Vehicles	Class A (Highway)		90
	us			
Commodity:	Heavy machinery.	Class B (Hwy/Mtn)		10
		Class C (Off-Hwy)		0
		Class D (Off-Road)		0
	Body	Maximum Grade:		6
Type:		Wheelbase (in):		268
Length (ft):	0	Overhang (in):		88
Height (ft):	0	Fr Axle to BOC (in):		90
Max Laden Weight (lbs):	0			
		Cab to Axle (in):		178
		Cab to EOF (in):		266
	Trailer	Overall Comb. Length (in):		1068
No. of Trailer Axles:	5			
Type:	Lowboy			
Length (ft):	65			
Height (ft):	13.2	Special Req.		
Kingpin Inset (in):	24	Canadian Registry		
Corner Radius (in):	0			
	Restrictions			
Length (ft):	75			
Width (in):	102			
Height (ft):	13.5			

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	Weight
Model			
0000900	S	W900 Series Conventional. Threaded steel spring pins & bushings, 16mm. fasteners from rear cab support to end-of-frame, except tractor taper crossmember. Vinyl inside sunvisors, driver side includes strap & mirror, rider side includes strap; Under-dash center console w/ 2 cup holders, 2-12V outlets & a storage compartment, Glove box door with locking latch.	15,873
0070077	S	W900: Straight or Sloped Hood.	0
0080055	O	CARB Idle Emissions Reduction - Cummins	0
0090037	O	72 in. AeroCab Sleeper & Tridem Rear Axle.	0
0098470	O	State of Registry: Canada	0
Engine & Equipment			
0130337	O	X15 605V 605@2000 2050@1000 2021 with Intebrake, Productivity Series N09420 C333 0.....Reserve Speed Limit Offset (N09380 C334 0.....Maximum Cycle Distance (C334 N09360 C400 474...Reserve Speed Function Reset N09200 C399 120...Standard Maximum Speed Limit N09400 C401 10.....Maximum Active Distance (C40 N09220 C402 0.....Expiration Distance (C402) N09540 C395 1259..Expiration Distance (C395) N09260 C121 64....Maximum Accelerator Pedal Ve N09440 C234 NO....Engine Protection Shutdown (N09460 C231 NO....Gear Down Protection (C231) N09580 C133 5.....Timer Setting (C133) N09680 C233 NO....Idle Shutdown Manual Overrul N09480 C132 1400..Max PTO Speed (C132) N09300 C128 64....Maximum Cruise Speed (C128) N09500 C239 NO....Cruise Control Auto Resume (N09520 C238 YES...Auto Engine Brake in Cruise N09240 C209 120...Hard Maximum Speed Limit (C2 N09780 C190 80....High Ambient Temperature Thr N09740 C188 40....Low Ambient Temperature Thre N09760 C189 60....Intermediate Ambient Tempera N09720 C382 YES...Enable Hot Ambient Automatic N09600 C396 YES...Enable Impending Shutdown Wa N09620 C397 60....Timer For Impending Shutdown N09640 C206 35....Engine Load Threshold (C206) N09560 C225 YES...Enable Idle Shutdown Park Br	0
1000046	O	EPA Emissions Warranty Engine	0
1000151	S	PremierSpec	0
1000170	O	Enable engine regeneration in PTO mode Cummins	0

Price Level: January 1, 2023
 Deal: W900 B LOWBED UNIT
 Printed On: 1/19/2023 11:10:30 AM

100% Complete

Date: January 18, 2023
 Quote Number: QUO-929396-X1D8J1



Sales Code	Std/ Opt	Description	Weight
1000233	O	Powertrain Protect with SmartAccel - X15 Torque Rate Limiting	0
1000244	O	Gearing Analysis: Balance power/economy blend results.	0
1000256	O	Customer's Typical Operating Spd: 64 MPH	0
1000744	O	Effective VSL Setting 65.0 MPH or Greater (CAN)	0
1000856	O	Enable Most Fuel Efficient EIST	0
1000857	S	Engine Idle Shutdown Timer Enabled	0
1000859	O	Enable EIST Ambient Temp Override	0
1000912		Eff EIST 1259000 Expiration Miles (CAN)	0
1002070	O	Air compressor: Cummins 37.4 CFM *For C500 Twin Steer use 1002075	15
1042260	O	Air Cleaner: Dual 15 in. stainless steel polished cowl mounted w/Kenworth bug w/Preferred Fit Element.	44
1099091	O	Fairings dual stainless steel for cowl mounted air cleaners.	2
1105220	S	Fan Hub: Horton 2-Speed for X15	0
1127950	S	Cooling module: W9 1670 square inches. Includes aluminum radiator core, aluminum charge air cooler, translucent surge tank and washer bottle, silicone hoses, and extended life coolant. Drain valve is not available with Allison transmissions.	0
1160105	O	Radiator winterfront.	2
1160208	O	Radiator bug screen mounted between hood & grille.	2
1247232	O	EXH: 2021 RH Under DPF/SCR with Dual SOAC mounted tailpipe, Aerocab sleeper only	132
1290448	O	Tailpipe: 7 in. dual 48 in. 45 degree curved.	17
1292332	O	EXH Shield: KW100 Dual Stainless Steel With full perforation	0
1292389	O	Black Back Plate for Dual Exhaust Shields	0
1321109	S	Fuel Filter:PACCAR Standard Service Interval Fuel/Water Separator. 2017 and Later Emissions	0
1321200	O	Run Aid:None *For Fuel Filter	0
1321300	S	Start Aid:None *For Fuel Filter	0
1504005	O	Immersion block heater 120V 1500W w/plug under door on C500, T660, T800 & W900.	2

Price Level: January 1, 2023

100% Complete

Date: January 18, 2023

Deal: W900 B LOWBED UNIT

Quote Number: QUO-929396-X1D8J1

Printed On: 1/19/2023 11:10:30 AM



Sales Code	Std/ Opt	Description	Weight
1506055	O	Engine oil pan heater, 120V / 300W Includes plug. For use with EPA 2007+ engines.	2
1507008	O	Block heater & oil pan heater wired to separate plugs.	0
1600116	O	Cummins air intake throttle overspeed shutdown for Cummins X15 engines.	0
1816260	S	Alternator: PACCAR 160 amp, brush type	0
1821215	O	Batteries: 4 PACCAR GP31 threaded post (700-730) 2800-2920 CCA dual purpose.	57
1836103	O	PACCAR Premium 12V Starter W/ Cummins X15 Engines PACCAR 12 volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system with circuit protection circuits number & color coded.	0
1840006	O	Battery disconnect switches 2, mounted in cab Requires battery box LH under.	2
1840063	O	Low voltage disconnect only available with 72 in. or 75 in. sleepers.	0
1900082	O	Multi-function engine connector for body builder interface for Cummins.	0
1900996	O	Jump start terminals under hood.	12
Transmission & Clutch			
2058771	O	Transmission: Fuller RTLO20918B 18-speed w/oil cooler & pump. Standard with synthetic lubricant. Includes severe-duty pilot bearing on all class 8 models. *Torque Limit: 2050 pound-feet.	16
2154321	O	Aux: AT1202 2-speed electric over air shift 3-position rocker switch dash mounted and includes synthetic lubricant	522
2250494	O	Clutch: Eaton 15-1/2 in. Advantage Self-Adjust to 2050 ft-lb, Ceramic, 6-Paddle	6
2294004	O	Kenworth Air Assisted clutch booster for mechanical clutch linkage	2
2294035	O	Grease bank for clutch & cross shaft.	11
2406314	O	Driveline: 2 SPL250SF no centerbearing For use with auxiliary transmission, jackshaft, or transfer case.	93
2410005	O	Optional neutral start switch.	0
2429100	O	Chassis will be fitted with LH transmission PTO. (Prevents ECU From Interfering With PTO Only)	0
2444000	O	Chrome shift lever for main transmission.	0
2460042	O	14" Eaton High Capacity Standard Cooler Oil to Water. For Transmission 1550-2250 LBFT, 18-speed AutoShift.	0
2460051	O	Kenworth oil to water cooler for auxiliary transmission.	0
2493004	O	Aluminum clutch housing replacing cast iron for engines w/torque ratings 1450 to 2050 lb-ft.	-52

Price Level: January 1, 2023
 Deal: W900 B LOWBED UNIT
 Printed On: 1/19/2023 11:10:30 AM

100% Complete

Date: January 18, 2023
 Quote Number: QUO-929396-X1D8J1



Sales Code	Std/ Opt	Description	Weight
Front Axle & Equipment			
2536002	O	PACCAR FX-20 Front Axle rated at 20K 4" drop standard track	156
2607015	O	Front Brakes: 14,601-22K Bendix RSD ADB22X disc brake.	10
2690024	S	Splined rotor for front air disc brakes for use with aluminum hubs.	0
2690039	O	Integral Knuckle for Air Disc Brake, for use on PACCAR FX Steer Axle	-33
2701319	O	Front Hubs Aluminum hub pilot 20,000 lbs. 16.5x6in. or 7in. or air disc brakes. 10 Bolt, 11-1/4 in. bolt circle.	16
2741970	S	ConMet PreSet Plus Hub package; front axle.	0
2750001	S	Hubcap: front vented.	0
2769000	S	Slack Adjusters included w/ front axle or brake. Also use w/ disc brakes.	0
2864116	O	Front Springs: Taperleaf 16K w/shock absorbers w/ maintenance-free elastomer spring pin bushings. Two leaf. Standard with rubber pins. Not available on W900L.	39
2893622	O	Dual power steering gears: 20K TRW TAS65.	60
2899336	O	Power Steering Cooler:Radiator Mounted Air-to-Oil	11
2900616	O	Threaded Bushings for taperleaf spring 16K, 18/20K, 22K, 40K replacing rubber.	0
Rear Axle & Equipment			
3156906	O	Tridem Meritor RZ-XX-166 single reduction rear axle. Capacity varies. Wide track.	3,181
3200410	O	Rear Axle Ratio - 4.10.	0
3306016	O	Tridem Rear Brakes Bendix RSD-Compliant ADB22X Disc brake for tridem axle, Max GAWR 69k.	60
3392704	O	Splined rotor for tridem rear air disc brakes for use with aluminum hubs.	-312
3407090	O	Tridem Rear Hubs: Aluminum hub pilot 69K 11-1/4 in. bolt circle.	0
3441973	O	ConMet PreSet Plus Hub package; tridem rear axle	0
3465900	O	Rear slack adjusters included w/ axle or air disc brakes.	0
3485003	O	Spring Brake Included With Air Disc Brake Tridem	0
3490901	O	Rear air disc brake dustshields for single axle; includes pads and rotor shields.	6
3495225	O	FMVSS-136 Stability Control Schedule Review	0

Price Level: January 1, 2023
 Deal: W900 B LOWBED UNIT
 Printed On: 1/19/2023 11:10:30 AM

100% Complete

Date: January 18, 2023
 Quote Number: QUO-929396-X1D8J1



Sales Code	Std/ Opt	Description	Weight
		Chassis meets FMVSS-136 requirements and must be equipped with Electronic Stability Control. Reference Option code placed on order.	
3495231	O	Bendix 6S/6M anti-lock brake system w/ air traction control (ATC) and electronic stability program (ESP) for tractor.	15
3500060	O	Interaxle Driveline: 2 Dana SPL170XL only available w/tridem axles.	94
3511425	O	Driver Controlled Differential Lock (Crosslock) for Meritor Axles to 69K forward rear, center rear & rear axle.	52
3573112	O	Flip valve, wiring and light separate for wheel differential lock or driver controlled differential lock for forward rear, center rear & rear rear axles.	0
3762020	O	Rear suspension: Tridem Hendrickson Primaax EX692 69K. 54 in. axle spacing. Air suspension with 10 in. ride height. Steel crossmembers and gussets. Includes air suspension dump valve.	910
3832002	O	Torque rods for 69K PRIMAAX EX using disc brakes. Replacing standard.	33
3832099	O	Track rods: heavy duty for Hendrickson Primaax EX tridem. Replaces standard duty track rods.	36
3839002	O	Air suspension over-inflation valve w/warning light to temporarily raise the frame.	0

Tires & Wheels

4017183	O	Front Tires: Michelin XZY3 425/65R22.5 20PR 44.7 in. Diameter, All Position. 20.6in. SLR.	190
4210151	O	Rear Tires: Michelin X Works D 11R24.5 16PR	480
4900012	O	Rear Tire Quantity: 12	0
5045216	O	Front Wheel: Alcoa 82362 22.5x12.25 aluminum, with Lvl One [TM] finish High Polish, hub-pilot mount. 11400lb. maximum rating. Super single. Standard track axles may be over 102 in. w/425 tires. Air disc brake compatible.	-10
5245275	O	Rear Wheel: Alcoa 98U63 24.5X8.25 AL Ultra One High Polish Wheel.	-204
5850040	O	Wheelguards: all axles.	2
5859007	O	Tridem Rear Axle Wheels: 6 Dura-Bright Mirror Polish Dura-Bright outboard surface of outer dual or single aluminum wheels.	0
5859010	O	Single Front Axle: 2 wheels Dura-Bright Mirror Polish Dura-Bright outboard surface of aluminum wheels.	0
5900012	O	Rear Wheel/Rim Quantity: 12	0

Frame & Equipment

6056600	O	Frame Rails: 10-3/4 x 3-1/2 x 3/8in. Steel 337in. to 416 in. Truck frame weight is 3.48 lb.-in. per pair of rails. Section modulus is 17.80, RBM is 2,132,000 in-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the	365
---------	---	---	-----

Price Level: January 1, 2023

100% Complete

Date: January 18, 2023

Deal: W900 B LOWBED UNIT

Quote Number: QUO-929396-X1D8J1

Printed On: 1/19/2023 11:10:30 AM



Sales Code	Std/ Opt	Description	Weight
		requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	
6141600	O	Full Steel Insert: for 10-5/8 in. or 10-3/4 in. Steel 337 in. to 416 in. or 2nd insert for 11-5/8 in. steel frame. Adds 1,149,000 in-lb to main rail RBM. Truck insert weight is 2.05 lb.-in. per pair of rails. Full frame insert length is equal to wheelbase plus rear frame cutoff plus dimension forward of front axle by model: T660, T680, T800, T880 = 21.26 in.; C500B = bumper setting minus 0.79 in.; W900B = 5.27 in., W900L = 1.50 in., W900S = 3.27 in.; T440/T470 50 in. bumper setting = 21.26 in., T470 73 in. bumper setting = 72.3 in.	741
6303428	O	Bumper: Straight steel box. Chrome. Requires bumper setting code.	211
6319035	O	35 in. Bumper setting. Requires a bumper code.	6
6324025	O	Front tow hook: Center mounted, cast. Requires iron front drive brackets.	28
6390001	S	Steel shackle links.	0
6390110	O	Mudflaps, Front: Extra wide for use w/ tires that are wide base singles.	6
6391201	O	Custom Frame Layout: one chassis CFL A/D: OUTSIDE RH RAIL BOC CFL A/T: AIR TANKS CLEAR OF TRANSMISSION AREA	0
6397001	O	Huck bolts throughout frame, where possible.	0
6405086	O	W9 parallel polished aluminum battery box module w/ integral step. Extended length for use w/ 2010 and later SCR style exhaust. Up to 2 air tanks may mount to bottom of box. Batteries will be oriented perpendicular on rail.	9
6409901	S	Battery box location: LH Side.	0
6451096	O	W9 polished DPF/SCR or CNG cover with step. For use with 2010 or later exhaust systems.	0
6600205	O	Fifth Wheel: Slide, Dealer & Customer-Installed over 36 inches.	0
6679824	O	Width across front tires exceeds 102 inches. Dealer to review delivery constraints w/transporter.	0
6679834	O	Width across rear tires exceeds 102 in. due to combination of wide track rear axles & dual tires. Dealer to review delivery constraints w/transporter.	0
6679915	O	Customer-installed bulkhead and/or headache rack.	0
6690090		FifthWheelRearFixedSetting FW rear/fixed setting behind bogie 9 in	0
6721102	S	Rear mudflap arms: Betts B-25 standard-duty, straight. Includes B1732 mounting brackets as standard.	0
6722000	S	Rear mudflap shields: White plastic antisail w/ Kenworth logo.	0
6743116	O	Tractor Taper bent & welded w/ heavy-duty cross	68

Price Level: January 1, 2023

100% Complete

Date: January 18, 2023

Deal: W900 B LOWBED UNIT

Quote Number: QUO-929396-X1D8J1

Printed On: 1/19/2023 11:10:30 AM



Sales Code	Std/ Opt	Description	Weight
		member. Non-towing end-of-frame configuration.	
6747000	O	Shortest end-of-frame cutoff with specified end-of-frame configuration. Selecting this code will override the overhang dimension found in the Vocational Analysis of Prospector.	0

Fuel Tanks & Equip

7214150	O	Fuel Tank: 150 US gallon 24.5in. aluminum BOC replace. Class 8 fuel tanks w/ o locking caps include an anti-siphon device on the filler neck. A third tank support is required with this tank unless heavy-duty 7 in. wide supports are specified.	55
7216110	O	Fuel Tank: 110 US gallon 24.5in. aluminum BOC add. Class 8 fuel tanks w/ o locking caps include an anti-siphon device on the filler neck. Multiple tank installations include a fuel equalization system w/ dual draw and return lines with a splitter valve located within 6 inches behind the cab. Single draw and return is an option in some cases.	116
7722155	O	Large round DEF tank, 30 gallons. The DEF tank will be located on the side you specified. If you have specific configuration or body builder concerns, please utilize the Custom Frame Layout option. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.	22
7821300	O	Heavy-duty 7in. steel supports/straps for two 24.5in. tanks. Two supports per tank.	36
7840029	O	Polish only two aluminum tanks.	0
7840038	O	Polished cover for 1 DEF tank any size.	3
7850051	O	Number ten 5/8 in. fuel crossover/equalizer line with two breakaway valves without shutoff valve.	6
7889004	O	Position fuel fill beyond rear of sleeper. May have gap between under cab components and fuel tank(s) visible on chassis without full chassis fairings.	0
7889082	O	Polish only 7in. stainless steel straps for two 24.5in. tanks; 2 straps per tank.	0
7889203	S	DEF to fuel fill ratio 2:1 or greater.	0
7889245	S	Anti-siphon device in fuel tank filler neck. For any number of fuel tanks.	0
7889604	S	DEF tank location is LH.	0
7930150	O	Location: 150 gal fuel tank RH behind cab	0
7940110	O	Location: 110 gal fuel tank LH behind cab	0

Cab & Equipment

8025300	O	Cab: AeroCab Curved Glass Conventional. AeroCab includes aluminum & fiberglass fully hucked cab w/ all aluminum bulkhead doors & continuous stainless steel piano-style door hinge & pins. Available only w/ AeroCab sleepers. Not for use on W900 w/ set	0
---------	---	---	---

Price Level: January 1, 2023

100% Complete

Date: January 18, 2023

Deal: W900 B LOWBED UNIT

Quote Number: QUO-929396-X1D8J1

Printed On: 1/19/2023 11:10:30 AM



Sales Code	Std/Opt	Description	Weight
		forward axle. C500B: 123 in. BBC. 74 in. FA to BOC. T660B: 122 in. BBC. 74 in. FA to BOC. T800B: 121 in. BBC. 74 in. FA to BOC. W900B: 120 in. BBC. 90 in. FA to BOC. W900L: 130in. BBC. 100 in. FA to BOC. Incandescent exterior lights include diagnosable bulb detection and warning. Trailer cable on tractors includes integrity detection. Standard features include multiplex wiring for interior lights, automated pre-trip inspection, short and open check diagnostics, and programmable daytime running lights. Warning alarm will sound when lights are left on.	
8049004	O	KW100 Limited Edition 72" Flat Top Limited Edition Package for the Kenworth 100th anniversary year only. Includes black dash, black under dash close-outs, black door pad, and black soft trim with Kenworth 100 logo on sleeper backwall. Also includes Kenworth 100th Anniversary badging on threshold, glove box, door pad and exterior.	0
8057572	O	Sleeper: 72 in. AeroCab FlatTop sleeper.	906
8080137	O	Cab door bearing blocks, top & bottom.	0
8080942	O	Sleeper door, LH/RH w/ sliding window.	19
8090105	S	Hood: Straight Unitglas hood w/ grille & shell use for W900B requires 1200/1430 square in. radiator & export engine, or 1430 square in. radiator & 2007 engine, or 1670 square in. radiator & 2010+ engine.	0
8098206	O	Hood hinge reinforcement.	5
8098404	O	Additional 4 ribs on radiator grille.	2
8158011	O	Espar Airtronic D2 Sleeper or Bunk Heater w/thermostat. Rated for 5,000 ft of elevation	14
8158012	O	Insulated fuel lines for Espar heater.	0
8158016	O	Espar D2 Heater Credit (Pre-Wire only)	0
8178210	O	Heater/Air Conditioner: Separate Units, Cab & Sleeper. W/integral Defrosters & A/C. Separate Heater & A/C In Sleeper. Includes 5 Mode Rotary Control In Dash. 45,000 BTU Cab Heater. Separate 29,000 BTU Sleeper Heater W/AC, Thermostatically Controlled. T660 Includes Filter Media. Includes On/Off Button For Sleeper Unit In Air Flow Control Dial. Parallel Plumbing Is Included W/ All Sleepers And Allows For Independent Control Of Heat Output At Each Heater. Shutoff Valves Are Optional.	0
8190564	O	Air Conditioning Excise Tax: Canadian Registry	0
8201041	O	Steering wheel: 18 in.4-spoke leather. Smartwheel multiplex steering wheel controls.	2
8201200	S	Adjustable telescoping tilt steering column.	0
8203060	O	5 sets of keys. Replaces standard 2 sets of keys.	0

Price Level: January 1, 2023

100% Complete

Date: January 18, 2023

Deal: W900 B LOWBED UNIT

Quote Number: QUO-929396-X1D8J1

Printed On: 1/19/2023 11:10:30 AM



Sales Code	Std/ Opt	Description	Weight
8203070	O	Flip valve on dash w/piping for customer-installed air-operated fifth wheel slide.	8
8203189	O	Switch & Wiring: For Air Cleaner Lights. Lights will be installed by customer, not factory supplied.	0
8205103	O	Information for customer-installed PTO Chelsea 8-bolt.	0
8221136	O	Gauge: Trailer reservoir air pressure gauge.	0
8221137	O	Gauge: Trailer air application gauge.	0
8221138	O	Gauge: Air suspension pressure gauge. For dual leveling valves, not dual read.	0
8221160	O	Gauge: Engine Oil Temperature Gauge With Integral warning light. The NavPlus HD unit includes a virtual engine oil temperature gauge.	0
8222712	O	Gauge: Fuel filter restriction gauge.	0
8222722	O	Gauge: Manifold Pressure Gauge. The NavPlus HD unit includes a virtual manifold pressure gauge.	0
8225656	O	Gauge: Axle oil temperature gauge tri-drive axle.	0
8226667	O	Gauge: Oil Temperature Gauge Transmission. The NavPlus HD unit includes a virtual transmission oil temperature gauge.	0
8240620	O	Canadian instrument package: KPH speedometer replaces MPH.	0
8282004	S	KW Driver Information Center: Includes fuel economy, RPM display, trip information, truck information, diagnostics, gear display, alarm clock.	0
8282009	S	Instrument package: Includes speedometer, tachometer, fuel gauge, engine coolant temperature gauge, engine oil pressure, voltmeter. Class 8 also includes primary & secondary air reservoir gauges & an air application gauge. DEF level gauge and warning lamp are included with 2010+ engines. Engine hour meter and outside air temperature readouts are standard. Primary read out will be MPH. Add 8240620 to switch primary scale to KPH in Canada.	0
8300017	O	Interior Color: KW100 Black w/Legacy Red Accent	0
8330672	O	Interior: KW100 Diamond VIT Cab 72" AeroCab Sleeper. Includes Quiet Cab package, diamond tufted upholstered side and back panels with accent lines, stitched upholstered diamond tufted door and carpeted kick panel, full diamond tufted vinyl headliner, button color matches primary lining color, black rubber floormat. Includes Kenworth NavPlus HD navigation system on 2010 and later engines. Sleeper includes sleeper curtain, full diamond tufted vinyl headliner, diamond tufted upholstered door pads and wall panels with accent lines, button color matches primary lining.	0
8390648	O	Black carpet in cab, replacing floormat.	0
8390748	O	Carpet replacing floormat: Black nylon In sleeper	0

Price Level: January 1, 2023

100% Complete

Date: January 18, 2023

Deal: W900 B LOWBED UNIT

Quote Number: QUO-929396-X1D8J1

Printed On: 1/19/2023 11:10:30 AM



Sales Code	Std/ Opt	Description	Weight
		dressing area.	
8410895	O	Driver Seat: Kenworth Air Cushion Premium Plus HB Limited Edition seats for the Kenworth 100th anniversary year only. Heated two-tone black ultraleather seats with red piping accent, embroidered KW logo, and anniversary tag.	0
8480895	O	Rider Seat: Kenworth Air Cushion Premium Plus HB Limited Edition seats for the Kenworth 100th anniversary year only. Heated two-tone black ultraleather seats with red piping accent, embroidered KW logo, and anniversary tag.	0
8490151	O	Seat Color: KW100 Black w/Legacy Red Accents	0
8497005	O	Air line fitting: At driver seat. Customer-installed air chuck.	4
8498453	O	Dual KW driver seat armrests: Stowable inboard & folding outboard.	2
8498553	O	Dual rider seat armrests: Stowable inboard & folding outboard.	2
8505072	O	Refrigerator/freezer: 72 in. AeroCab VIT & 75 in. sleepers. 12V front loading. Replaces shelves in lower RH cabinet. Indicator light on dash. Standard on 86 inch AeroCab.	42
8505110	O	TV Installation Package: AeroCabs. Low Mounted Includes 12V power outlet, vibration absorbing pad, holddown strap & antenna mounted in roof. 10 in. TV recommended.	6
8520141	O	Premium pocket innerspring mattress on lower bunk.	0
8530237	O	Rubber floormat in tool compartment.	0
8570000	O	LH lower cabinet w/two drawers.	11
8601429	O	Kenworth Radio DEA730 AM/FM/WB/USB, Bluetooth & Sirius-XM Satellite	0
8601880	O	CB Radio: Cobra 29. Includes weatherband w/header mounted quick release. Includes transceiver & separate speaker remote-mounted in headliner & dual CB antennas. Includes sound tracker & illuminated panel.	11
8698998	O	Speakers: Two 5-1/4 in. For sleeper w/fader in radio for volume control to sleeper.	2
8699147	O	Solid post antenna: Mounted on LH cowl. Replaces top-of-cab antenna. Recommended for dump trucks, loggers, & where overcab clearance is limited.	0
8699514	O	Speakers: Four 4 in. x 6 in. high performance. Adds 2 speakers to the Panasonic standard 2. Located in cab header & rear cab corners.	0
8700023	O	Additional 12V accessory plug in sleeper.	0
8700049	O	Logbook holder under dash.	0
8700101	O	Black dash: Replacing trim color dash.	0

Price Level: January 1, 2023
 Deal: W900 B LOWBED UNIT
 Printed On: 1/19/2023 11:10:30 AM

100% Complete

Date: January 18, 2023
 Quote Number: QUO-929396-X1D8J1



Sales Code	Std/Opt	Description	Weight
		W/Diamond trim the dash top, area by the glovebox & lower dash will be black. The trim around the main dash area, above the glove box, the header spear & trim on the doors will be woodgrain.	
8700168	S	Non-self cancelling turn signal: W/column-mounted headlight dimmer switch & intermittent wiper control.	0
8700186	S	Electric LH & RH door locks.	0
8700188	O	Remote Keyless Entry	0
8700405	O	Stainless steel permit panels on cab.	13
8700663	S	Kenworth TruckTech+ The Kenworth Remote Diagnostics system provides the Worlds Best reporting of engine and aftertreatment fault codes, as well as enhanced support for the truck owner through rapid communication of fault severity and recommended actions. This option is Standard on all Heavy Duty Kenworths with a PACCAR MX engine, Cummins X15 engine, PX engine or Natural Gas engine. Optional on Medium Duty Kenworths.	0
8700964	O	Delete KW NavPlus HD System:VIT Diamond Interior	0
8720100	O	Delete Kenworth nameplates from hood. *Do not drill hood*	0
8800400	S	Grabhandle: LH inside door frame above dash.	0
8800401	S	Grabhandle: RH inside door frame above dash.	0
8800733	O	Grabhandle: LH w/ short extension over door.	4
8800734	O	Grabhandle: RH w/ short extension over door.	2
8832115	S	Daylite Door: LH/RH includes RH peeper window	0
8841411	S	Single air horn under cab.	0
8850300	S	Look-Down, Pass. Door, Stainless 8.5x4.4	0
8863570	O	Dual convex heated mirror 8.5 inch w/ offset mounting below regular mirror.	11
8866102	O	Mirror: Dual Prutsman Lighted Mirrors 7 in. x 16 in. Polished Stainless Steel, Thermostatically Controlled & Lighted. Switch Located On Door Pad.	0
8867207	U	MIRROR: DUAL MOTO STNLS STL 7"X16" Narr MIRROR: DUAL MOTO STNLS STL 7"X16" MIRROR: DUAL MOTO STNLS STL 7"X16"	0
8869010	O	Mirror brackets 10 ft load width.	24
8879213	O	Electric-powered LH & RH door window lifts. Switch located on door.	0
8879440	O	Cab door & windshield window cover: In addition	4

Price Level: January 1, 2023

100% Complete

Date: January 18, 2023

Deal: W900 B LOWBED UNIT

Quote Number: QUO-929396-X1D8J1

Printed On: 1/19/2023 11:10:30 AM



Sales Code	Std/Opt	Description	Weight
		to cab/sleeper curtain.	
8879590	O	Fresnel lens for peeper window, RH door 10-1/8 in. X 11-1/8 in. Replaces standard peeper window.	0
8890100	S	One-piece windshield, w/ curved glass.	0
8890139	O	Sunvisor: KW100 Limited Edition Package Stainless Steel Exterior	0
8890290	O	Chrome beading around windows.	0
8890353	O	4 1/2in. rubber wheelwell fender extension.	11
8890872	O	Kenworth cab/sleeper air suspension for use w/ 38/62/72/86 in. AeroCabs only.	0
Lights & Instruments			
9010802	S	Headlamps: Dual Rectangular, extended life halogen	0
9022137	O	Marker Lights: Five, rectangular, LED	0
9030014	O	Turn Signal Lights: LED, mounted on fender.	0
9030052	S	LED Stop,Turn,Tail: With Two LED Backup Lights and With An LED License Plate.	0
9034107	O	Turn Signal Lights: Rectangular mounted mirror bottom, in addition to standard.	2
9049825	O	Customer-installed road/fog lights switch & wiring.	0
9058020	O	Coiled Wire BOC/BOS: Additional 30ft. For Customer-Installed Floodlights - 1st Set.	0
9058037	O	Switch & Wiring for Customer-Installed Floodlight W/O Electrical Pass-Through - 1st Set. Wire Coiled BOC/BOS.	0
9058052	O	Switch & Wiring for Customer-Installed Floodlight : W/O Electrical Pass-Through - 2nd Set. Wire Coiled BOC/BOS.	0
9080200	O	Switch & Wiring: Customer-installed beacon lights w/ additional coiled wire to 20ft. coiled BOC.	0
9090000	O	Daytime Running Lamps.	0
9090027	O	Headlamps to turn on when wipers are active.	0
9090049	S	Omit Brake Light with Engine Brake. Can only be selected when chassis also has engine brake. Cannot be used with options to delete engine brake.	0
9090060	O	LH Courtesy Lamp: On upper skirt to light up step.	0
9090117	O	Marker Lights: Midframe & reflectors mounted standout. Required on tractors where overall length exceeds 30 feet.	22
9090126	O	Electric Backup Alarm: Meets SAE J994 & OSHA requirements.	4

Price Level: January 1, 2023

100% Complete

Date: January 18, 2023

Deal: W900 B LOWBED UNIT

Quote Number: QUO-929396-X1D8J1

Printed On: 1/19/2023 11:10:30 AM



Sales Code	Std/ Opt	Description	Weight
9090302	O	Junction Box: Mounted Behind Cab or Sleeper Not Mounted at End of Frame.	1
9090845	O	Circuit Breakers: Replacing fuses. Does not apply to any 5-amp fuse box position. Brakers include stop/brake/turn, tail lamp, high & low beams, marker/clearance lamps, horn, fuel heat, gauges, air dryer, HVAC controls, panel lamps. Some circuits will remain fuses.	0
Air Equipment			
9101245	O	Air Dryer: Bendix Dual AD-IS Everflow heated. PuraGuard	46
9108001	S	Moisture ejection valve w/ pull cable drain.	0
9110068	S	Air & Electrical Supply Kits: Tractor LH frame- mounted kit w/ hosetenna. Includes composite gladhand/light plug holder. Kit includes dash mounted trailer air supply valve, trailer hand control valve, and hoses/fittings for the valves. Dash mounted parking brake valve and tractor protection valve are standard. Air lines are detachable at one end only, light lines are detachable at both ends. Conspicuity components are standard. Use code 9140177 for short hosetenna option, this is not available on the T3 series.	0
9120014	O	Air and light line length 14 feet	0
9140020	S	Nylon air tubing in frame & cab, excluding hoses subject to excessive heat or flexing.	0
9140238	O	Locate air dryer outside RH rail BOC. This code requires the use of a custom frame layout code.	0
9140288	O	Air tanks: clear of transmission area. This code requires the use of a custom frame layout code.	0
9140328	S	Trailer ABS electric supply through SAE J560 7-pin connector per TMC RP137).	0
9140700	S	Standard hosetenna Bracket Location. Hosetenna bracket will be located plus or minus six inches from standard location of eight inches.	0
Extended Warranty			
9200021	S	Base Warranty - Standard Service Heavy Duty 12 months / 100,000 miles / 160,000 km.	0
9212611	S	24 Month TruckTech+ Subscription for Cummins Engines	0
9220001	O	Base Warranty: Emissions 5YR/100K MI - EPA Engine (Does not include CARB Clean Idle sticker)	0
Miscellaneous			
9407014	U	PREPAID FREIGHT ADJUSTMENT <i>Narr PREPAID FREIGHT ADJUSTMENT PREPAID FREIGHT ADJUSTMENT</i>	0
9409852	S	GHG Secondary Manufacturer: Does Not Apply	0



Sales Code	Std/Opt	Description	Weight
9490003	O	Additional lead time required for off highway & /or specialty component truck.	0
9490206	O	Warning triangle reflector kit: Shipped loose. Kit consists of 3 triangles in plastic carrying case. Not floor mounted.	4
9490413	O	One 5 lb. dry chemical type fire extinguisher mounted LH of sleeper toolbox. Class ABC. Not for use with 40 in. sleeper.	11

Promotions

9510860	U	2023 SCHEDULING CODE - RENTON <i>Narr 2023 SCHEDULING CODE - RENTON</i>	0
9510876	U	TC565 Q2 2023 CLASS 8 SALES PROGRAM <i>Narr TC565 Q2 2023 CLASS 8 SALES PROGRAM</i>	0

Paint

9700000	O	Paint color number(s). N9702 A - L2130 BLACK N9720 FRAME N0001 BLACK	0
9943004	O	Bumper Unpainted	0
9943055	O	Sleeper Pearl/Metallic Paint	0
9944821	O	1 - Color Paint - Sleeper Color will be White if no other color is specified.	0
9965510	S	Base coat/clear coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0
9999945	O	Charge chassis in United States dollars.	0

Order Comments

Total Weight

24,418

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change

Price Level: January 1, 2023
Deal: W900 B LOWBED UNIT
Printed On: 1/19/2023 11:10:30 AM

100% Complete

Date: January 18, 2023
Quote Number: QUO-929396-X1D8J1



without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: NONE

Final Destinations	Quantity
I018 - INLAND - LANGLEY 26770 GLOUCESTER WAY LANGLEY, British Columbia V4W 3V6	1

708



Chassis

VIN	1NKWX4EX6RR983860	Months in service	1
Model	W900B	In-service date	04/10/2024
Intended service	HEAVY EQUIPMENT TRANSPORT	Build date	12/04/2023

Customer

Name	Spruce Hollow Heavy Haul Ltd.
City	Abbotsford
State/Province	BC

Selling dealer

Name	I018 - INLAND KENWORTH - LANGLEY
City	LANGLEY
State/Province	BRITISH COLUMBIA

Servicing dealer

Name	I018 - INLAND KENWORTH - LANGLEY
City	LANGLEY
State/Province	BRITISH COLUMBIA

Odometer and Engine Hours

System Date	Engine hours	Current odometer	Odometer type
05/02/2024	0	---	---

Components

Engine

Engine make	Engine model	Engine Series	Emissions Type	Engine serial	Engine family	Engine model year	Engine build date
CUMMINS	X15-PERFORMAN CE	2021	EPA	80577705	PCEXH0912XC C	2023	09/29/2023

Transmission

Transmission make	Transmission model	Transmission serial
FULLER	RTLO20918B	P1624719

DPF

DPF make	DPF model	DPF serial
CUMMINS	DPF/SCR	6D264237522

Axles

Steer Axle Make	Steer Axle Model	Steer Axle Serial
PACCAR	FX-20	239L04436

Dual Steer Axle Make	Dual Steer Axle Model	Dual Steer Axle Serial
N/A	N/A	N/A

Forward Rear Axle Make	Forward Rear Axle Model	Forward Rear Axle Serial
MERITOR	RZ-XX-166WT	FOR08752299

Rear Rear Axle Make	Rear Rear Axle Model	Rear Rear Axle Serial
MERITOR	RZ-XX-166WT	FOR08752298

Center Rear Axle	Center Rear Axle	Center Rear Axle Serial

Pusher Axle1 Make	Pusher Axle1 Model	Pusher Axle1 Serial
N/A	N/A	N/A

Pusher Axle2 Make	Pusher Axle2 Model	Pusher Axle2 Serial
N/A	N/A	N/A

Pusher Axle3 Make	Pusher Axle3 Model	Pusher Axle3 Serial
N/A	N/A	N/A

Pusher Axle4 Make	Pusher Axle4 Model	Pusher Axle4 Serial
N/A	N/A	N/A

Tag Axle Make	Tag Axle Model	Tag Axle Serial
N/A	N/A	N/A

Make	Model	FOR08752
MERITOR	RZ-XX-166WT	297

Campaigns

Campaign code	Description	Campaign status	Expiration date	Repair type	Type
PDI	Pre-Delivery Inspection	COMPLETED	---	FIX AS FAIL	VEHICLE

Truck Notes

Truck notes	Description
Truck note 1	KENWORTH TRUCKTECH+ (REMOTE DIAGNOSTICS)

Base Warranty

Warranty code	Warranty description	Max coverage months	Max coverage mileage	Max coverage kilometers	Max engine hours	Active/Expired
Warranty Code 1	BASE WARR: STANDARD SERVICE HEAVY DUTY 12 MONTHS/100K MI/160K KM	12	100000	160000		

Extended Warranty

Warranty code	Warranty description	Max coverage months	Max coverage mileage	Max coverage kilometers	Max engine hours	Active/Expired
Warranty Code 1	EW: CA RAD/CAAC 5YR/640K KM	60	400000	640000		

Supplier Extended Warranty

[See Also Cummins RapidServe or

Eaton Roadranger to verify warranty coverage]

Warranty code	Warranty description	Max coverage months	Max coverage mileage	Max coverage kilometers	Max engine hours	Active/Expired
No items found						