



Queensland  
Government



# Certificate of Inspection Caravans and Trailers

(over 3.5 tonne ATM to and 10.0 tonne ATM)  
Transport Operations (Road Use Management) Act 1995

## Owner and vehicle details

Vehicle Owner's name and address

WORLD WELDING  
PO Box 1808  
MOUNT ISA

Postcode 4825

Plate number (if applicable) State

VIN/Chassis number

6F8000068L101814

Make

LUSTY EONS

Body shape

SIDE TIPPER

Current Gas Certificate number (if applicable)

## Compliance type

Compliance  
Plate ☒

Import  
Plate ☐

Other ☐

Give details

Date on Plate Vehicle

0.219 SILVER

Tare

ATM (if applicable)

42000

## Results of inspection

Please indicate: Pass ☒

Fail ☒

First  
inspection

Final  
inspection

Identification

Modifications

Lights and electrical components

Body and chassis

Suspension

Wheels and tyres

Brakes

Tow couplings

Details of other items rejected

Mobile AIS unit - location of vehicle inspection

## First inspection

Result ☒

Inspection date

29.8.24

Inspection time

1:00 am

Mobile AIS unit  
odometer reading

Signature of Examiner

DALE BLACKBURN

Examiner's no.

27554

## Final inspection (must not be more than 14 days from date of first inspection)

Result ☐

Inspection date

/ /

Inspection time

: am  
pm

Mobile AIS unit  
odometer reading

Signature of Examiner

Examiner's no.

## Inspection Station details

Name and location

ATS 5254 CROCODILE  
CREW, BOTTLE

Postcode 4818

Approved Inspection  
Station Number

12333

Mobile AIS unit Registration Number

## Certification

Approved Examiner - I have inspected the vehicle indicated on this form in strict accordance with the guidelines set out in the Code of Practice Vehicle Inspection Guidelines and have found no defect that would affect its safe use on the road and it meets the requirements of the Transport Operations (Road Use Management) Act.

Inspected by - Signature of Examiner

DALE BLACKBURN

Date

29.8.24

Name of Examiner (please print)

DALE BLACKBURN

Examiner's no.

27554

Proprietor - I have ensured that the requirements of the Transport Operations (Road Use Management) Act relating to the issue of this certificate have been complied with.

Issued by - Signature of Proprietor

DALE BLACKBURN

Date

29.8.24

Name of Proprietor (please print)

DALE BLACKBURN

- Original (Pink) - This copy for registration of vehicle
- Triplicate (Green) - To be given to owner where a further inspection is required

- Duplicate (Yellow) - Purchaser's/ Owner's copy
- Quadruplicate (White) - Book copy

**Privacy Statement:** The Department of Transport and Main Roads is collecting the information on this form for the purposes of managing the Department of Transport and Main Roads' vehicle register. This information is authorised or required by the Transport Operations (Road Use Management) Act. The Department of Transport and Main Roads or its agents usually gives some or all of this information to vehicle insurers, statutory entities, lawyers, insolvency entities, persons involved in vehicle accidents/incidents or vehicle manufacturers or their employees or agents and to or through interstate registration authorities. Your personal details will not be disclosed to any other third party without your consent unless required or authorised by law.



WORLD WELDING & TRANSPORT SERVICES

## Maintenance Report

VEHICLE:


TL112

DATE:

6/9/24

HRS

KLM



### DESCRIPTION OF MAINTENANCE:

BACK GUAGE AND RE-WELD CRACKS IN  
BOLT SCREWS OF CHASSIS

BACK GUAGE & REWELD CRACKS IN COMB PLATES  
ON HYDRAULIC MOUNTS (ON TUM).

NAME:

FITZG


SIGNATURE:

FF



## Maintenance Report

DATE: 4-9-27



**DESCRIPTION OF MAINTENANCE:**

- Replace 24/30 booster on LHS center axle
- Fit rebuilt Ringfeder & boss to rear of unit
- Checkover
- Replace hydraulic couplings on rear of unit
- Check bearings

NAME: MARK ALLEN

SIGNATURE: \_\_\_\_\_





# TRAILER & DOLLY SERVICE SHEET

01814

DATE 10-9-24 START TIME \_\_\_\_\_ FINISH TIME \_\_\_\_\_  
FLEET NO 72112 KM'S N/A HRS \_\_\_\_\_

JOB NO \_\_\_\_\_  
REGO 4B65ED

Service Items - Mechanic/Fitters to complete Initial = OK, X Repair, NA = Not Applicable		A Service	B Service	C Service
Local Trailers	40000km/365 days	7 DAYS	14 DAYS	40000KM
Linehaul Trailers	15000km 10 days 150000km/365days		15000KM	150000KM
1	Check faults noted on daily prestart and repair as necessary			MLL
2	Check fleet numbers are serviceable			MH
3	Record Hub meter reading			N/A
4	Lubricate Container Pins			N/A
5	Check operation & condition of all lights/reflectors			MH
6	Apply Air Check for leaks from boosters, valves & air lines			MH
7	Adjust brakes , visually inspect components			MH
8	Check air cells for air leaks and deterioration			MH
9	Drain all air tanks, report if any oil is present in system			MH
10	Grease trailer incl. brake cams, slack adjusters, landing legs, ring feeder & other grease points			MH
11	Check hoist mounting bolts, hoses, coupling			MH
12	Check number plate & rego label security. Check that rego label is current			MH
13	Check condition of front air connections, light plug base & electrical lead			MH
14	Check security of spare wheels & spare wheel carrier/gate rack			N/A
15	Check condition & security of all mudflaps, mudguards, brackets & spray suppression			MH
16	Check landing legs for damage & security			MH
17	Check sub frame & cross members for cracks, damage & security			MH
18	Check condition, position & security of all air hoses			MH

19	Check brake linings & drums for wear. Check hub seals for leakage
20	Check security of height control valves and links & adjust if required
Check skid plate/king pin security & condition, check draw bar/bushes and towing eye NOTE: If draw bar eye bolt is found loose, it is not to be retorqued and must be removed and replaced and draw bar eye boss to be checked for tolerances	
21	checked for tolerances
22	Check wheel nut tensions, check valve stem alignment
23	Check all tyre pressures and refit valve caps (including spare) report abnormal wear
24	Check condition & security of rear marker signs
25	Check ring feeder condition, operation & security
26	Lubricate twist locks & check operation & security of pedestals, straighten handles as required
27	Check condition & security of rope rails, gate pockets, winch rails & straps
28	Check condition & security of floor and associated components
29	Raise trailer by rear frame & individually inspect rocker/radius bushes, wear pads, air cells for wear
30	Check security & bolt tension od airbag suspension hangers & radius rod arms
31	Raise wheel assembly & check bearings for free play by "feel" only & adjust as required
32	Indicate on below drawing wheel bearings that are replaced, checked and/or adjusted

MH
MH
MH
MH
MH
MH
MH
N/A
N/A
MH
MH
MH
MH
MH



33	Check brake linings & drums for wear whilst hubs are removed
34	Check hubs for cracks and tapered shoulders for wear
35	Remove bearings and clean/inspect for reuse
36	Replace mudflaps & decals as required
37	Remove s/cam slack adjuster pins and rotate/lubricate
38	Pack bearings with fresh grease & reassemble

MH
MH
N/A
MH
N/A
N/A

Initial if adjusted - Tick if OK

PLEASE COMPLETE PAGE 2



Tradesperson Name	MATT H	Signature	<i>[Signature]</i>
		Date	10-9-24

PLEASE COMPLETE PAGE 2











## TRAILER & DOLLY SERVICE SHEET

Work/Repairs carried out


List any defect found


Part No/Consumables	Qty	Part No/Consumables	Qty

Tradesperson Name	MAT H	Signature	MAT H
		Date	10-10-24

ENTERED  
DATE 6/11/24 BY DF




**WORLD WELDING & TRANSPORT SERVICES**

## Maintenance Report

VEHICLE: 72112 DATE: 30-10-24

HRS \_\_\_\_\_

KLM N/A



**DESCRIPTION OF MAINTENANCE:**

\* REMOVE DAMAGED RING FEEDER

NAME: WATT H

SIGNATURE: 









WORLD WELDING & TRANSPORT SERVICES

## Maintenance Report


VEHICLE: TL 112

DATE: 24-11-24

HRS: \_\_\_\_\_

KLM: \_\_\_\_\_

DESCRIPTION OF MAINTENANCE:



\* CHANGE FLAT TIRE ON MIDDLE  
AXLE RHS

\* REPLACE WORN TIRES ON REAR  
AXLE LHS WITH NEW ONES (CARGO POWER)

\* INSTALL NEW WHEEL HUB ASSEMBLY  
TO REAR AXLE LHS

\* INSTALL NEW BRAKE CALIPER AND  
BRAKE PADS TO REAR AXLE LHS

NAME: Matt H

SIGNATURE: [Signature]



WORLD WELDING & TRANSPORT SERVICES


## Maintenance Report

VEHICLE: 18 TL112

DATE: 5/12/24

HRS: \_\_\_\_\_

KLM: \_\_\_\_\_



### DESCRIPTION OF MAINTENANCE:

x Replace Caliper Back drivers Axle (Adjustment screw damaged)

# Middle axle passenger inspect for movement Brakes worn

x Replace passenger Front axle Caliper due to damage

NAME: Leonardo Flores

SIGNATURE: [Signature]





DATE 15-12-24

START TIME \_\_\_\_\_ FINISH TIME \_\_\_\_\_

JOB NO \_\_\_\_\_


FLEET NO 72112

KM'S 214 HRS           

REGO \_\_\_\_\_

Service Items - Mechanic/Fitters to complete Initial = OK, X Repair, NA = Not Applicable		A Service	B Service	C Service
Local Trailers	40000km/365 days	7 DAYS	14 DAYS	40000KM
Linehaul Trailers	15000km 10 days 150000km/365days		15000KM	150000KM
1	Check faults noted on daily prestart and repair as necessary	MH		
2	Check fleet numbers are serviceable	MH		
3	Record Hub meter reading	N/A		
4	Lubricate Container Pins	N/A		
5	Check operation & condition of all lights/reflectors	MH		
6	Apply Air Check for leaks from boosters, valves & air lines	MH		
7	Adjust brakes , visually inspect components	MH		
8	Check air cells for air leaks and deterioration	MH		
9	Drain all air tanks, report if any oil is present in system	MH		
10	Grease trailer incl. brake cams, slack adjusters, landing legs, ring feeder & other grease points	MH		
11	Check hoist mounting bolts, hoses, coupling	MH		
12	Check number plate & rego label security. Check that rego label is current	MH		
13	Check condition of front air connections, light plug base & electrical lead	MH		
14	Check security of spare wheels & spare wheel carrier/gate rack	N/A		
15	Check condition & security of all mudflaps, mudguards, brackets & spray suppression	MH		
16	Check landing legs for damage & security	MH		
17	Check sub frame & cross members for cracks, damage & security	MH		
18	Check condition, position & security of all air hoses	MH		

19	Check brake linings & drums for wear. Check hub seals for leakage
20	Check security of height control valves and links & adjust if required
21	Check skid plate/king pin security & condition, check draw bar/bushes and towing eye eye bolt is found loose, it is not to be retorqued and must be removed and replaced and draw bar eye boss to be checked for tolerances
22	Check wheel nut tensions, check valve stem alignment
23	Check all tyre pressures and refit valve caps (including spare) report abnormal wear
24	Check condition & security of rear marker signs
25	Check ring feeder condition, operation & security
26	Lubricate twist locks & check operation & security of pedestals, straighten handles as required
27	Check condition & security of rope rails, gate pockets, winch rails & straps
28	Check condition & security of floor and associated components
29	Raise trailer by rear frame & individually inspect rocker/radius bushes, wear pads, air cells for wear
30	Check security & bolt tension of airbag suspension hangers & radius rod arms
31	Raise wheel assembly & check bearings for free play by "feel" only & adjust as required
32	Indicate on below drawing wheel bearings that are replaced, checked and/or adjusted

[illegible]


rear

- 33 Check brake linings & drums for wear whilst hubs are removed
- 34 Check hubs for cracks and tapered shoulders for wear
- 35 Remove bearings and clean/inspect for reuse
- 36 Replace mudflaps & decals as required
- 37 Remove s/cam slack adjuster pins and rotate/lubricate
- 38 Pack bearings with fresh grease & reassemble


Initial if adjusted - Tick if OK

PLEASE COMPLETE PAGE 2

[illegible][illegible]

Tradesperson Name	MAT 14	Signature	
		Date	15-12-24




## TRAILER & DOLLY SERVICE SHEET

DATE 21-12-24 START TIME \_\_\_\_\_ FINISH TIME \_\_\_\_\_  
FLEET NO 72112 KM'S N/A HRS \_\_\_\_\_

JOB NO \_\_\_\_\_  
REGO \_\_\_\_\_

Service Items - Mechanic/Fitters to complete Initial = OK, X Repair, NA = Not Applicable		A Service	B Service	C Service
Local Trailers	40000km/365 days	7 DAYS	14 DAYS	40000KM
Linehaul Trailers	15000km 10 days 150000km/365days		15000KM	150000KM
1	Check faults noted on daily prestart and repair as necessary	MH		
2	Check fleet numbers are serviceable	MH		
3	Record Hub meter reading	N/A		
4	Lubricate Container Pins	N/A		
5	Check operation & condition of all lights/reflectors	MH		
6	Apply Air Check for leaks from boosters, valves & air lines	MH		
7	Adjust brakes , visually inspect components	MH		
8	Check air cells for air leaks and deterioration	MH		
9	Drain all air tanks, report if any oil is present in system	MH		
10	Grease trailer incl. brake cams, slack adjusters, landing legs, ring feeder & other grease points	MH		
11	Check hoist mounting bolts, hoses, coupling	MH		
12	Check number plate & rego label security. Check that rego label is current	MH		
13	Check condition of front air connections, light plug base & electrical lead	MH		
14	Check security of spare wheels & spare wheel carrier/gate rack	N/A		
15	Check condition & security of all mudflaps, mudguards, brackets & spray suppression	MH		
16	Check landing legs for damage & security	MH		
17	Check sub frame & cross members for cracks, damage & security	MH		
18	Check condition, position & security of all air hoses	MH		

19	Check brake linings & drums for wear. Check hub seals for leakage
20	Check security of height control valves and links & adjust if required
21	Check skid plate/king pin security & condition, check draw bar/bushes and towing eye eye bolt is found loose, it is not to be retorqued and must be removed and replaced and draw bar eye boss to be checked for tolerances
22	Check wheel nut tensions, check valve stem alignment
23	Check all tyre pressures and refit valve caps (including spare) report abnormal wear
24	Check condition & security of rear marker signs
25	Check ring feeder condition, operation & security
26	Lubricate twist locks & check operation & security of pedestals, straighten handles as required
27	Check condition & security of rope rails, gate pockets, winch rails & straps
28	Check condition & security of floor and associated components
29	Raise trailer by rear frame & individually inspect rocker/radius bushes, wear pads, air cells for wear
30	Check security & bolt tension of airbag suspension hangers & radius rod arms
31	Raise wheel assembly & check bearings for free play by "feel" only & adjust as required
32	Indicate on below drawing wheel bearings that are replaced, checked and/or adjusted

[illegible]

- 33 Check brake linings & drums for wear whilst hubs are removed
- 34 Check hubs for cracks and tapered shoulders for wear
- 35 Remove bearings and clean/inspect for reuse
- 36 Replace mudflaps & decals as required
- 37 Remove s/cam slack adjuster pins and rotate/lubricate
- 38 Pack bearings with fresh grease & reassemble


Initial if adjusted - Tick if OK

PLEASE COMPLETE PAGE 2

## TRAILER & DOLLY SERVICE SHEET

Work/Repairs carried out

- \* CHECK & GREASE KING PIN
- \* TIGHTEN LOOSE U-BOLTS ON FRONT AXLE RHS.

[illegible][illegible]

Tradesperson Name	<i>M. H.</i>	Signature	<i>[Signature]</i>
		Date	<i>24-12-24</i>