

## **Vehicle Description**

Engine: Cummins ISX E5 SCR ADR80/03 550hp @ 1850lbft Torque

Transmission: Eaton RTLO-22918B eighteen speed Front Axle: Meritor MFS73 (7,300 kg capacity.)

Front Suspension: 7.2t multi leaf front springs

Rear Axle: Meritor RT52-185GP Series (23.6t capacity.) Ratio 4.89:1

Rear Suspension: Kenworth KW6-60A 21 Low 10.5" (21t capacity.)

Rear Suspension: Kenworth KW6-60A 21 Low 10.5" (21t capacity.)

Frame: 5,500mm Wheelbase, 273mm x 89mm x 9.5mm chassis rail
Full length 251mm x73mm x 6mm insert

Wheels and Tyres; Steer Michelin 385/65R 22.5 X Multiway XZE, Alcoa Polished 12.25x 22.5 285PCD

Drive Michelin 11R22.5 XDY3, Alco Dura bright 8x 22.5 285PCD

Fuel Tanks: 1 x 450litre RHF 625mm diameter polished round aluminium tanks

1 x 450litre LHF & 1x 450litre LHR 625 diameter polished round aluminium tank. 1 x 170litre RHR 625mm diameter polished round stainless steel AdBlue tank 1 x 220lt RHRR 625mm diameter polished round aluminium hydraulic tank

Sleeper 36 inch mid roof integrated Sleeper

Paint: Cab & Sleeper in Ice White
Chassis in Black

 Rating:
 GVM:
 28,000Kg
 GVM

 GCM:
 80,000Kg
 B Double

GCM: 80,000Kg. B Double
163,000Kg Road Train (subject to engineering approval

## Refer Attached Specifications Sheet

## **Dealer Fitted Items**

- Holland FW70 fixed plate QRL T/Table.
- Suzie air & electrical lines with glad hand fittings.
- Stoodley rubber mat drive Guards
- Stoodley hydraulics to suit triple side tippers
- Chassis deck plate front of T/Table
- Radio CD/MP3/ Blue Tooth
- Electrophone UHF
- Powder coated King 4 post alloy FUPS bull bar with road train signs
- LED Head lights
- · Cab floor mats
- Canvas seat covers
- First aid kit
- Safety triangles
- Window tint
- 1.5kg fire extinguisher in cab
- 16lt draw fridge under passenger seat
- 2 x Hella LED driving lights mounted on bull bar
- · 2 stainless vents in battery box
- Cab dust blower

Refer Attached Specifications Sheet