

Vehicle Inspection Certificate Number: 68P0AE84

Start Date / Time: Jun 9, 2026, 1:40 PM

End Date / Time: Jun 9, 2026, 2:31 PM

VEHICLE/ENGINE INFORMATION	CHASSIS
Plate#: W8905A	Year: 2012
VIN: 2LDHG2836CF053466	Make: LODE KING
GVWR(kg): 38000	Model: B-TRAIN LEAD
Odometer:	Fleet ID:

SAFETY INSPECTION RESULT	PASS
--------------------------	------

SAFETY SYSTEM INSPECTION RESULTS

All Safety System Components Passed Inspection
--

MANDATORY ITEMS

Inspection Item	Result
Axle 1, Driver Side, Inner Tire	
Tire Tread Depth (mm)	8
Initial Tire Pressure (kPa)	700
Axle 1, Driver Side, Outer Tire	
Tire Tread Depth (mm)	8
Initial Tire Pressure (kPa)	700
Drum Brakes (Limited Inspection) Bolted/riveted block	
Shoe Lining Thickness (mm)	10
Drum Inside Diameter (mm)	419.79
Within OEM specifications?	Yes
S-Cam Drum Brakes (Limited Inspection)	
Chamber Type (size)	30
Brake Stroke (mm)	38

Inspection Item	Result
Axle 1, Passenger Side, Inner Tire	
Tire Tread Depth (mm)	8
Initial Tire Pressure (kPa)	700
Axle 1, Passenger Side, Outer Tire	
Tire Tread Depth (mm)	9
Initial Tire Pressure (kPa)	700
Drum Brakes (Limited Inspection) Bolted/riveted block	
Shoe Lining Thickness (mm)	11
Drum Inside Diameter (mm)	419.7
Within OEM specifications?	Yes
S-Cam Drum Brakes (Limited Inspection)	
Chamber Type (size)	30
Brake Stroke (mm)	38

Inspection Item	Result
Axle 2, Driver Side, Inner Tire	
Tire Tread Depth (mm)	11
Initial Tire Pressure (kPa)	700
Axle 2, Driver Side, Outer Tire	
Tire Tread Depth (mm)	8
Initial Tire Pressure (kPa)	700

Inspection Item	Result
Axle 2, Passenger Side, Inner Tire	
Tire Tread Depth (mm)	10
Initial Tire Pressure (kPa)	700
Axle 2, Passenger Side, Outer Tire	
Tire Tread Depth (mm)	10
Initial Tire Pressure (kPa)	700

Drum Brakes (Limited Inspection) Bolted/riveted block	
Shoe Lining Thickness (mm)	11
Drum Inside Diameter (mm)	420.31
Within OEM specifications?	Yes
S-Cam Drum Brakes (Limited Inspection)	
Chamber Type (size)	30
Brake Stroke (mm)	38

Drum Brakes (Limited Inspection) Bolted/riveted block	
Shoe Lining Thickness (mm)	10
Drum Inside Diameter (mm)	419.7
Within OEM specifications?	Yes
S-Cam Drum Brakes (Limited Inspection)	
Chamber Type (size)	30
Brake Stroke (mm)	38

Inspection Item	Result
Axle 3, Driver Side, Inner Tire	
Tire Tread Depth (mm)	13
Initial Tire Pressure (kPa)	700
Axle 3, Driver Side, Outer Tire	
Tire Tread Depth (mm)	13
Initial Tire Pressure (kPa)	700
Drum Brakes (Limited Inspection) Bolted/riveted block	
Shoe Lining Thickness (mm)	9
Drum Inside Diameter (mm)	420.03
Within OEM specifications?	Yes
S-Cam Drum Brakes (Limited Inspection)	
Chamber Type (size)	30
Brake Stroke (mm)	38

Inspection Item	Result
Axle 3, Passenger Side, Inner Tire	
Tire Tread Depth (mm)	7
Initial Tire Pressure (kPa)	700
Axle 3, Passenger Side, Outer Tire	
Tire Tread Depth (mm)	8
Initial Tire Pressure (kPa)	700
Drum Brakes (Limited Inspection) Bolted/riveted block	
Shoe Lining Thickness (mm)	10
Drum Inside Diameter (mm)	420.25
Within OEM specifications?	Yes
S-Cam Drum Brakes (Limited Inspection)	
Chamber Type (size)	30
Brake Stroke (mm)	38

Vehicle Inspection Centre #: 15913	Technician #: 362238
WYSS DIESEL INC.	Name: RILEY O'BRIEN
14245 CONCESSION 10-11 RD	Report Number: 347
CRYSLER, ON K0A1R0	Tablet ID: 8102
613-884-1660	STO ID/Account: 15008660
Software Version: 2025.06.18.1	Trade Code: 310T, 310S

Vehicle Inspection Questions? Call the Public Contact Centre 1-833-420-2103 or go to <https://www.ontario.ca/page/driveon-emissions-and-safety-inspection-program>